

Virgilio Cocianni
Remediation Manager

Schlumberger
205 Industrial Boulevard
Sugar Land, TX 77478
Tel: (281) 285-4747

March 31, 2015

Mr. Jim Griswold
Environmental Bureau
New Mexico Oil Conservation Division
1220 South St. Francis Drive
Santa Fe, New Mexico 87505

Re: 2014 Annual Groundwater Monitoring Report, Former Dowell Schlumberger Facility, 507 East Richey Avenue, Artesia, Eddy County, New Mexico. Discharge Permit GW-114.

Dear Mr. Griswold,

Enclosed please find the Annual Groundwater Monitoring Report for the Former Dowell Schlumberger Facility in Artesia, New Mexico.

The Discharge Permit GW-114 renewal application was submitted to NMOCD on July 15, 2013 and Schlumberger kindly requests a status update.

Should you have any questions regarding the enclosed submittal or the Discharge Permit renewal, please contact me at (281) 285-4747. I can also be reached by e-mail at cocianni-v@slb.com.

I look forward to our continued work with you.

Sincerely,



Virgilio Cocianni
Remediation Manager

Enclosure

c: Jim Strunk, The Dow Chemical Company
Cathy Barnett, CH2M HILL
Jeffrey Minchak, CH2M HILL

2014 Annual Groundwater Monitoring Report Former Dowell Schlumberger Facility Artesia, New Mexico

**507 East Richey Avenue
Artesia, Eddy County, New Mexico**

Prepared for
**Schlumberger Technology Corporation and
The Dow Chemical Company**

March 2015

CH2MHILL®

3721 Rutledge Road NE, Suite B-1
Albuquerque, NM 87109
(505) 884-5600

Contents

Acronyms and Abbreviations.....	vii
Introduction	1-1
Site Background.....	2-1
2.1 Site Description and History	2-1
2.2 Geology and Hydrogeology.....	2-2
2.2.1 Regional Geology and Hydrogeology.....	2-2
2.2.2 Site Geology and Hydrogeology.....	2-3
2.3 Modifications to the Sitewide Activities	2-3
2014 Site Activities.....	3-1
3.1 Groundwater Monitoring Activities.....	3-1
3.1.1 Depth-to-Water Measurements and Groundwater Sampling.....	3-1
3.2 Groundwater Treatment System Testing	3-2
3.2.1 Groundwater Extraction and Treatment System.....	3-2
3.3 Closure of Former Wash Bay SVE System.....	3-2
3.4 Well Installation	3-2
3.4.1 Injection Wells	3-2
3.4.2 Extraction Well.....	3-3
3.4.3 Monitoring Well.....	3-3
3.5 Sodium Permanganate Injections.....	3-3
Results and Discussion	4-1
4.1 Groundwater Elevation and Gradient.....	4-1
4.2 Groundwater Analytical Results	4-1
4.3 Sodium Permanganate Injections.....	4-2
Conclusions and Recommendations.....	5-1
5.1 Conclusions	5-1
5.2 Recommendations for Future Activities	5-1
5.2.1 Install Upgraded Groundwater Treatment Facility.....	5-1
5.2.2 Groundwater Monitoring	5-1
References.....	6-1

Tables

1	Substrate Injection Summary
2	Groundwater Elevation Data - 2014
3	Summary of Groundwater Analytical Results - 2014

Figures

1	Site Location Map
2	Site Plan
3	Potentiometric Surface Map - April 2014
4	Potentiometric Surface Map - November 2014
5	Isopleth Map for 1,1-DCA - April 2014

- 6 Isopleth Map for 1,1-DCE - April 2014
- 7 Isopleth Map for 1,1-DCE - October 2014
- 8 Isopleth Map for PCE - April 2014
- 9 Isopleth Map for PCE - October 2014
- 10 Isopleth Map for Naphthalene - April 2014
- 11 Isopleth Map for Naphthalene - October 2014

Appendixes

- A Work Plan Amendments and NMOCD Correspondence
- B NMOSE Well Permits, Soil Boring Logs, and Well Completion Diagrams
- C Analytical Laboratory Reports
- D Data Quality Evaluation Memorandum

Acronyms and Abbreviations

bgs	below ground surface
COC	contaminant of concern
CVOC	chlorinated volatile organic compound
1,1-DCA	1,1-dichloroethane
1,1-DCE	1,1-dichloroethene
Dowell	a defunct joint venture between Schlumberger Technology Corporation and The Dow Chemical Company
GAC	granular activated carbon
ID	inside diameter
ISCO	in situ chemical oxidation
IJ	injection well
mg/L	milligrams per liter
NaMnO ₄	sodium permanganate
NEWP	National Exploration Wells and Pumps
NMED	New Mexico Environment Department
NMOCD	New Mexico Oil Conservation Division
NMOSE	New Mexico Office of the State Engineer
NMWQCC	New Mexico Water Quality Control Commission
NTU	nephelometric turbidity units
PCE	tetrachloroethene
PVC	polyvinyl chloride
SCH40	schedule 40
site	Former Dowell Schlumberger Facility, Artesia, New Mexico
STC	Schlumberger Technology Corporation
SVE	soil vapor extraction
VOC	volatile organic compound
USCS	Unified Soil Classification System
USEPA	United States Environmental Protection Agency
UST	underground storage tank
USTB	Underground Storage Tank Bureau
ZVI	zero-valent iron

Introduction

CH2M HILL has completed the 2014 groundwater monitoring program at the Former Dowell Schlumberger Facility located in Artesia, New Mexico (the site). The site is regulated by the New Mexico Oil Conservation Division (NMOCD) under Discharge Permit GW-114 and is located at 507 East Richey Avenue, Artesia, Eddy County, New Mexico. The site location is shown in **Figure 1**, and the site plan is shown in **Figure 2**.

Site Background

Section 2 provides an overview of the site background, history of operations, geology and hydrogeology, and modifications to the sitewide activities during 2014.

2.1 Site Description and History

The project site is located at 500 East Richey Avenue, Artesia, New Mexico (**Figure 1**) and was used as an oilfield service facility operated by Dowell Schlumberger Incorporated (Dowell; a defunct joint venture between Schlumberger Technology Corporation [STC] and The Dow Chemical Company) between 1969 and 1990 and in the early 2000s. In 1988, the New Mexico Environment Department (NMED) Underground Storage Tank Bureau (USTB) directed response actions in connection with fuel-related volatile organic compound (VOC) releases from underground storage tanks (USTs) at the site. During the early 1990s, NMOCD assumed responsibility for regulatory oversight of the facility. Dowell ceased facility operations during the 1990s. For a limited time between 2000 and 2010, Dowell resumed and then ceased facility operations.

In 1988, fuel-related VOC impacts to site soil and groundwater were discovered during UST removal activities and were regulated by the NMED-USTB. In 1995, a chlorinated VOC (CVOC) groundwater plume was discovered onsite near the former Wash Bay and was determined to be migrating to an adjacent downgradient property. The NMED Groundwater Protection and Remediation Bureau began oversight of the CVOC plume response and continued to regulate the pre-1995 UST impacts. In response to the discovery of the plume, Dowell purchased the downgradient property. Following the purchase of the adjacent land, it was discovered that Eddy County, New Mexico, owns right-of-way property between numerous land parcels and, as of 2014, remains the owner of the right-of-way between the two adjacent properties.

The site is currently inactive. The USTs and acid plant have been decommissioned and removed, but the office, maintenance, and storage buildings remain at the site (**Figure 2**). The remaining property outside the facility fence line is undeveloped other than for limited environmental-related infrastructure.

The adjacent properties include the following:

- Artesia Alfalfa Growers Association - property to the north
- Mr. Donald Kiddy and Chase Farms - properties to the east
- East Richey Avenue (NM 357) and residential - properties to the south
- Southeast Ready Mix Products - property to the west

Two prior remediation strategies, soil excavation and soil vapor extraction (SVE), have been implemented to remove the petroleum hydrocarbons and CVOCs from site groundwater and soil surrounding the former USTs, former Wash Bay, and former Acid Plant (**Figure 2**). During the early to mid-1990s, soil contaminated with fuel-related VOCs and CVOCs was excavated at these locations. Following soil excavation, in January 1994, SVE systems began operation at the location of the former USTs and at the former Wash Bay. The SVE system at the former USTs successfully removed fuel-related VOCs within that area, and the SVE system at that location was decommissioned in the early 2000s. The former Wash Bay SVE system last operated during 2013 and was decommissioned in November 2014. Between 2001 and 2002, pilot-scale zero-valent iron (ZVI) injections were performed in the downgradient portions of the CVOC groundwater plume. Difficulties with the ZVI injections and subsurface distribution were encountered and resulted in no significant changes in CVOC concentrations in the groundwater. A groundwater extraction and treatment system is in operation in the downgradient portion of the plume, located adjacent to monitoring well MW-30. Groundwater is treated using granular activated carbon (GAC), then discharged back into the ground by gravity at the subsurface infiltration gallery located approximately 230 yards upgradient, near the location of MW-31.

The following activities occurred at the site during 2014:

- Semiannual and annual groundwater sampling events were conducted, including depth to water measurements.
- Groundwater samples were collected for dissolved iron and manganese, and sulfate and sulfide at selected locations to determine baseline (pre-substrate injection) conditions in the aquifer to assist with substrate dosing calculations.
- Eight injection wells were drilled and installed in a linear transect near existing monitoring well MW-25, to facilitate the injection of an oxidant substrate (sodium permanganate [NaMnO₄]) into the groundwater. A third extraction well, EW-03, was installed near existing monitoring well MW-28. One monitoring well, MW-34, was installed downgradient of the in situ chemical oxidation (ISCO) treatment zone between the northern end of the injection transect and EW-03. The locations of the new wells are shown on **Figure 2**.
- 22,650 pounds of a 40 percent sodium permanganate solution were injected into the aquifer via the eight injection wells (IJ-1 through IJ-8).
- The former Wash Bay SVE system was permanently decommissioned and completely removed in November 2014.
- A groundwater extraction and treatment system operated in the downgradient portion of the plume located at monitoring well MW-30. Groundwater was treated using GAC, then discharged back into the ground by gravity at the infiltration gallery located approximately 230 yards upgradient, near the location of MW-31.

2.2 Geology and Hydrogeology

2.2.1 Regional Geology and Hydrogeology

The underlying geology in the area includes the east-dipping Permian San Andres Limestone. Overlying the Permian San Andres Limestone are the Artesia Group and Quaternary alluvium (Lyford 1973).

Artesia, New Mexico, is located in the Roswell groundwater basin. The basin is bounded to the north roughly 20 miles north of Roswell, to the south in the Seven Rivers area between Artesia and Carlsbad, to the east by the Pecos River, and to the west roughly 20 miles west of Artesia. The Roswell groundwater basin consists of two aquifers separated by a leaky confining layer. The upper aquifer is contained in the quartzose unit of Quaternary alluvium and the lower aquifer consists of the Permian San Andres Limestone. The upper aquifer is unconfined and is composed of Quaternary alluvial valley fill. The majority of the water-producing zones in the aquifer are located in the quartzose unit. The zones are typically sand and gravel separated by adjacent zones of silt and clay. Most zones are around 20 feet thick (Welder 1983).

The leaky confining layer between the two aquifers is formed from the lower three formations of the Artesia Group, which are mudstones. The moderately permeable layers form a leaky confining layer between the lower and upper aquifers (Hendrickson and Jones 1952). The layers vary in thickness across the basin due to erosion and solution collapse. The lower aquifer is located within the San Andres Limestone and the lower part of the Artesia Group. There are five different water-bearing zones in the deep aquifer. The thickness of the aquifer ranges from 260 to 460 feet, with water-bearing zones typically 50 feet or less in thickness. In the northern part of the basin near Roswell, the middle of the San Andres Limestone is the main water-producing zone. Near Artesia, in the middle of the basin, the main zone of production is the top of the San Andres Limestone. In the southern part of the basin, the main zone of production is the lower part of the Artesia Group (Welder 1983).

The transmissivities of the two aquifers vary due to irregular fractures, solution permeability in the deep aquifer, and erratic occurrences of sand and gravel in the shallow aquifer (Hendrickson and Jones 1952). The transmissivities range from 7,500 to 196,000 square feet per day in the deep aquifer, and 4,200 to

186,000 square feet per day in the shallow aquifer (Welder 1983). The aquifer zone yields vary greatly due to groundwater moving principally through cavities and fractures (Hendrickson and Jones 1952) at various depths. As a result, it is difficult to find specific water-bearing depth intervals in the aquifer during monitoring well installation (Welder 1983). Groundwater moves from the lower aquifer to the shallow, although Welder (1983) states that flow may reverse due to heavy pumping in the lower aquifer. The estimated net rate of upward leakage is around 12,400 acre-feet per month (Welder 1983). Several water-bearing units in the leaky confining layer exist, and wells have been advanced and completed in the zones (Welder 1983). In general in the Roswell basin, groundwater flow is to the east; however, groundwater pumping in the Artesia area has caused a depression in the potentiometric surface of nearly 90 feet.

2.2.2 Site Geology and Hydrogeology

The geology and hydrogeology beneath the site were assessed during an investigation conducted in March 1995 by Western Water Consultants, Inc. Observations made during drilling activities described the predominant lithologies to consist of light-brown to reddish-brown silt and silty clay, interbedded with clay layers and stringers of carbonate rubble. The very fine-grained sediments were deposited in an arid, alluvial overbank environment and can be expected to be more laterally continuous than coarse-grained alluvial channel deposits (Western Water Consultants, Inc. 1995). The carbonate layers are believed to be the result of the evaporation of water containing elevated concentrations of dissolved solids. The 1991 investigation arrived at the conclusion that the stringers of carbonate rubble constitute the primary water-bearing zones. The rubble layers were observed at depths ranging from 20 to 26 feet below ground surface (bgs) (Western Water Consultants, Inc. 1995).

2.3 Modifications to the Sitewide Activities

No modifications to the sitewide activities were requested in 2014. However modifications requested in 2013 were implemented during 2014 and are described below.

On July 9, 2013, STC submitted via email a *Work Plan Amendment for the Schlumberger Oilfield Services Facility—Artesia* (STC 2013a) requesting that reporting frequency for the site be modified to annual and to include activities for the prior calendar year. The work plan amendment was conditionally approved by NMOCD in an e-mail dated July 15, 2013 (**Appendix A**). The conditional approval required that the annual report be submitted by April 1 of each following year.

On August 15, 2013, the *Work Plan Amendment, Soil Investigation and Soil Vapor Extraction System Closure, Former Dowell Schlumberger Facility, Artesia, New Mexico* (STC 2013b) was submitted to NMOCD. The work plan amendment was conditionally approved by NMOCD in an e-mail dated August 22, 2013 (**Appendix A**). The work plan amendment included a provision for taking the former Wash Bay SVE system offline pending the results of the soils investigation. The SVE system was taken offline during the fourth quarter of 2013 and was decommissioned in November 2014. The SVE decommissioning is described in the *Soil Vapor Extraction System Closure Report, Former Dowell Schlumberger Facility, Artesia, New Mexico (GW-114)* (CH2M HILL 2015).

On August 15, 2013, the *Work Plan Amendment, Groundwater Remediation Program Modifications, Former Dowell Schlumberger Facility, Artesia, New Mexico* (STC 2013c) was submitted to NMOCD. The work plan amendment was conditionally approved by NMOCD in an e-mail dated August 22, 2013 (**Appendix A**). The work plan amendment included provisions for modifying the existing groundwater extraction and treatment system and for evaluating and performing ISCO to enhance the removal of VOCs in site groundwater. The conditional approval required monitoring for manganese and sulfate in groundwater to demonstrate the New Mexico Water Quality Control Commission (NMWQCC) standards for those constituents are not exceeded following substrate injection. On September 17, 2013, the *Work Plan Amendment, Modifications to the Groundwater Monitoring Program, Former Dowell Schlumberger Facility, Artesia, New Mexico* (STC 2013d) was submitted to the NMOCD. The work plan amendment was conditionally approved by NMOCD in

an e-mail dated September 18, 2013 (**Appendix A**). The monitoring program modifications implemented in October 2013 and described in the *2013 Annual Groundwater Monitoring Report Former Dowell Schlumberger Facility, Artesia, New Mexico* (CH2M HILL 2014) were continued in 2014.

2014 Site Activities

Section 3 summarizes the 2014 groundwater testing, well drilling and installation, groundwater treatment, and permanganate injection activities at the site.

3.1 Groundwater Monitoring Activities

The following subsections summarize the activities conducted during the semiannual groundwater monitoring events.

3.1.1 Depth-to-Water Measurements and Groundwater Sampling

Depth to water was measured at each of the 27 site wells during the semiannual events (April and October). During October 2014, southern New Mexico received a 500-year rainfall event. There was widespread flooding and localized standing water at the site. Additionally, a broken water line, unrelated to the environmental work at the site, was discovered in October 2014 near MW-9 in the former main operations area of the facility. The broken water line was subsequently repaired by others. Both of these October events resulted in significant anomalies in the depth to groundwater and groundwater table elevations and these measurements were not used to evaluate groundwater gradient and flow direction. In November 2014, the depth to water measurements were again collected at each of the 27 site monitoring wells and used to evaluate the groundwater gradient and flow direction. The groundwater elevation near MW-9 in the former main operations area of the facility remained elevated in November.

The first semiannual groundwater sampling event was conducted in April and included sample collection from 11 of the 27 monitoring wells (MW-12, MW-17C, MW-18, MW-21, MW-25, MW-26, MW-28, MW-30, MW-31, MW-32, and MW-33). The second semiannual groundwater sampling event occurred in October and included sample collection from 19 of the 27 monitoring wells (MW-1, MW-7, MW-8, MW-11, MW-12, MW-15, MW-17C, MW-18, MW-20, MW-21, MW-22, MW-26, MW-28, MW-29, MW-30, MW-31, MW-32, MW-33, and MW-34). A groundwater sample was not collected at MW-25 during the October event, because MW-25 is located adjacent to the injection transect and NaMnO_4 was observed in the well during the injections.

Prior to groundwater sample collection, the monitoring wells were purged with a peristaltic pump using low-flow methods. Field parameters (temperature, pH, conductivity, turbidity, dissolved oxygen, and oxidation-reduction potential) were measured and recorded during purging activities. Groundwater samples were collected following either field-parameter stabilization or the removal of three well-casing volumes. Groundwater samples were submitted for laboratory analysis of VOCs by U.S. Environmental Protection Agency (USEPA) SW-846 Method 8260B.

As a condition of NMOC's Discharge Permit Work Plan (GW Remediation Program) Amendment Approval (**Appendix A**) to inject NaMnO_4 at the site, post-injection monitoring for manganese is required. A total of 11 monitoring wells are located within and adjacent to the permanganate injection target treatment zone (MW-18, MW-21, MW-22, MW-25, MW-26, MW-28, MW-29, MW-30, MW-31, MW-32, and MW-34) (**Figure 2**); these wells were selected for manganese monitoring. During the second semiannual groundwater sampling event, groundwater samples were collected at 10 of the 11 monitoring wells (MW-18, MW-21, MW-22, MW-26, MW-28, MW-29, MW-30, MW-31, MW-32, and MW-34) and submitted for laboratory analysis of dissolved manganese by USEPA Method 6020. Monitoring well MW-25 was not sampled due to the presence of NaMnO_4 in that well. Monitoring well MW-25 is located approximately 63 feet from the nearest injection well and given that injections were underway, the NaMnO_4 was likely not diluted. A decision was made to not collect a sample and send it to the laboratory. Monitoring well MW-25 will be monitored for manganese in the next semiannual event following dispersion of the oxidant beyond the injection zone.

Groundwater extracted during purging activities was contained in a 55-gallon drum and transferred to the GAC drums at the groundwater treatment system and processed through the treatment system.

3.2 Groundwater Treatment System Testing

The groundwater treatment system includes both the extraction pumping, treatment, and infiltration component and the ISCO component. From June 2 through 5, during the planning phases for the pump and treat system improvements and the injections, testing activities were conducted to evaluate aquifer pumping rates, gravity reinjection rates, and to collect groundwater samples from monitoring wells MW-25 and MW-28 for laboratory analyses of dissolved iron, dissolved manganese, sulfate, and sulfide concentrations to assist with selection of the oxidant reagent, dosing, and injection rates.

3.2.1 Groundwater Extraction and Treatment System

The groundwater extraction and treatment system operated continuously through September 18, 2014, when the groundwater treatment infrastructure was modified so the extracted groundwater could be used to deliver the NaMnO_4 to the aquifer via installed injection wells. From January to September the groundwater extraction and treatment system operated continuously except for roughly a 1-hour period during GAC exchanges, which occurred in April. During the monitoring event, the groundwater treatment system was inspected. The system hoses, drums, and equalization tank were examined for possible leaks or malfunctions to minimize the possibility of upset conditions or system failure; no issues were found.

Following the inspection, the system's four GAC drums were disconnected and replaced with new GAC vessels. Four spent GAC drums were transported offsite for disposal on both April 8 and November 25, 2014.

The system was shut down at the completion of injections on October 26, 2014, to allow the NaMnO_4 to remain in contact with the CVOs in the aquifer.

3.3 Closure of Former Wash Bay SVE System

The former Wash Bay SVE system operated until the fourth quarter of 2013. The SVE system was taken offline in November 2013, in accordance with the NMOCD-approved work plan amendment, as discussed in Section 2.3. The system was decommissioned and completely removed in November 2014.

Decommissioning is detailed in the *Soil Vapor Extraction System Closure Report, Former Dowell Schlumberger Facility, Artesia, New Mexico (GW-114)* (CH2M HILL 2015).

3.4 Well Installation

Well permit applications for non-consumptive use of water were submitted to the New Mexico Office of the State Engineer (NMOSE). Well permits were granted by the NMOSE on August 14, 2014, and are included as **Appendix B**. On August 18, 2014, National Exploration Wells and Pumps (NEWP), a licensed New Mexico driller, mobilized to the site to install eight injection wells, one downgradient monitoring well, and one extraction well. Prior to well installation, ground-penetrating radar was used at each drilling location to identify the presence of subsurface utilities within the proposed drilling area.

At the completion of well installation the wells were developed by surging with a surge block followed by bailing out the fine-grained sediment that entered the well screen during the surging step. Following the surging/bailing step, a submersible pump was placed into the well and pumped at a suitable flow rate to prevent the screen interval from dewatering, until the water's turbidity began to decrease. Development was considered complete when the measured turbidity of the groundwater was less than 10 nephelometric turbidity units (NTU). Water removed from the wells during development was containerized and transferred to the GAC system for treatment and reinjection.

3.4.1 Injection Wells

Eight injection wells were installed upgradient of monitoring well MW-25 in a linear transect, spaced 30-feet apart, as shown on **Figure 2**, using a CME 85 hollow-stem auger drill rig with a center plug; soil was logged

using the Unified Soil Classification System (USCS) from auger cuttings. Soil boring logs are included in **Appendix B**.

Injection wells were drilled to a total depth of 32-feet bgs and constructed with 2-inch inside diameter (ID) schedule 40 (SCH40) polyvinyl chloride (PVC) well casing. The screen, consisting of 2-inch ID SCH40 wire-wrapped PVC 0.040-inch slot, was set from approximately 20 to 30-feet bgs. Well construction diagrams are included in **Appendix B** and include filter pack type and size, bentonite seal depth, and grout mixture. Injection wells were finished with an 8-inch diameter steel protective casing and a locking cap within a 4-foot by 4-foot by 4-inch thick concrete well pad.

3.4.2 Extraction Well

An additional extraction well, EW-03, was installed near monitoring well MW-28 to a total depth of 60-feet bgs using a CME 85 hollow-stem auger drilling rig and continuous soil core barrel. The borehole was installed using 4.25-inch ID augers in conjunction with a 3-inch ID, 5-feet long continuous coring barrel. The soil retrieved from the continuous core barrel was logged using the USCS. Upon reaching the total depth of the borehole, 6.25-inch ID augers were used to over-ream the borehole to accommodate the installation of a 4-inch ID SCH40 PVC well. The screen, consisting of 4-inch ID SCH40 wire-wrapped 0.040-inch slot, was set from 15 to 55-feet bgs. The soil boring logs and well construction diagram are included in **Appendix B** and include filter pack type and size, bentonite seal depth, and grout mixture.

The extraction well casing was terminated at 2-feet bgs to accommodate the installation of a 0.5-horsepower submersible Grundfos pump and associated piping and electrical conduit. A 5-foot diameter concrete well vault and manhole was installed.

3.4.3 Monitoring Well

One additional monitoring well, MW-34, was installed to a total depth of 36.5 feet bgs between the northern end of the injection transect and new extraction well EW-03 using a CME 85 hollow-stem auger drilling rig and continuous soil core barrel. The borehole was installed using 4.25-inch ID augers in conjunction with a 3-inch ID, 5-feet long continuous coring barrel. The soil retrieved from the continuous core barrel was logged using the USCS. Upon reaching the total depth of the borehole, 6.25-inch ID augers were used to over-ream the borehole to accommodate the installation of a 4-inch ID SCH40 PVC well. The screen, consisting of 4-inch ID SCH40 0.010-inch mil slot, was set from 17 to 27-feet bgs. The soil boring log and well construction diagram are included in **Appendix B** and include filter pack type and size, bentonite seal depth, and grout mixture.

3.5 Sodium Permanganate Injections

On September 15, 2014, CH2M HILL personnel and a crew from Advanced Environmental Solutions mobilized to the site to begin construction of the temporary injection system. The injection system was installed by modifying the plumbing from the GAC drums inside the groundwater extraction and treatment facility such that treated groundwater from the GAC outlets was used as the water source for the permanganate solution. The treated groundwater was delivered to an above-grade jet pump, mixed with permanganate, and the solution was delivered to the injection wells via a piping manifold. Flow was controlled with various valves throughout the system and digital flow meters were used to measure the volume of solution injected into each well.

Injection of a 0.4 to 0.5 percent NaMnO_4 solution into the groundwater via eight injection wells began on September 18 and continued through October 26, 2014. Due to the 500-year rainfall event and subsequent flooding at the site, the injections did not occur continuously during this period. **Table 1** details volume of permanganate solution injected into each well. At the completion of oxidant injections, 1,000 gallons of treated water was injected into the injection wells to flush the well screens and sandpack of residual oxidant. Injection volumes and flow meter information were submitted to the NMOSE on January 6, 2015, as required by the NMOSE-issued well permits.

The temporary injection system was dismantled and removed from the site at the completion of the injections. During the October groundwater sampling event, the groundwater from monitoring wells in the downgradient portion of the plume, within and adjacent to the injection wells, was checked for the presence of NaMnO_4 . The check was made by comparing the groundwater against a white background and observing for purple color, which indicates the presence of NaMnO_4 .

Results and Discussion

4.1 Groundwater Elevation and Gradient

The groundwater gradient was 0.004 to 0.007 foot per foot in April, with the overall direction of groundwater flow to the northeast. The gradient and groundwater flow direction were consistent with previous reports.

The groundwater extraction, treatment, and infiltration system had been off for approximately one month at the time the measurements were collected in November. As discussed in Section 3.1.1, a broken potable water line in the northeast portion of the facility artificially increased groundwater elevations in the upgradient portion of the site. Groundwater elevations near the gravity infiltration trench (near MW-31) remained locally high; very little influence was observed elsewhere at the site. The groundwater gradient was 0.006 to 0.010 foot per foot in November, with the overall direction of groundwater flow to the northeast.

Table 2 contains the 2014 groundwater elevation data. Please refer to previous annual monitoring reports for historical groundwater elevation data. Potentiometric surface maps depicting the groundwater elevation measured during the April and November 2014 semiannual gauging events are provided in **Figures 3 and 4**, respectively.

4.2 Groundwater Analytical Results

Table 3 summarizes the groundwater analytical results for 2014. Please refer to previous annual monitoring reports for historical groundwater analytical data. The 2014 laboratory analytical reports are in **Appendix C**, and the results of the data validation process are in **Appendix D**. The groundwater analytical results have been compared to the NMWQCC standards, which are shown on **Table 3**. Other analytes are reported in the analytical data, but do not have NMWQCC standards and are not shown on **Table 3**. **Table 3** generally follows the data format of prior annual reports. **Figures 5 through 11** present concentrations in groundwater for only the contaminants of concern (COCs) that exceeded NMWQCC standards during a given semiannual event. The extent of the exceedance of the NMWQCC standard is shown as an isopleth line on each figure. The following discussion summarizes the COC distribution at the site.

Concentrations of 1,1-dichloroethane (1,1-DCA) exceeded the NMWQCC standard of 0.025 milligrams per liter (mg/L) during the April sampling event at monitoring well MW-12 (**Figure 5**) and did not exceed the NMWQCC standard at monitoring well locations sampled during the October sampling event.

Concentrations in wells where 1,1-DCA was detected decreased between the April and October events, except for slight increases in monitoring wells MW-28 and MW-31, however, the concentrations were still well below the NMWQCC standard.

Concentrations of 1,1-dichloroethene (1,1-DCE) exceeded the NMWQCC standard of 0.005 mg/L in multiple wells during the April and October sampling events (**Figures 6 and 7**). The exceedances are limited to the downgradient plume located outside the facility proper. 1,1-DCE is a focus of the oxidant injections and the groundwater extraction and treatment system modifications currently underway.

Concentrations of tetrachloroethene (PCE) exceeded the NMWQCC standard of 0.020 mg/L during the April and October sampling events (**Figures 8 and 9**). The exceedances are limited to the downgradient plume located outside the facility proper. The PCE is being acted upon by the groundwater extraction and treatment system and is a focus of the system modifications and oxidant injections currently underway.

Concentrations of naphthalene exceeded the NMWQCC standard of 0.030 mg/L during the April and October sampling events at MW-12 (**Figures 10 and 11**). Naphthalene concentrations are limited to the facility proper where benzene concentrations have previously exceeded NMWQCC standards.

It appears that the downgradient VOC plume is migrating beyond the current treatment system and moving further downgradient in the area of monitoring wells MW-28 and MW-29. The pumping of groundwater from EW-03 and the oxidant injections are anticipated to address CVOCs in this portion of the plume.

Dissolved manganese and sulfate samples were collected for analyses at monitoring wells MW-25 and MW-28 in June to determine baseline concentrations in the groundwater prior to oxidant injections. Samples were again collected for dissolved manganese analysis in October to demonstrate the injection of NaMnO_4 into the groundwater did not increase the concentration of manganese in the aquifer. No manganese exceedances were found during the October sampling event, however, this sampling event was immediately following the completion of the injections.

Baseline sulfate concentrations in the groundwater exceeded the NMWQCC standard of 600 mg/L, however a persulfate oxidant was not chosen as the injection substrate; sulfate concentrations in the aquifer were not monitored in the October sampling event. The sulfate is believed to be at background concentrations and no further sulfate monitoring is planned.

4.3 Sodium Permanganate Injections

As presented on **Table 1**, a total of 475,810 gallons of NaMnO_4 solution were injected into the groundwater via eight injection wells. Each of the eight injection well received an average of 232.3 gallons of NaMnO_4 blended with an average 59,244 gallons of treated groundwater.

During the October semiannual groundwater sampling event, the color purple, indicating the presence of NaMnO_4 , was observed in MW-25 but was not observed in other monitoring wells at the site.

Conclusions and Recommendations

The following conclusions and recommendations are presented relative to groundwater conditions at the site, based on the potentiometric and analytical data obtained during the 2014 site activities.

5.1 Conclusions

Groundwater monitoring has been conducted at the site since 1991. Most of the groundwater concentrations reported in the 2014 annual groundwater sampling period were stable or showed decreasing concentrations compared to historical data. A review of the historical analytical data indicates that VOC concentrations onsite have significantly decreased because of the former SVE systems and the groundwater extraction, treatment, and infiltration system. Most of the VOCs that persist are just slightly above NMWQCC standards; however, it appears that the downgradient VOC plume extends beyond the current groundwater extraction, treatment, and infiltration system and is moving further downgradient in the area of monitoring well MW-28.

The semiannual October sampling event was conducted less than one month after the completion of NaMnO_4 injections and no changes in VOCs concentrations due to the injections were observed.

5.2 Recommendations for Future Activities

5.2.1 Operate Upgraded Groundwater Treatment Facility

The updated groundwater treatment system was installed during February 2015 and included the following upgrades:

1. A larger GAC system that allows for longer time between GAC exchanges and provides an easier and more efficient process for exchanging spent GAC.
2. Remote-monitoring telemetry to allow real-time monitoring that will confirm that the system is operating correctly and that will send notifications of upset conditions.
3. Startup of the third extraction well, EW-03, near monitoring well MW-28 to manage the plume at the site boundary.

The upgraded system is expected to assist with the distribution of NaMnO_4 through the aquifer to maximize the treatment of CVOCs by the oxidant. Once the oxidant is observed in the extracted groundwater, the GAC will be bypassed in the groundwater system and the extracted groundwater will be sent directly to the infiltration gallery to recirculate the residual oxidant throughout the downgradient plume.

5.2.2 Groundwater Monitoring

The groundwater monitoring program will continue on a semiannual basis following the NMOSE-approved schedule. Monitored analytes will include VOCs and manganese. The monitoring wells in the downgradient portion of the plume, along with the extracted groundwater, will be monitored for the presence of NaMnO_4 .

References

CH2M HILL, Inc. 2015. *Soil Vapor Extraction System Closure Report, Former Dowell Schlumberger Facility, Artesia, New Mexico (GW-114)*. March.

CH2M HILL, Inc. 2014. *2013 Annual Groundwater Monitoring Report, Former Dowell Schlumberger Facility, Artesia, NM*. March.

Hendrickson, G. E., and Jones, R. S. 1952. *Geology and Groundwater Resources of Eddy County, New Mexico*. New Mexico Bureau of Mines and Mineral Resources, Groundwater Report 3.

Lyford, F. P. 1973. *Valley Fill in the Roswell-Artesia Area, New Mexico*. USGS Open File Report.

Schlumberger Technology Corporation. 2013a. *Work Plan Amendment for the Schlumberger Oilfield Services Facility—Artesia* (via email). July 9.

Schlumberger Technology Corporation. 2013b. *Work Plan Amendment Soil Investigation and Soil Vapor Extraction System Closure Former Dowell Schlumberger Facility, Artesia, New Mexico*. August 16.

Schlumberger Technology Corporation. 2013c. *Work Plan Amendment Groundwater Remediation Program Modifications Former Dowell Schlumberger Facility, Artesia, New Mexico*. August 16.

Schlumberger Technology Corporation. 2013d. *Work Plan Amendment Modifications to the Groundwater Monitoring Program Former Dowell Schlumberger Facility, Artesia, New Mexico*. September 16.

Welder, G. E. 1983. *Geohydrologic Framework of the Roswell Groundwater Basin, Chaves and Eddy Counties, New Mexico*. USGS/New Mexico State Engineer Technical Report No. 42.

Western Water Consultants, Inc. 1995. *Quarterly Report for Additional Investigation and Remediation, Dowell Schlumberger Artesia, New Mexico*. July 13

TABLE 1

Substrate Injection Summary*2014 Annual Groundwater Monitoring Report**Former Dowell Schlumberger Facility, Artesia, New Mexico*

Well ID	Substrate Injection			Substrate	Maximum Injection Flow Rate (gpm)	Maximum Injection Pressure (psi)
	Total Injection Volume (gal)	Substrate (lb)	Substrate (gal)			
IJ-1	55,721	2,496	218.5	NaMnO ₄	2.66	2.5
IJ-2	56,566	2,516	220.3	NaMnO ₄	3.06	3.3
IJ-3	62,445	2,784	243.8	NaMnO ₄	2.68	4.5
IJ-4	56,864	2,547	223.0	NaMnO ₄	2.98	9.0
IJ-5	58,264	2,600	227.7	NaMnO ₄	2.90	8.0
IJ-6	62,731	2,794	244.7	NaMnO ₄	2.84	2.5
IJ-7	60,215	2,686	235.2	NaMnO ₄	3.02	2.5
IJ-8	63,004	2,796	244.8	NaMnO ₄	2.75	4.5
Totals	475,810	21,219	1,858	Maximum Values	3.06	9.0

Notes:

gal = gallons

lb = pounds

gpm = gallon per minute

psi = pounds per square inch

NaMnO₄ = sodium permanganate

TABLE 2

Groundwater Elevation Data - 2014

2014 Annual Groundwater Monitoring Report

Former Dowell Schlumberger Facility, Artesia, New Mexico

Well ID	Date	Total Depth (ft btoc)	Top of Casing Elevation (ft amsl)	Depth to Water (ft btoc)	Groundwater Elevation (ft amsl)
MW-1	4/7/14	30.0	3358.52	13.99	3344.53
	10/14/14	30.0	3358.52	6.75	3351.77
	11/6/14	30.0	3358.52	7	3351.52
MW-6	4/7/14	35.0	3358.80	16.96	3341.84
	10/14/14	35.0	3358.80	4.36	3354.44
	11/6/14	35.0	3358.80	8.10	3350.70
MW-7	4/7/14	35.0	3358.19	16.84	3341.35
	10/14/14	35.0	3358.19	3.91	3354.28
	11/6/14	35.0	3358.19	8.59	3349.60
MW-8	4/7/14	35.0	3359.43	16.85	3342.58
	10/14/14	35.0	3359.43	5.92	3353.51
	11/6/14	35.0	3359.43	10.42	3349.01
MW-9	4/7/14	30.0	3357.29	14.85	3342.44
	10/14/14	30.0	3357.29	5.42	3351.87
	11/6/14	30.0	3357.29	7.35	3349.94
MW-10	4/7/14	30.0	3357.80	15.34	3342.46
	10/14/14	30.0	3357.80	4.43	3353.37
	11/6/14	30.0	3357.80	7.91	3349.89
MW-11	4/7/14	30.0	3356.16	14.83	3341.33
	10/14/14	30.0	3356.16	0.40	3355.76
	11/6/14	30.0	3356.16	6.68	3349.48
MW-12	4/7/14	25.7	3356.45	14.64	3341.81
	10/14/14	25.7	3356.45	0.70	3355.75
	11/6/14	25.7	3356.45	6.41	3350.04
MW-15	4/7/14	34.0	3357.65	14.67	3342.98
	10/14/14	34.0	3357.65	5.49	3352.16
	11/6/14	34.0	3357.65	7.00	3350.65
MW-16	4/7/14	NM	NM	13.75	NM
	10/14/14	NM	NM	6.20	NM
	11/6/14	NM	NM	6.53	NM
MW-17C	4/7/14	62.4	3356.49	14.66	3341.83
	10/14/14	62.4	3356.49	1.94	3354.55
	11/6/14	62.4	3356.49	6.35	3350.14
MW-18	4/7/14	30.1	3356.65	15.82	3340.83
	10/14/14	30.1	3356.65	3.24	3353.41
	11/6/14	30.1	3356.65	7.94	3348.71
MW-19	4/7/14	28.0	3357.02	15.56	3341.46
	10/14/14	28.0	3357.02	3.13	3353.89
	11/6/14	28.0	3357.02	6.96	3350.06
MW-20	4/7/14	28.0	3359.05	17.85	3341.20
	10/14/14	28.0	3359.05	12.21	3346.84
	11/6/14	28.0	3359.05	13.11	3345.94

TABLE 2

Groundwater Elevation Data - 2014

2014 Annual Groundwater Monitoring Report

Former Dowell Schlumberger Facility, Artesia, New Mexico

Well ID	Date	Total Depth (ft btoc)	Top of Casing Elevation (ft amsl)	Depth to Water (ft btoc)	Groundwater Elevation (ft amsl)
MW-21	4/7/14	17.41	3356.83	15.85	3340.98
	10/14/14	17.41	3356.83	9.76	3347.07
	11/6/14	17.41	3356.83	11.08	3345.75
MW-22	4/7/14	15.63	3355.11	14.62	3340.49
	10/14/14	15.63	3355.11	6.40	3348.71
	11/6/14	15.63	3355.11	8.81	3346.30
MW-23	4/7/14	25.0	3355.26	15.08	3340.18
	10/14/14	25.0	3355.26	4.43	3350.83
	11/6/14	25.0	3355.26	6.32	3348.94
MW-25	4/7/14	27.3	3355.61	17.82	3337.79
	10/14/14	27.3	3355.61	9.68	3345.93
	11/6/14	27.3	3355.61	11.05	3344.56
MW-26	4/7/14	27.35	3354.14	17.05	3337.09
	10/14/14	27.35	3354.14	9.74	3344.40
	11/6/14	27.35	3354.14	10.42	3343.72
MW-27	4/7/14	25.0	3354.17	15.29	3338.88
	10/14/14	25.0	3354.17	7.33	3346.84
	11/6/14	25.0	3354.17	9.44	3344.73
MW-28	4/7/14	27.94	3355.88	19.71	3336.17
	10/14/14	27.94	3355.88	15.25	3340.63
	11/6/14	27.94	3355.88	14.65	3341.23
MW-29	4/7/14	20.25	3354.99	19.36	3335.63
	10/14/14	20.25	3354.99	16.09	3338.90
	11/6/14	20.25	3354.99	15.32	3339.67
MW-30	4/7/14	27.89	3354.53	19.52	3335.01
	10/14/14	27.89	3354.53	15.95	3338.58
	11/6/14	27.89	3354.53	12.62	3341.91
MW-31	4/7/14	30.89	3356.32	15.63	3340.69
	10/14/14	30.89	3356.32	5.42	3350.90
	11/6/14	30.89	3356.32	8.71	3347.61
MW-32	4/7/14	38.85	3354.46	18.53	3335.93
	10/14/14	38.85	3354.46	12.63	3341.83
	11/6/14	38.85	3354.46	12.23	3342.23
MW-33	4/7/14	35.0	3349.63	16.98	3332.65
	10/14/14	35.0	3349.63	12.49	3337.14
	11/6/14	35.0	3349.63	12.78	3336.85
MW-34	10/14/14	32.0	NM	12.81	NM
	11/6/14	32.0	NM	12.82	NM

ft btoc = feet below top of casing

ft amsl = feet above mean sea level

NM = not measured, MW-16 and MW-34 have not been surveyed; groundwater elevation in ft amsl is not calculated.

TABLE 3
Summary of Groundwater Analytical Results - 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico

WELL NUMBER	SAMPLE DATE	Iron, Dissolved (mg/L)	Manganese, Dissolved (mg/L)	Sulfate (mg/L)	Sulfide (mg/L)	1,1,1-TCA (mg/L)	1,1,2,2-Tetrachloroethane (mg/L)	1,1,2- Trichloroethane (mg/L)	1,1-DCA (mg/L)	1,1-DCE (mg/L)	1,2-DCA (mg/L)	Benzene (mg/L)	Carbon Tetrachloride (mg/L)	Chloroform (mg/L)
NMWQCC Standards		1.0	0.2	600		0.06	0.01	0.01	0.025	0.005	0.01	0.01	0.01	0.1
MW-1	10/21/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	<0.00011	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
MW-7	10/17/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	<0.00011	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
MW-8	10/17/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	0.00206	0.00125	<0.00014	<0.00008	<0.00015	<0.00013
MW-11	10/17/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	0.000253 J	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
MW-12	04/08/14	--	--	--	--	<0.00075	<0.0011	<0.0014	0.0263	0.00229 J	<0.0007	0.00621	<0.00075	<0.00065
	10/17/14	--	--	--	--	<0.00015 J	<0.00022 J	<0.00028 J	0.00434 J	0.000484 J	<0.00014 J	<0.00265	<0.00015 J	<0.00013 J
MW-15	10/17/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	0.000119 J	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
MW-17C	04/08/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	0.000221 J	0.000438 J	<0.00014	<0.00008	<0.00015	<0.00013
	10/17/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	0.000184 J	0.000436 J	<0.00014	<0.00008	<0.00015	<0.00013
MW-18	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.00118	0.00551	<0.00014	<0.00008	<0.00015	<0.00013
	10/16/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	<0.00011	0.00019 J	<0.00014	<0.00008	<0.00015	<0.00013
MW-20	10/16/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	0.0121	0.0038	0.000168 J	<0.000211	<0.00015	<0.00013
MW-21	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.000221 J	<0.00019	<0.000187	<0.00008	<0.00015	<0.00013
	10/16/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.000195 J	0.000196 J	<0.00014	<0.00008	<0.00015	<0.00013
MW-22	10/16/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.00187	0.00489	<0.00014	<0.00008	<0.00015	<0.00013
MW-25	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.00436	<0.00019	<0.00023	<0.00008	<0.00015	<0.00013
	06/05/14	<0.0866	0.000894 J	2140	<0.009	--	--	--	--	--	--	--	--	--
MW-26	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.000219 J	0.0011	<0.000147	<0.00008	<0.00015	<0.00013
	10/14/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.000136 J	0.000964 J	<0.00014	<0.00008	<0.00015	<0.00013
MW-28	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.00815	0.0241	<0.000322	<0.00008	<0.00015	<0.00013
	06/05/14	<0.0866	0.00314 J	2340	<0.009	--	--	--	--	--	--	--	--	--
	10/15/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.00889	0.0361	0.000196 J	<0.000103	<0.00015	<0.00013
MW-29	10/15/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.0037	0.0238	<0.00014	<0.00008	<0.00015	<0.00013
MW-30	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.0093	0.0322	<0.000366	0.0000842 J	<0.00015	0.000142 J
	10/15/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.00606	0.0221	0.000164 J	<0.00008	<0.00015	<0.00013
MW-31	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.000291 J	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
	10/16/14	--	0.138	--	--	<0.00015	<0.00022 J	<0.00028	0.0008 J	0.00122	<0.00014	<0.00008	<0.00015	<0.00013
MW-32	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	0.00089 J	0.00355	<0.00014	<0.00008	<0.00015	<0.00013
	10/15/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.000603 J	0.00296	<0.00014	<0.00008	<0.00015	<0.00013
MW-33	04/08/14	--	--	--	--	<0.00015	<0.00022	<0.00028	<0.00011	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
	10/15/14	--	--	--	--	<0.00015	<0.00022 J	<0.00028	<0.00011	<0.00019	<0.00014	<0.00008	<0.00015	<0.00013
MW-34	10/15/14	--	<0.0116	--	--	<0.00015	<0.00022 J	<0.00028	0.00406	0.0131	<0.00014	<0.00008	<0.00015	<0.00013

NOTES:
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter (equivalent to parts per million)
<0.001 = analyte not detected at concentration above detection limit shown
J = analyte detected at concentration above instrument detection limit but below method detection limit
-- = sample not analyzed for this analyte
0.000196 Bolded cells indicate the analyte was positively detected.
0.0241 Shaded cells indicate concentrations exceed their respective NMWQCC standards.

DCA - dichloroethane
DCE - dichloroethene
PCE - tetrachloroethene
TCE - trichloroethene

TABLE 3

Summary of Groundwater Analytical Results - 2014

2014 Annual Groundwater Monitoring Report

Former Dowell Schlumberger Facility, Artesia, New Mexico

WELL NUMBER	SAMPLE DATE	Ethylbenzene (mg/L)	Ethylene Dibromide (mg/L)	m,p-Xylene (sum of isomers) (mg/L)	Methylene Chloride (Dichloromethane) (mg/L)	Naphthalene (mg/L)	o-Xylene (mg/L)	PCE (mg/L)	Toluene (mg/L)	TCE (mg/L)	Vinyl Chloride (mg/L)	Xylenes, Total (mg/L)
NMWQCC Standards		0.75	0.0001	0.62	0.1	0.03	0.62	0.02	0.75	0.1	0.001	0.62
MW-1	10/21/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	<0.00013	<0.00015	<0.00018	<0.00011	<0.00026
MW-7	10/17/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000161 J	<0.00015	<0.00018	<0.00011	<0.00026
MW-8	10/17/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00181	<0.00015	0.00108	<0.00011	<0.00026
MW-11	10/17/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	<0.00013	<0.00015	0.000211 J	<0.00011	<0.00026
MW-12	04/08/14	0.148	<0.0009	0.0486	<0.00075 J	0.0419 J	0.00127 J	0.00113 J	<0.00075	0.00367 J	<0.00055	0.0499
	10/17/14	0.00379 J	<0.00018 J	0.0554	<0.00015 J	0.104	0.0116 J	0.00083 J	<0.00015 J	0.000851 J	<0.00011 J	0.067
MW-15	10/17/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00592	<0.00015	0.0154	<0.00011	<0.00026
MW-17C	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032 J	<0.00012	0.0002 J	<0.00015	0.000262 J	<0.00011	<0.00026
	10/17/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000199 J	<0.00015	0.000615 J	<0.00011	<0.00026
MW-18	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00067	<0.00012	0.00564	<0.00015	<0.00018	<0.00011	<0.00026
	10/16/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000361 J	<0.00015	<0.00018	<0.00011	<0.00026
MW-20	10/16/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00263	<0.00015	0.0043	0.000374 J	<0.00026
MW-21	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000408 J	<0.00015	<0.00018	<0.00011	<0.00026
	10/16/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000134 J	<0.00015	<0.00018	<0.00011	<0.00026
MW-22	10/16/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00668	<0.00015	0.00135	<0.00011	<0.00026
MW-25	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.0157	<0.00015	0.00285	<0.00011	<0.00026
	06/05/14	--	--	--	--	--	--	--	--	--	--	--
MW-26	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000959 J	<0.00015	0.000369 J	<0.00011	<0.00026
	10/14/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000261 J	<0.00015	0.000384 J	<0.00011	<0.00026
MW-28	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.0263	<0.00015	0.00721	<0.00011	<0.00026
	06/05/14	--	--	--	--	--	--	--	--	--	--	--
	10/15/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.0224	<0.00015	0.00873	<0.00011	<0.00026
MW-29	10/15/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00884	<0.00015	0.00503	<0.00011	<0.00026
MW-30	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.0413	<0.00015	0.00822	<0.00011	<0.00026
	10/15/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.0205	<0.00015	0.0058	<0.00011	<0.00026
MW-31	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	<0.00013	<0.00015	<0.00018	<0.00011	<0.00026
	10/16/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.000499 J	<0.00015	0.000258 J	<0.00011	<0.00026
MW-32	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00538	<0.00015	0.000963 J	<0.00011	<0.00026
	10/15/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00341	<0.00015	0.000887 J	<0.00011	<0.00026
MW-33	04/08/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	<0.00013	<0.00015	<0.00018	<0.00011	<0.00026
	10/15/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	<0.00013	<0.00015	<0.00018	<0.00011	<0.00026
MW-34	10/15/14	<0.00011	<0.00018	<0.00017	<0.00015	<0.00032	<0.00012	0.00752	<0.00015	0.00266 J	<0.00011	<0.00026

NOTES:

NMWQCC = New Mexico Water Quality Control Commission

mg/L = milligrams per liter (equivalent to parts per million)

<0.001 = analyte not detected at concentration above detection limit shown

J = analyte detected at concentration above instrument detection limit but below method detection limit

-- = sample not analyzed for this analyte

0.000196 Bolded cells indicate the analyte was positively detected.

0.0241 Shaded cells indicate concentrations exceed their respective NMWQCC standards.

DCA - dichloroethane


DCE - dichloroethene

PCE - tetrachloroethene

TCE - trichloroethene



FIGURE 1
Site Location Map
 2014 Annual Groundwater Monitoring Report
 Former Dowell Schlumberger Facility, Artesia, New Mexico



LEGEND

- ▲ Groundwater Extraction Well
- Injection Well
- ⊕ Monitoring Well
- Property Line
- Right of Way Boundary
- × — × Fence

Notes:
UST = underground storage tank
SVE = soil vapor extraction





FIGURE 2
Site Plan
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



Legend

— Property Line

× — × Fence

— Potentiometric Surface Contour (Dashed Where Inferred)

➔ Groundwater Flow Direction

● Monitoring Well

▲ Groundwater Extraction Well

3340.00 Groundwater Elevation (ft amsl)

NM Not Measured

Notes:
UST = underground storage tank
SVE = soil vapor extraction
ft amsl = feet above mean sea level





FIGURE 3
Potentiometric Surface Map – April 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



- Legend**
- Property Line
 - Fence
 - Potentiometric Surface Contour (Dashed Where Inferred)
 - Groundwater Flow Direction
 - Groundwater Extraction Well
 - Injection Well
 - Monitoring Well
 - Groundwater Elevation (ft amsl)
 - NM Not Measured

Notes:
UST = underground storage tank
SVE = soil vapor extraction
ft amsl = feet above mean sea level





FIGURE 4
Potentiometric Surface Map – November 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



Source: Esri, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AEX, Getmapping, Aerogrid, IGN, IGP, swisstopo, and the GIS User Community

LEGEND

- Property Line
- × — × Fence
- Monitoring Well
- ▲ Groundwater Extraction Well

- 0.025 mg/L NMWQCC Standard for 1,1-DCA Isopleth
- 0.005 1,1-DCA Concentration mg/L
- NS Not Sampled

Notes:
J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction
DCA = dichloroethane





FIGURE 5
Isopleth Map for 1,1-DCA – April 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



LEGEND

- Property Line
- x — x Fence
- Monitoring Well
- ▲ Groundwater Extraction Well

0.005 mg/L NMWQCC Standard
for 1,1-DCE Isopleth (Dashed where inferred)
0.005 1,1-DCE Concentration mg/L
NS Not Sampled

Notes:

J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
DCE = Dichloroethene
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction





FIGURE 6
Isopleth Map for 1,1-DCE – April 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



Source: Esri, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AEX, Getmapping, Aerogrid, IGN, IGP, swisstopo, and the GIS User Community

LEGEND

- Property Line
- × × × Fence
- ▲ Groundwater Extraction Well
- Injection Well
- Monitoring Well
- 0.005 mg/L NMWQCC Standard for 1,1-DCE Isopleth (Dashed where inferred)
- 0.005 1,1-DCE Concentration mg/L
- NS Not Sampled

Notes:

J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
DCE = Dichloroethene
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction





FIGURE 7
Isopleth Map for 1,1-DCE – October 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



LEGEND

- Property Line
- Fence
- Monitoring Well
- Groundwater Extraction Well
- 0.020 mg/L NMWQCC Standard for PCE Isopleth (Dashed where inferred)
- 0.005 PCE Concentration mg/L
- NS Not Sampled

Notes:
J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
PCE = tetrachloroethene
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction





FIGURE 8
Isopleth Map for PCE – April 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



LEGEND

- Property Line
- Fence
- Groundwater Extraction Well
- Injection Well
- Monitoring Well
- 0.020 mg/L NMWQCC Standard for PCE Isopleth (Dashed where inferred)
- 0.005 PCE Concentration mg/L
- NS Not Sampled

Notes:

J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
PCE = tetrachloroethene
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction





FIGURE 9
Isopleth Map for PCE – October 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



LEGEND

- Property Line
- Fence
- Monitoring Well
- Groundwater Extraction Well

0.030 mg/L NMWQCC Standard for Naphthalene Isopleth
0.030 Naphthalene Concentration mg/L
NS Not Sampled

Notes:

J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction





FIGURE 10
Isopleth Map for Naphthalene – April 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico



LEGEND

- Property Line
- Fence
- Groundwater Extraction Well
- Injection Well
- Monitoring Well
- 0.030 mg/L NMWQCC Standard for Naphthalene Isoleth
- 0.030 Naphthalene Concentration mg/L
- NS Not Sampled

Notes:

J = Analyte detected at concentration above instrument detection limit but below method detection limit
<0.001 = analyte not detected at concentration above detection limit shown
NMWQCC = New Mexico Water Quality Control Commission
mg/L = milligrams per liter
UST = underground storage tank
SVE = soil vapor extraction




FIGURE 11
Isoleth Map for Naphthalene – October 2014
2014 Annual Groundwater Monitoring Report
Former Dowell Schlumberger Facility, Artesia, New Mexico

Appendix A

Work Plan Amendments and NMOCD Correspondence

Minchak, Jeff/ABQ

From: Hansen, Edward J., EMNRD <edwardj.hansen@state.nm.us>
Sent: Monday, July 15, 2013 2:54 PM
To: Virgilio Cocianni
Cc: VonGonten, Glenn, EMNRD; Strunk Jr, Jim (JStrunkJr@dow.com); Barnett, Cathy/STL; Minchak, Jeff/ABQ
Subject: Discharge Permit (GW-114) Work Plan Amendment Approval - Schlumberger Oilfield Services Facility - Artesia

**RE: Work Plan Amendment
for the Schlumberger Oilfield Services'
Schlumberger Oilfield Services Facility - Artesia
507 E. Richey Ave., Artesia, New Mexico
Discharge Permit (GW-114) Work Plan Amendment Approval**

Dear Mr. Cocianni:

The New Mexico Oil Conservation Division (OCD) has received the Work Plan Amendment for the Schlumberger Oilfield Services Facility - Artesia, dated July 9, 2013. The proposed amendment, submitted for the above-referenced site, indicates that the Schlumberger Oilfield Services (Schlumberger) is substantially complying with the requirements of 20.6.2 NMAC [Water Quality Control Commission (WQCC) Regulations]. Therefore, the OCD conditionally approves the amendment to the work plan:

Schlumberger shall continue to submit an annual report to the OCD by April 1 of the following year.

Please be advised that OCD approval of this amendment does not relieve the owner/operator of responsibility should operations pose a threat to ground water, surface water, human health or the environment. In addition, OCD approval does not relieve the owner/operator of responsibility for compliance with any OCD, federal, state, or local laws and/or regulations.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact at 505-476-3489.

Edward J. Hansen
Hydrologist
Environmental Bureau

P.S.: The OCD has reviewed the Meeting Minutes of June 18, 2013. The OCD has two amendments to the meeting minutes:

- 1) The groundwater remediation for the site (including any investigation or source control) will continue under the discharge permit; i.e., the WQCC regulations, 20.6.2 NMAC (*not NMAC 19.15.29 as stated in the minutes*).
- 2) The discharge permit fee for remediation will be \$2,600 (*not \$2,400 as stated in the minutes*).

From: Virgilio Cocianni [mailto:cocianni-v@slb.com]
Sent: Tuesday, July 09, 2013 6:44 AM
To: Hansen, Edward J., EMNRD; VonGonten, Glenn, EMNRD

Cc: Strunk Jr, Jim (JStrunkJr@dow.com); Cathy Barnett (Cathy.Barnett@CH2M.com); Jeffrey.Minchak@CH2M.com

Subject: Artesia Meeting Notes

Good morning, Ed and Glenn.

Please find attached the minutes of the meeting we held in your offices on June 18th. Forgive us for the delay in getting these minutes to you. If you have any concerns about the content, please let me know.

As we discussed during the meeting, STC and Dow formally request to cease the quarterly reporting requirement and to continue only with the annual report. With your approval, the Second Quarter Monitoring Results report that you are about to receive will be the last quarterly report.

Have a wonderful week.

Best regards,

Vic.

Vic Cocianni

Schlumberger Remediation Manager

Phone: +1-281-285-4747

" Courage doesn't always roar. Sometimes courage is the little voice at the end of the day that says I'll try again tomorrow." Mary Ann Radmacher.

(Please continue to be patient with me, She is still making me).

Minchak, Jeff/ABQ

From: Hansen, Edward J., EMNRD <edwardj.hansen@state.nm.us>
Sent: Thursday, August 22, 2013 4:39 PM
To: cocianni-v@slb.com
Cc: VonGonten, Glenn, EMNRD; Strunk Jr, Jim (JStrunkJr@dow.com); Barnett, Cathy/STL; Minchak, Jeff/ABQ
Subject: Discharge Permit (GW-114) Work Plan (Soil Investigation and Soil Vapor Extraction System Closure) Amendment Approval - Schlumberger Oilfield Services Facility - Artesia

**RE: Work Plan Amendment
for the Schlumberger Oilfield Services'
Schlumberger Oilfield Services Facility - Artesia
507 E. Richey Ave., Artesia, New Mexico
Discharge Permit (GW-114) Work Plan (Soil Investigation and Soil Vapor Extraction System Closure)
Amendment Approval**

Dear Mr. Cocianni:

The Oil Conservation Division (OCD) has received the Work Plan Amendment for the Schlumberger Oilfield Services Facility - Artesia, dated August 15, 2013. The proposed amendment, submitted for the above-referenced site, indicates that the Schlumberger Oilfield Services (Schlumberger) is substantially complying with the requirements of 20.6.2 NMAC [Water Quality Control Commission (WQCC) Regulations]. Therefore, the OCD conditionally approves the amendment to the work plan:

Schlumberger shall submit to the OCD for approval a soil investigation report and soil remediation plan prior to the Soil Vapor Extraction System Closure.

Please be advised that OCD approval of this amendment does not relieve the owner/operator of responsibility should operations pose a threat to ground water, surface water, human health or the environment. In addition, OCD approval does not relieve the owner/operator of responsibility for compliance with any OCD, federal, state, or local laws and/or regulations.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact at 505-476-3489.

Edward J. Hansen
Hydrologist
Environmental Bureau

Minchak, Jeff/ABQ

From: Hansen, Edward J., EMNRD <edwardj.hansen@state.nm.us>
Sent: Thursday, August 22, 2013 4:44 PM
To: cocianni-v@slb.com
Cc: VonGonten, Glenn, EMNRD; Strunk Jr, Jim (JStrunkJr@dow.com); Barnett, Cathy/STL; Minchak, Jeff/ABQ
Subject: Discharge Permit (GW-114) Work Plan (GW Remediation Program) Amendment Approval - Schlumberger Oilfield Services Facility - Artesia

**RE: Work Plan Amendment
for the Schlumberger Oilfield Services'
Schlumberger Oilfield Services Facility - Artesia
507 E. Richey Ave., Artesia, New Mexico
Discharge Permit (GW-114) Work Plan (GW Remediation Program) Amendment Approval**

Dear Mr. Cocianni:

The Oil Conservation Division (OCD) has received the Work Plan Amendment for the Schlumberger Oilfield Services Facility - Artesia, dated August 15, 2013. The proposed amendment, submitted for the above-referenced site, indicates that the Schlumberger Oilfield Services (Schlumberger) is substantially complying with the requirements of 20.6.2 NMAC [Water Quality Control Commission (WQCC) Regulations]. Therefore, the OCD conditionally approves the amendment to the work plan:

Schlumberger shall provide to the OCD for approval a demonstration that the WQCC standards for Manganese (0.2 mg/L) or Sulfate (600.0 mg/L) will not be exceeded in ground water at the site prior to initiation of the ISCO treatment. Also, Schlumberger must monitor for Manganese or Sulfate in ground water depending on the ISCO substrate used for the treatment.

If any other substrate other than permanganate or persulfate is proposed to be used, Schlumberger must obtain OCD approval prior to such use.

Please be advised that OCD approval of this amendment does not relieve the owner/operator of responsibility should operations pose a threat to ground water, surface water, human health or the environment. In addition, OCD approval does not relieve the owner/operator of responsibility for compliance with any OCD, federal, state, or local laws and/or regulations.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact at 505-476-3489.

Edward J. Hansen
Hydrologist
Environmental Bureau

Minchak, Jeff/ABQ

From: Hansen, Edward J., EMNRD <edwardj.hansen@state.nm.us>
Sent: Wednesday, September 18, 2013 1:52 PM
To: Virgilio Cocianni
Cc: VonGonten, Glenn, EMNRD; Strunk Jr, Jim (JStrunkJr@dow.com); Barnett, Cathy/STL; Laggan, Jennifer/DEN; Minchak, Jeff/ABQ
Subject: Discharge Permit (GW-114) Work Plan (GW Monitoring Program) Amendment Approval - Schlumberger Oilfield Services Facility - Artesia

**RE: Work Plan Amendment
for the Schlumberger Oilfield Services'
Schlumberger Oilfield Services Facility - Artesia
507 E. Richey Ave., Artesia, New Mexico
Discharge Permit (GW-114) Work Plan (GW Monitoring Program) Amendment Approval**

Dear Mr. Cocianni:

The Oil Conservation Division (OCD) has received the Work Plan Amendment for the Schlumberger Oilfield Services Facility - Artesia, dated September 17, 2013. The proposed amendment, submitted for the above-referenced site, indicates that the Schlumberger Oilfield Services (Schlumberger) is substantially complying with the requirements of 20.6.2 NMAC [Water Quality Control Commission (WQCC) Regulations]. Therefore, the OCD conditionally approves the amendment to the work plan:

Schlumberger shall continue to monitoring ground water at MW-1 and MW-20 at least annually.

Schlumberger may discontinue monitoring ground water at MW-19.

Schlumberger shall use a cement grout with 1% to 3% bentonite and a 3-foot cap of cement to the surface when plugging the monitoring wells.

Schlumberger shall submit to OCD a plugging report within 180 days.

Please be advised that OCD approval of this amendment does not relieve the owner/operator of responsibility should operations pose a threat to ground water, surface water, human health or the environment. In addition, OCD approval does not relieve the owner/operator of responsibility for compliance with any OCD, federal, state, or local laws and/or regulations.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact at 505-476-3489.

Edward J. Hansen
Hydrologist
Environmental Bureau

Appendix B
NMOSE Well Permits, Soil Boring Logs, and Well Completion
Diagrams

Scott A. Verhines, P.E.
State Engineer



Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

**STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER**

Trn Nbr: 552041
File Nbr: C 03774 POD1 MONITOR

Aug. 05, 2014

Jeffrey Minchak, P.G.
Senior Project Manager
CH2M HILL
3721 Rutledge Rd. NE, Suite B-1
Albuquerque, NM 87109

RE: VIRGILIO COCIANNI, SCHLUMBERGER TECHNOLOGY CORP


Greetings:

Enclosed is your copy of the above numbered permit that has been approved subject to the conditions set forth on the approval page. In accordance with the conditions of approval, the well can only be tested for 10 cumulative days, and the well is to be plugged on or before 08/31/2015, unless a permit to use the water is acquired from this office.

A Well Record & Log (OSE Form wr-20) shall be filed in this office within twenty (20) days after completion of drilling, but no later than 08/31/2015.

Appropriate forms can be downloaded from the OSE website www.ose.state.nm.us or will be mailed upon request.

Sincerely,


Andy Morley
(575) 622-6521

Enclosure

File No.

C-3774

NEW MEXICO OFFICE OF THE STATE ENGINEER

APPLICATION FOR PERMIT TO DRILL A WELL
WITH NO CONSUMPTIVE USE OF WATER

(check applicable box):

For fees, see State Engineer website: <http://www.ose.state.nm.us/>

2-34841

Purpose:

☐ Pollution Control And / Or Recovery☐ Geo-Thermal☐ Exploratory☐ Construction Site De-Watering☐ Other (Describe):☒ Monitoring☐ Mineral De-Watering

A separate permit will be required to apply water to beneficial use.

☐ Temporary Request - Requested Start Date:

Requested End Date:

Plugging Plan of Operations Submitted? ☐ Yes ☒ No

1. APPLICANT(S)

Name: Virgilio Cocianni	Name:
Contact or Agent: check here if Agent ☐ Schlumberger Technology Corporation	Contact or Agent: check here if Agent ☐
Mailing Address: 105 Industrial Boulevard	Mailing Address:
City: Sugar Land	City:
State: TX Zip Code: 77478	State: Zip Code:
Phone: ☐ Home ☐ Cell Phone (Work): (281) 285-4747	Phone: ☐ Home ☐ Cell Phone (Work):
E-mail (optional): cocianni-v@slb.com	E-mail (optional):

FOR OSE INTERNAL USE

Application for Permit, Form wr-07, Rev 4/12/12

File Number:

C-3774

Trn Number:

552041

Trans Description (optional):

PODI Monitor

Sub-Basin:

CUB

PCW/LOG Due Date:

8-31-15

2. WELL(S) Describe the well(s) applicable to this application.

Location Required: Coordinate location must be reported in NM State Plane (NAD 83), UTM (NAD 83), or Latitude/Longitude (Lat/Long - WGS84). District II (Roswell) and District VII (Cimarron) customers, provide a PLSS location in addition to above.			
☐ NM State Plane (NAD83) (Feet) ☐ NM West Zone ☐ NM East Zone ☐ NM Central Zone		☐ UTM (NAD83) (Meters) ☐ Zone 12N ☐ Zone 13N	
		☒ Lat/Long (WGS84) (to the nearest 1/10 th of second)	
Well Number (if known):	X or Easting or Longitude:	Y or Northing or Latitude:	Provide if known: -Public Land Survey System (PLSS) (Quarters or Halves, Section, Township, Range) OR - Hydrographic Survey Map & Tract; OR - Lot, Block & Subdivision; OR - Land Grant Name
MW-34	103.8945949	32.43942826	SW 1/4, S4, T17S, R26E
NOTE: If more well locations need to be described, complete form WR-08 (Attachment 1 - POD Descriptions) Additional well descriptions are attached: ☐ Yes ☒ No If yes, how many _____			
Other description relating well to common landmarks, streets, or other: Former Dowell Schlumber Facility, 507 East Richey Avenue, Artesia, NM 88210			
Well is on land owned by: Schlumberger Technology Corporation			
Well Information: NOTE: If more than one (1) well needs to be described, provide attachment. Attached? ☐ Yes ☒ No If yes, how many _____			
Approximate depth of well (feet): 35.00		Outside diameter of well casing (inches): 4.50	
Driller Name: National Drilling		Driller License Number: WD-1210	

3. ADDITIONAL STATEMENTS OR EXPLANATIONS

For Item 4 - The monitoring well is required to provide data related to the investigation and remediation of groundwater that contains chlorinated solvents concentrations in exceedance of New Mexico Water Quality Control Commission standards. Monitoring events are performed semi-annually and are expected to continue for up to 5-7 years.
--

FOR OSE INTERNAL USE

Application for Permit, Form wr-07

File Number:

C-3774

Trn Number:

55204

4. SPECIFIC REQUIREMENTS: The applicant must include the following, as applicable to each well type. Please check the appropriate boxes, to indicate the information has been included and/or attached to this application:

Exploratory: ☐ Include a description of any proposed pump test, if applicable.	Pollution Control and/or Recovery: ☐ Include a plan for pollution control/recovery, that includes the following: ☐ A description of the need for the pollution control or recovery operation. ☐ The estimated maximum period of time for completion of the operation. ☐ The annual diversion amount. ☐ The annual consumptive use amount. ☐ The maximum amount of water to be diverted and injected for the duration of the operation. ☐ The method and place of discharge.	Construction De-Watering: ☐ Include a description of the proposed dewatering operation, ☐ The estimated duration of the operation, ☐ The maximum amount of water to be diverted, ☐ A description of the need for the dewatering operation, and, ☐ A description of how the diverted water will be disposed of.	Mine De-Watering: ☐ Include a plan for pollution control/recovery, that includes the following: ☐ A description of the need for mine dewatering. ☐ The estimated maximum period of time for completion of the operation. ☐ The source(s) of the water to be diverted. ☐ The geohydrologic characteristics of the aquifer(s). ☐ The maximum amount of water to be diverted per annum. ☐ The maximum amount of water to be diverted for the duration of the operation. ☐ The quality of the water. ☐ The method of measurement of water diverted.
Monitoring: ☒ Include the reason for the monitoring well, and, ☒ The duration of the planned monitoring.	☐ The method of measurement of water produced and discharged. ☐ The source of water to be injected. ☐ The method of measurement of water injected. ☐ The characteristics of the aquifer, ☐ The method of determining the resulting annual consumptive use of water and depletion from any related stream system. ☐ Proof of any permit required from the New Mexico Environment Department. ☐ An access agreement if the applicant is not the owner of the land on which the pollution plume control or recovery well is to be located.	Geo-Thermal: ☐ Include a description of the geothermal heat exchange project, ☐ The amount of water to be diverted and re-injected for the project, ☐ The time frame for constructing the geothermal heat exchange project, and, ☐ The duration of the project. ☐ Preliminary surveys, design data, and additional information shall be included to provide all essential facts relating to the request.	☐ The recharge of water to the aquifer. ☐ Description of the estimated area of hydrologic effect of the project. ☐ The method and place of discharge. ☐ An estimation of the effects on surface water rights and underground water rights from the mine dewatering project. ☐ A description of the methods employed to estimate effects on surface water rights and underground water rights. ☐ Information on existing wells, rivers, springs, and wetlands within the area of hydrologic effect.

ACKNOWLEDGEMENT

I, We (name of applicant(s)), Virgilio Cocianni

Print Name(s)

affirm that the foregoing statements are true to the best of (my, our) knowledge and belief,


Applicant Signature

Applicant Signature

ACTION OF THE STATE ENGINEER


This application is:

☒ approved ☐ partially approved ☐ denied

provided it is not exercised to the detriment of any others having existing rights, and is not contrary to the conservation of water in New Mexico nor detrimental to the public welfare and further subject to the attached conditions of approval.

Witness my hand and seal this 5th day of August 20 14, for the State Engineer,

Scott A Verhines, P.E., State Engineer

By: 
Signature

Print

Title: Andy Morley, District II Manager

FOR OSE INTERNAL USE

Application for Permit, Form wr-07

File Number:

C-3774

Trn Number:

SS2041

**NEW MEXICO STATE ENGINEER OFFICE
PERMIT TO EXPLORE**

SPECIFIC CONDITIONS OF APPROVAL

- 4 No water shall be appropriated and beneficially used under this permit.
- 6 The well shall be plugged upon completion of the permitted use, and a plugging report shall be filed with the State Engineer within 10 days.
- 7 The Permittee shall utilize the highest and best technology available to ensure conservation of water to the maximum extent practical.
- B The well shall be drilled by a driller licensed in the State of New Mexico in accordance with Section 72-12-12 New Mexico Statutes Annotated.
- C Driller's well record must be filed with the State Engineer within 20 days after the well is drilled or driven. Well record forms will be provided by the State Engineer upon request.
- C2 No water shall be diverted from this well except for testing purposes which shall not exceed **ten (10)** cumulative days, and well shall be plugged or capped on or before , unless a permit to use water from this well is acquired from the Office of the State Engineer.
- P The well shall be constructed, maintained, and operated to prevent inter-aquifer exchange of water and to prevent loss of hydraulic head between geologic zones.
- LOG The Point of Diversion C 03774 POD1 must be completed and the Well Log filed on or before 08/31/2015.

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:34:52

WR File Number: C-MW34
Purpose: OTHER

Applicant First Name: VIRILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

NE 1/4 of NE 1/4 of SE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 21.9 Seconds N
Longitude: 103 Degrees 53 Minutes 40.5 Seconds W

Universal Transverse Mercator Zone: 13N

NAD 1983(92) (Meters)	N: 3,589,682	E: 603,913
NAD 1983(92) (Survey Feet)	N: 11,777,150	E: 1,981,339
NAD 1927 (Meters)	N: 3,589,480	E: 603,962
NAD 1927 (Survey Feet)	N: 11,776,486	E: 1,981,499

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,677	E: 206,255
NAD 1983(92) (Survey Feet)	N: 523,873	E: 676,689
NAD 1927 (Meters)	N: 159,658	E: 193,703
NAD 1927 (Survey Feet)	N: 523,812	E: 635,508

Scott A. Verhines, P.E.
State Engineer



Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

**STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER**

Trn Nbr: 552040
File Nbr: C 03773 POD1 POLLUTION CONTROL

Aug. 05, 2014

Jeffrey Minchak, P.G.
Senior Project Manager
CH2M HILL
3721 Rutledge Rd. NE, Suite B-1
Albuquerque, NM 87109

RE: VIRGILIO COCIANNI, SCHLUMBERGER TECHNOLOGY CORP

Greetings:

Enclosed is your copy of the above numbered permit that has been approved subject to the conditions set forth on the approval page. In accordance with the conditions of approval, the well can only be tested for 10 cumulative days, and the well is to be plugged on or before 08/31/2015, unless a permit to use the water is acquired from this office.

A Well Record & Log (OSE Form wr-20) shall be filed in this office within twenty (20) days after completion of drilling, but no later than 08/31/2015.

Appropriate forms can be downloaded from the OSE website www.ose.state.nm.us or will be mailed upon request.

Sincerely,


Andy Morley
(575) 622-6521

Enclosure

File No.

C-3773

NEW MEXICO OFFICE OF THE STATE ENGINEER

APPLICATION FOR PERMIT TO DRILL A WELL
WITH NO CONSUMPTIVE USE OF WATER

(check applicable box):

For fees, see State Engineer website: <http://www.ose.state.nm.us/>

2-31841

- Purpose:
- ☒ Pollution Control And / Or Recovery ☐ Geo-Thermal
- ☐ Exploratory ☐ Construction Site De-Watering ☐ Other (Describe):
- ☐ Monitoring ☐ Mineral De-Watering

A separate permit will be required to apply water to beneficial use.

☐ Temporary Request - Requested Start Date:

Requested End Date:

Plugging Plan of Operations Submitted? ☐ Yes ☒ No

1. APPLICANT(S)

Name: Virgilio Cocianni	Name:
Contact or Agent: check here if Agent ☐ Schlumberger Technology Corporation	Contact or Agent: check here if Agent ☐
Mailing Address: 105 Industrial Boulevard	Mailing Address:
City: Sugar Land	City:
State: TX Zip Code: 77478	State: Zip Code:
Phone: ☐ Home ☐ Cell Phone (Work): (281) 285-4747	Phone: ☐ Home ☐ Cell Phone (Work):
E-mail (optional): cocianni-v@slb.com	E-mail (optional):

FOR OSE INTERNAL USE

Application for Permit, Form wr-07, Rev 4/12/12

File Number:

C-3773

Trn Number:

SS2040

Trans Description (optional):

POD1

Pol Control

Sub-Basin:

CUB

PCW/LOG Due Date:

8-31-15

2. WELL(S) Describe the well(s) applicable to this application.

Location Required: Coordinate location must be reported in NM State Plane (NAD 83), UTM (NAD 83), <u>or</u> Latitude/Longitude (Lat/Long - WGS84). District II (Roswell) and District VII (Cimarron) customers, provide a PLSS location in addition to above.			
☐ NM State Plane (NAD83) (Feet) ☐ NM West Zone ☐ NM East Zone ☐ NM Central Zone		☐ UTM (NAD83) (Meters) ☐ Zone 12N ☐ Zone 13N	
☒ Lat/Long (WGS84) (to the nearest 1/10 th of second)			
Well Number (if known):	X or Easting or Longitude:	Y or Northing or Latitude:	Provide if known: -Public Land Survey System (PLSS) (Quarters or Halves, Section, Township, Range) OR - Hydrographic Survey Map & Tract; OR - Lot, Block & Subdivision; OR - Land Grant Name
EW-03	103.8941086	32.4399139	SW 1/4, S4, T17S, R26E
NOTE: If more well locations need to be described, complete form WR-08 (Attachment 1 – POD Descriptions) Additional well descriptions are attached: ☐ Yes ☒ No If yes, how many _____			
Other description relating well to common landmarks, streets, or other: Former Dowell Schlumber Facility, 507 East Richey Avenue, Artesia, NM 88210			
Well is on land owned by: Schlumberger Technology Corporation			
Well Information: NOTE: If more than one (1) well needs to be described, provide attachment. Attached? ☐ Yes ☒ No If yes, how many _____			
Approximate depth of well (feet): 60.00			Outside diameter of well casing (inches): 4.50
Driller Name: National EWP			Driller License Number: WD-1210

3. ADDITIONAL STATEMENTS OR EXPLANATIONS

Pollution Control/Recovery Plan
Former Dowell Schlumberger Facility
507 East Richey Avenue, Artesia, New Mexico

The following information is provided to capture the applicable items under Section 4. Specific Requirements, of the Application for Permit to Drill a Well with No Consumptive Use of Water.

1. Description of the need for the pollution control or recovery operation.

The remediation system operation is required to remediate chlorinated hydrocarbons present in groundwater as a result of historical site operations as an oil and gas support facility. Chlorinated hydrocarbons are currently present in groundwater at concentrations that exceed New Mexico Water Quality Control Commission standards. The investigation and remediation of the site is being performed under Groundwater Discharge Permit GW-114, under the New Mexico Oil Conservation Division Environmental Bureau.

2. Estimated maximum period of time for completion of the operation.

Injection to be completed in a single operation expected to take 6-8 weeks. Groundwater extraction, treatment, and horizontal well injection system to operate for up to 5 years.

3. Annual diversion amount.

Groundwater extraction, treatment, and horizontal well injection system – 7,884,000 gallons (15 gpm)

Injections, 1st year only – 930,000 gallons maximum anticipated. This water is to come from the groundwater extraction system and is included in the 7,884,000 gallons total above.

4. Annual consumptive use amount.

Zero gallons; no consumptive use will occur. The system is a closed-loop and water will be pumped onsite and re-injected onsite using horizontal and vertical injection wells.

5. Maximum amount of water to be diverted and injected for the duration of the operation.

Injections – One time maximum of 930,000 gallons, anticipated during 2014.

Groundwater extraction, treatment, and horizontal well injection – 39,420,000 gallons (7,884,000 gallons per year x 5 years)

6. Method and place of discharge

Vertical Injections – 8 injection wells in a linear transect roughly 300 feet long. Each injection well will receive a maximum of 116,250 gallons of 1% potassium permanganate solution.

Horizontal Injection - the groundwater extraction and treatment system discharges to a buried 200 ft long horizontal injection well. The vertical component of the horizontal injection well will be sealed with a bentonite clay seal to prevent downward vertical migration adjacent to the pipe.

STATE ENGINEER OFFICE
JUL 10 2014 10 11 AM
10 11 AM

4. SPECIFIC REQUIREMENTS: The applicant must include the following, as applicable to each well type. Please check the appropriate boxes, to indicate the information has been included and/or attached to this application:

Exploratory: ☐ Include a description of any proposed pump test, if applicable.	Pollution Control and/or Recovery: ☒ Include a plan for pollution control/recovery, that includes the following: ☒ A description of the need for the pollution control or recovery operation. ☒ The estimated maximum period of time for completion of the operation. ☒ The annual diversion amount. ☒ The annual consumptive use amount. ☒ The maximum amount of water to be diverted and injected for the duration of the operation. ☒ The method and place of discharge.	Construction De-Watering: ☐ Include a description of the proposed dewatering operation, ☐ The estimated duration of the operation, ☐ The maximum amount of water to be diverted, ☐ A description of the need for the dewatering operation, and, ☐ A description of how the diverted water will be disposed of.	Mine De-Watering: ☐ Include a plan for pollution control/recovery, that includes the following: ☐ A description of the need for mine dewatering. ☐ The estimated maximum period of time for completion of the operation. ☐ The source(s) of the water to be diverted. ☐ The geohydrologic characteristics of the aquifer(s). ☐ The maximum amount of water to be diverted per annum. ☐ The maximum amount of water to be diverted for the duration of the operation. ☐ The quality of the water. ☐ The method of measurement of water diverted.
Monitoring: ☐ Include the reason for the monitoring well, and, ☐ The duration of the planned monitoring.	☒ The method of measurement of water produced and discharged. ☒ The source of water to be injected. ☒ The method of measurement of water injected. ☒ The characteristics of the aquifer. ☒ The method of determining the resulting annual consumptive use of water and depletion from any related stream system. ☒ Proof of any permit required from the New Mexico Environment Department. ☒ An access agreement if the applicant is not the owner of the land on which the pollution plume control or recovery well is to be located.	Geo-Thermal: ☐ Include a description of the geothermal heat exchange project, ☐ The amount of water to be diverted and re-injected for the project, ☐ The time frame for constructing the geothermal heat exchange project, and, ☐ The duration of the project. ☐ Preliminary surveys, design data, and additional information shall be included to provide all essential facts relating to the request.	☐ The recharge of water to the aquifer. ☐ Description of the estimated area of hydrologic effect of the project. ☐ The method and place of discharge. ☐ An estimation of the effects on surface water rights and underground water rights from the mine dewatering project. ☐ A description of the methods employed to estimate effects on surface water rights and underground water rights. ☐ Information on existing wells, rivers, springs, and wetlands within the area of hydrologic effect.

ACKNOWLEDGEMENT

I, We (name of applicant(s)), Virgilio Cocianni

Print Name(s)

affirm that the foregoing statements are true to the best of (my, our) knowledge and belief.


Applicant Signature

Applicant Signature

ACTION OF THE STATE ENGINEER

This application is:

☒ approved

☐ partially approved


☐ denied

provided it is not exercised to the detriment of any others having existing rights, and is not contrary to the conservation of water in New Mexico nor detrimental to the public welfare and further subject to the attached conditions of approval.

Witness my hand and seal this 5th day of August 20 14, for the State Engineer,

Scott A Verhines, P.E.

State Engineer

By: 
Signature

Print

Title: Andy Morley, District II Manager

FOR OSE INTERNAL USE

Application for Permit, Form wr-07

File Number:

C-3773

Trn Number:

SS2040

**NEW MEXICO STATE ENGINEER OFFICE
PERMIT TO EXPLORE**

SPECIFIC CONDITIONS OF APPROVAL

- 4 No water shall be appropriated and beneficially used under this permit.
- 5B A totalizing meter shall be installed before the first branch of the discharge line from the well and the installation shall be acceptable to the State Engineer; the Engineer shall be advised of the make, model, serial number, date of installation, and initial reading of the meter prior to appropriation of water; pumping records shall be submitted to the District Supervisor on or before the 10th of Jan., April, July, and Oct. of each year for the 3 preceding calendar months.
- 7 The Permittee shall utilize the highest and best technology available to ensure conservation of water to the maximum extent practical.
- B The well shall be drilled by a driller licensed in the State of New Mexico in accordance with Section 72-12-12 New Mexico Statutes Annotated.
- C Driller's well record must be filed with the State Engineer within 20 days after the well is drilled or driven. Well record forms will be provided by the State Engineer upon request.
- C2 No water shall be diverted from this well except for testing purposes which shall not exceed **ten (10)** cumulative days, and well shall be plugged or capped on or before , unless a permit to use water from this well is acquired from the Office of the State Engineer.

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:36:33

WR File Number: C-EW-03
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SE 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 23.7 Seconds N
Longitude: 103 Degrees 53 Minutes 38.8 Seconds W

Universal Transverse Mercator Zone: 13N


NAD 1983(92) (Meters)	N: 3,589,737	E: 603,958
NAD 1983(92) (Survey Feet)	N: 11,777,328	E: 1,981,487
NAD 1927 (Meters)	N: 3,589,535	E: 604,007
NAD 1927 (Survey Feet)	N: 11,776,665	E: 1,981,647

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,731	E: 206,301
NAD 1983(92) (Survey Feet)	N: 524,050	E: 676,838
NAD 1927 (Meters)	N: 159,712	E: 193,749
NAD 1927 (Survey Feet)	N: 523,990	E: 635,657

NEW MEXICO OFFICE OF STATE ENGINEER

Locator Tool Report



WR File Number: C-EW-03

Scale: 1:19,134

Northing/Easting: UTM83(92) (Meter): N: 3,589,737

E: 603,958

Northing/Easting: SPCS83(92) (Feet): N: 524,050

E: 676,838

GW Basin: Carlsbad

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552040
File Nbr: C 03773
Well File Nbr: C 03773 POD1

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03773 POD1

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

Scott A. Verhines, P.E.
State Engineer



Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

**STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER**

Trn Nbr: 552039
File Nbr: C 03772 POD1-8 POLLUTION CONTROL

Aug. 05, 2014

Jeffrey Minchak, P.G.
Senior Project Manager
CH2M HILL
3721 Rutledge Rd. NE, Suite B-1
Albuquerque, NM 87109

RE: VIRGILIO COCIANNI, SCHLUMBERGER TECHNOLOGY CORP

Greetings:

Enclosed is your copy of the above numbered permit that has been approved subject to the conditions set forth on the approval page. In accordance with the conditions of approval, the well can only be tested for 10 cumulative days, and the well is to be plugged on or before 08/31/2015, unless a permit to use the water is acquired from this office.

A Well Record & Log (OSE Form wr-20) shall be filed in this office within twenty (20) days after completion of drilling, but no later than 08/31/2015.

Appropriate forms can be downloaded from the OSE website www.ose.state.nm.us or will be mailed upon request.

Sincerely,

fw *ym*
Andy Morley
(575) 622-6521

Enclosure

File No.

C-3772



NEW MEXICO OFFICE OF THE STATE ENGINEER

APPLICATION FOR PERMIT TO DRILL A WELL WITH NO CONSUMPTIVE USE OF WATER



(check applicable box):

For fees, see State Engineer website: <http://www.ose.state.nm.us/>

2-34841

- Purpose:
- ☒ Pollution Control And / Or Recovery ☐ Geo-Thermal
- ☐ Exploratory ☐ Construction Site De-Watering ☐ Other (Describe):
- ☐ Monitoring ☐ Mineral De-Watering

A separate permit will be required to apply water to beneficial use.

☐ Temporary Request - Requested Start Date:

Requested End Date:

Plugging Plan of Operations Submitted? ☐ Yes ☒ No

1. APPLICANT(S)

Name: Virgilio Cocianni	Name:
Contact or Agent: Schlumberger Technology Corporation check here if Agent ☐	Contact or Agent: check here if Agent ☐
Mailing Address: 105 Industrial Boulevard	Mailing Address:
City: Sugar Land	City:
State: TX Zip Code: 77478	State: Zip Code:
Phone: ☐ Home ☐ Cell Phone (Work): (281) 285-4747	Phone: ☐ Home ☐ Cell Phone (Work):
E-mail (optional): cocianni-v@slb.com	E-mail (optional):

FOR OSE INTERNAL USE

Application for Permit, Form wr-07, Rev 4/12/12

File Number: C-3772	Trn Number: 552039
Trans Description (optional): POD-1-8 Pol Control	
Sub-Basin: CUB	
PCW/LOG Due Date: 8-31-15	

2. WELL(S) Describe the well(s) applicable to this application.

Location Required: Coordinate location must be reported in NM State Plane (NAD 83), UTM (NAD 83), <u>or</u> Latitude/Longitude (Lat/Long - WGS84). District II (Roswell) and District VII (Cimarron) customers, provide a PLSS location in addition to above.			
☐ NM State Plane (NAD83) (Feet) ☐ UTM (NAD83) (Meters) ☒ Lat/Long (WGS84) (to the nearest 1/10 th of second)			
☐ NM West Zone ☐ Zone 12N ☐ NM East Zone ☐ Zone 13N ☐ NM Central Zone			
Well Number (if known):	X or Easting or Longitude:	Y or Northing or Latitude:	Provide if known: -Public Land Survey System (PLSS) (Quarters or Halves , Section, Township, Range) OR - Hydrographic Survey Map & Tract; OR - Lot, Block & Subdivision; OR - Land Grant Name
INJ. WELL	103.8951655	32.43937252	SW 1/4, S4, T17S, R26E
INJ. WELL	103.8952709	32.43946595	SW 1/4, S4, T17S, R26E
INJ. WELL	103.8953684	32.43955935	SW 1/4, S4, T17S, R26E
INJ. WELL	103.895466	32.43965275	SW 1/4, S4, T17S, R26E
INJ. WELL	103.8955596	32.43974281	SW 1/4, S4, T17S, R26E
INJ. WELL	103.8956532	32.43982955	SW 1/4, S4, T17S, R26E
INJ. WELL	103.8957469	32.43991961	SW 1/4, S4, T17S, R26E
INJ. WELL	103.8958366	32.44000301	SW 1/4, S4, T17S, R26E
NOTE: If more well locations need to be described, complete form WR-08 (Attachment 1 – POD Descriptions)			
Additional well descriptions are attached: ☐ Yes ☒ No If yes, how many _____			
Other description relating well to common landmarks, streets, or other: Former Dowell Schlumber Facility, 507 East Richey Avenue, Artesia, NM 88210			
Well is on land owned by: Schlumberger Technology Corporation			
Well Information: NOTE: If more than one (1) well needs to be described, provide attachment. Attached? ☐ Yes ☒ No If yes, how many _____			
Approximate depth of well (feet): 32.00		Outside diameter of well casing (inches): 2.375	
Driller Name: National Ewp		Driller License Number: WD-1210	

3. ADDITIONAL STATEMENTS OR EXPLANATIONS

FOR OSE INTERNAL USE

Application for Permit, Form wr-07

File Number: **C-3172**

Tm Number: **552039**

4. SPECIFIC REQUIREMENTS: The applicant must include the following, as applicable to each well type. Please check the appropriate boxes, to indicate the information has been included and/or attached to this application:

Exploratory: ☐ Include a description of any proposed pump test, if applicable.	Pollution Control and/or Recovery: ☒ Include a plan for pollution control/recovery, that includes the following: ☒ A description of the need for the pollution control or recovery operation. ☒ The estimated maximum period of time for completion of the operation. ☒ The annual diversion amount. ☒ The annual consumptive use amount. ☒ The maximum amount of water to be diverted and injected for the duration of the operation. ☒ The method and place of discharge.	Construction De-Watering: ☐ Include a description of the proposed dewatering operation, ☐ The estimated duration of the operation, ☐ The maximum amount of water to be diverted, ☐ A description of the need for the dewatering operation, and, ☐ A description of how the diverted water will be disposed of.	Mine De-Watering: ☐ Include a plan for pollution control/recovery, that includes the following: ☐ A description of the need for mine dewatering. ☐ The estimated maximum period of time for completion of the operation. ☐ The source(s) of the water to be diverted. ☐ The geohydrologic characteristics of the aquifer(s). ☐ The maximum amount of water to be diverted per annum. ☐ The maximum amount of water to be diverted for the duration of the operation. ☐ The quality of the water.
Monitoring: ☐ Include the reason for the monitoring well, and, ☐ The duration of the planned monitoring.	☒ The method of measurement of water produced and discharged. ☒ The source of water to be injected. ☒ The method of measurement of water injected. ☒ The characteristics of the aquifer. ☒ The method of determining the resulting annual consumptive use of water and depletion from any related stream system. ☒ Proof of any permit required from the New Mexico Environment Department. ☒ An access agreement if the applicant is not the owner of the land on which the pollution plume control or recovery well is to be located.	Geo-Thermal: ☐ Include a description of the geothermal heat exchange project, ☐ The amount of water to be diverted and re-injected for the project, ☐ The time frame for constructing the geothermal heat exchange project, and, ☐ The duration of the project. ☐ Preliminary surveys, design data, and additional information shall be included to provide all essential facts relating to the request.	☐ The method of measurement of water diverted. ☐ The recharge of water to the aquifer. ☐ Description of the estimated area of hydrologic effect of the project. ☐ The method and place of discharge. ☐ An estimation of the effects on surface water rights and underground water rights from the mine dewatering project. ☐ A description of the methods employed to estimate effects on surface water rights and underground water rights. ☐ Information on existing wells, rivers, springs, and wetlands within the area of hydrologic effect.

ACKNOWLEDGEMENT

I, We (name of applicant(s)), Virgilio Cocianni

Print Name(s)

affirm that the foregoing statements are true to the best of (my, our) knowledge and belief.


 Applicant Signature

Applicant Signature

ACTION OF THE STATE ENGINEER

This application is:

☒ approved ☐ partially approved ☐ denied

provided it is not exercised to the detriment of any others having existing rights, and is not contrary to the conservation of water in New Mexico nor detrimental to the public welfare and further subject to the attached conditions of approval.

FOR OSE INTERNAL USE

Application for Permit, Form wr-07

File Number:

C-3772

Trn Number:

552039

Pollution Control/Recovery Plan
Former Dowell Schlumberger Facility
507 East Richey Avenue, Artesia, New Mexico

The following information is provided to capture the applicable items under Section 4. Specific Requirements, of the Application for Permit to Drill a Well with No Consumptive Use of Water.

1. Description of the need for the pollution control or recovery operation.

The remediation system operation is required to remediate chlorinated hydrocarbons present in groundwater as a result of historical site operations as an oil and gas support facility. Chlorinated hydrocarbons are currently present in groundwater at concentrations that exceed New Mexico Water Quality Control Commission standards. The investigation and remediation of the site is being performed under Groundwater Discharge Permit GW-114, under the New Mexico Oil Conservation Division Environmental Bureau.

2. Estimated maximum period of time for completion of the operation.

Injection to be completed in a single operation expected to take 6-8 weeks. Groundwater extraction, treatment, and horizontal well injection system to operate for up to 5 years.

3. Annual diversion amount.

Groundwater extraction, treatment, and horizontal well injection system – 7,884,000 gallons (15 gpm)

Injections, 1st year only – 930,000 gallons maximum anticipated. This water is to come from the groundwater extraction system and is included in the 7,884,000 gallons total above.

4. Annual consumptive use amount.

Zero gallons; no consumptive use will occur. The system is a closed-loop and water will be pumped onsite and re-injected onsite using horizontal and vertical injection wells.

5. Maximum amount of water to be diverted and injected for the duration of the operation.

Injections – One time maximum of 930,000 gallons, anticipated during 2014.

Groundwater extraction, treatment, and horizontal well injection – 39,420,000 gallons (7,884,000 gallons per year x 5 years)

6. Method and place of discharge

Vertical Injections – 8 injection wells in a linear transect roughly 300 feet long. Each injection well will receive a maximum of 116,250 gallons of 1% potassium permanganate solution.

Horizontal Injection - the groundwater extraction and treatment system discharges to a buried 200 ft long horizontal injection well. The vertical component of the horizontal injection well will be sealed with a bentonite clay seal to prevent downward vertical migration adjacent to the pipe.

STATE ENGINEER OFFICE
NEW MEXICO
JUN 11 11:55 AM

**NEW MEXICO STATE ENGINEER OFFICE
PERMIT TO EXPLORE**

SPECIFIC CONDITIONS OF APPROVAL

- 4 No water shall be appropriated and beneficially used under this permit.
- 5B A totalizing meter shall be installed before the first branch of the discharge line from the well and the installation shall be acceptable to the State Engineer; the Engineer shall be advised of the make, model, serial number, date of installation, and initial reading of the meter prior to appropriation of water; pumping records shall be submitted to the District Supervisor on or before the 10th of Jan., April, July, and Oct. of each year for the 3 preceding calendar months.
- 7 The Permittee shall utilize the highest and best technology available to ensure conservation of water to the maximum extent practical.
- B The well shall be drilled by a driller licensed in the State of New Mexico in accordance with Section 72-12-12 New Mexico Statutes Annotated.
- C Driller's well record must be filed with the State Engineer within 20 days after the well is drilled or driven. Well record forms will be provided by the State Engineer upon request.
- C2 No water shall be diverted from this well except for testing purposes which shall not exceed **ten (10)** cumulative days, and well shall be plugged or capped on or before , unless a permit to use water from this well is acquired from the Office of the State Engineer.

NEW MEXICO STATE ENGINEER OFFICE
PERMIT TO EXPLORE


ACTION OF STATE ENGINEER

Notice of Intention Rcvd: Date Rcvd. Corrected:
Formal Application Rcvd: 08/04/2014 Pub. of Notice Ordered:
Date Returned - Correction: Affidavit of Pub. Filed:

This application is approved provided it is not exercised to the detriment of any others having existing rights, and is not contrary to the conservation of water in New Mexico nor detrimental to the public welfare of the state; and further subject to the specific conditions listed previously.

Witness my hand and seal this 5th day of Aug A.D., 2014

Scott A. Verhines, P.E., State Engineer

By: 
Andy Morley

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD1

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD1

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD2

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD2

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD3

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD3

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD4

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD4

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()

Circle appropriate unit of measure.

Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD5

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD5

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

**STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER**

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD6

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD6

Serial Number: _____ Meter Make: _____
Number of Dials: _____ Multiplier: (0) (00) (000)
Number of dials that move on the left side of dial on meter. Circle number of zeros that don't move on right side of dial on meter.
Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD7

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD7

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

METER INSTALLATION AND
INSPECTION FORM



STATE ENGINEER OFFICE
Roswell Office
1900 WEST SECOND STREET
ROSWELL, NM 88201

STATE OF NEW MEXICO
OFFICE OF THE STATE ENGINEER

Trn Nbr: 552039
File Nbr: C 03772
Well File Nbr: C 03772 POD8

VIRGILIO COCIANNI
SCHLUMBERGER TECHNOLOGY CORP
105 INDUSTRIAL BOULEVARD
SUGAR LAND, TX 77478

1. WATER METER INFORMATION:

Well File Nbr: C 03772 POD8

Serial Number: _____

Meter Make: _____

Number of Dials: _____

Multiplier: (0) (00) (000)

Number of dials that move on the
left side of dial on meter.

Circle number of zeros that don't
move on right side of dial on meter.

Unit of Measure: (GALLONS) (CUBIC FEET) (BARRELS) (ACRE-FEET) ()
Circle appropriate unit of measure. Specify Other

Initial Reading: _____ Initial Reading Date: _____

2. COMMENTS:

Submitted By: _____

Date: _____

wellcon5

OFFICE OF THE STATE ENGINEER/INTERSTATE STREAM COMMISSION – ROSWELL OFFICE

OFFICIAL RECEIPT NUMBER: 2- 34841 DATE: Aug 4, 2014 FILE NO.: _____

TOTAL: 50.00 RECEIVED: _____ DOLLARS CHECK NO.: 3169 CASH: _____

PAYOR: Jeffrey Mincey ADDRESS: 1446 Ryline Ave NE CITY: Albuquerque STATE: NM

ZIP: 87103 RECEIVED BY: [Signature]

INSTRUCTIONS: Indicate the number of actions to the left of the appropriate type of filing. Complete the receipt information. **Original** to payor; **pink** copy to Program Support/ASD; **yellow** copy remains in district office, and **goldenrod** copy to accompany application being filed. If you make an error, void original and all copies and submit to Program Support/ASD along with other valid receipts.

A. Ground Water Rights Filing Fees

1. Declaration of Water Right	\$ 1.00
2. Application to Appropriate or Supplement Domestic 72-12-1 Well	\$125.00
3. Application for Stock Well	\$ 5.00
4. Application to Repair or Deepen 72-12-1 Well	\$ 75.00
5. Application for Replacement 72-12-1 Well	\$ 75.00
6. Application to Change Purpose of Use 72-12-1 Well	\$ 75.00
7. Application to Appropriate Irrig., Mun., or Comm. Use	\$ 25.00
8. Application for Supplemental Non 72-12-1 Well	\$ 25.00
9. Application to Change Location of Non 72-12-1 Well	\$ 25.00
10. Application to Change Place or Purpose of Use Non 72-12-1 Well	\$ 25.00
11. Application to Change Location of Well and Place and/or Purpose of Use	\$ 50.00
12. Application for Extension of Time	\$ 25.00
13. Proof of Application to Beneficial Use	\$ 25.00
14. Application to Change Point of Diversion and Place and/or Purpose of Use from Surface Water to Ground Water	\$ 50.00
15. Application for Test, Expl. Observ. Well	\$ 5.00
16. Change of Ownership of Water Right	\$ 2.00
17. Application to Repair or Deepen Non 72-12-1 Well	\$ 5.00

B. Surface Water Rights Filing Fees

1. Declaration of Water Right	\$ 10.00
2. Amended Declaration	\$ 25.00
3. Declaration of Livestock Water Impoundment	\$ 10.00
4. Application for Livestock Water Impoundment	\$ 10.00
5. Application to Appropriate	\$ 25.00
6. Notice of Intent to Appropriate	\$ 25.00
7. Application to Change Point of Diversion	\$100.00
8. Application to Change Place and/or Purpose of Use	\$100.00
9. Application to Change Point of Diversion and Place and/or Purpose of Use	\$200.00
10. Application to Change Point of Diversion and Place and/or Purpose of Use from Ground Water to Surface Water	\$200.00
11. Application for Extension of Time	\$ 50.00
12. Supplemental Well to a Surface Right	\$100.00
13. Return Flow Credit	\$100.00
14. Proof of Completion of Works	\$ 25.00
15. Proof of Application of Water to Beneficial Use	\$ 25.00
16. Water Development Plan	\$100.00
17. Change of Ownership of Water Right	\$ 5.00

C. Miscellaneous Fees

1. Application for Well Driller's License	\$50.00
2. Application for Renewal of Well Driller's License	\$50.00
3. Application to Amend Well Driller's License	\$50.00

D. Reproduction of Documents

_____ @ 0.25¢/copy	\$ _____
_____ Map(s)	\$ _____

E. Certification

_____	\$ _____
-------	----------

E. Other

_____	\$ _____
-------	----------

G. Comments:

* Fed ex

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:37:49

WR File Number: C-POD1
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

NW 1/4 of NE 1/4 of SE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 21.7 Seconds N
Longitude: 103 Degrees 53 Minutes 42.6 Seconds W

Universal Transverse Mercator Zone: 13N


NAD 1983(92) (Meters)	N: 3,589,676	E: 603,860
NAD 1983(92) (Survey Feet)	N: 11,777,127	E: 1,981,162
NAD 1927 (Meters)	N: 3,589,473	E: 603,908
NAD 1927 (Survey Feet)	N: 11,776,464	E: 1,981,323

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,670	E: 206,202
NAD 1983(92) (Survey Feet)	N: 523,852	E: 676,513
NAD 1927 (Meters)	N: 159,652	E: 193,649
NAD 1927 (Survey Feet)	N: 523,791	E: 635,331

NEW MEXICO OFFICE OF STATE ENGINEER

Locator Tool Report



WR File Number: C-POD1

Scale: 1:19,134

Northing/Easting: UTM83(92) (Meter): N: 3,589,676

E: 603,860

Northing/Easting: SPCS83(92) (Feet): N: 523,852

E: 676,513

GW Basin: Carlsbad

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:39:09

WR File Number: C-POD2
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 22.1 Seconds N
Longitude: 103 Degrees 53 Minutes 43.0 Seconds W

Universal Transverse Mercator Zone: 13N

NAD 1983(92) (Meters)	N: 3,589,686	E: 603,850
NAD 1983(92) (Survey Feet)	N: 11,777,161	E: 1,981,130
NAD 1927 (Meters)	N: 3,589,484	E: 603,898
NAD 1927 (Survey Feet)	N: 11,776,498	E: 1,981,290

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,681	E: 206,192
NAD 1983(92) (Survey Feet)	N: 523,886	E: 676,481
NAD 1927 (Meters)	N: 159,662	E: 193,639
NAD 1927 (Survey Feet)	N: 523,825	E: 635,299

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:39:52

WR File Number: C-POD3
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 22.4 Seconds N
Longitude: 103 Degrees 53 Minutes 43.3 Seconds W

Universal Transverse Mercator Zone: 13N


NAD 1983(92) (Meters)	N: 3,589,696	E: 603,840
NAD 1983(92) (Survey Feet)	N: 11,777,195	E: 1,981,099
NAD 1927 (Meters)	N: 3,589,494	E: 603,889
NAD 1927 (Survey Feet)	N: 11,776,532	E: 1,981,260

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,691	E: 206,183
NAD 1983(92) (Survey Feet)	N: 523,920	E: 676,450
NAD 1927 (Meters)	N: 159,672	E: 193,630
NAD 1927 (Survey Feet)	N: 523,859	E: 635,269

NEW MEXICO OFFICE OF STATE ENGINEER

Locator Tool Report



WR File Number: C-POD3

Scale: 1:19,134

Northing/Easting: UTM83(92) (Meter): N: 3,589,696

E: 603,840

Northing/Easting: SPCS83(92) (Feet): N: 523,920

E: 676,450

GW Basin: Carlsbad

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:40:31

WR File Number: C-POD4
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 22.8 Seconds N
Longitude: 103 Degrees 53 Minutes 43.7 Seconds W

Universal Transverse Mercator Zone: 13N

NAD 1983(92) (Meters)	N: 3,589,706	E: 603,831
NAD 1983(92) (Survey Feet)	N: 11,777,229	E: 1,981,069
NAD 1927 (Meters)	N: 3,589,504	E: 603,880
NAD 1927 (Survey Feet)	N: 11,776,565	E: 1,981,229

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,701	E: 206,173
NAD 1983(92) (Survey Feet)	N: 523,954	E: 676,420
NAD 1927 (Meters)	N: 159,683	E: 193,621
NAD 1927 (Survey Feet)	N: 523,893	E: 635,238

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:41:35

WR File Number: C-POD5
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 23.1 Seconds N
Longitude: 103 Degrees 53 Minutes 44.0 Seconds W

Universal Transverse Mercator Zone: 13N


NAD 1983(92) (Meters)	N: 3,589,716	E: 603,822
NAD 1983(92) (Survey Feet)	N: 11,777,261	E: 1,981,040
NAD 1927 (Meters)	N: 3,589,514	E: 603,871
NAD 1927 (Survey Feet)	N: 11,776,598	E: 1,981,200

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,711	E: 206,164
NAD 1983(92) (Survey Feet)	N: 523,986	E: 676,391
NAD 1927 (Meters)	N: 159,693	E: 193,612
NAD 1927 (Survey Feet)	N: 523,925	E: 635,209

NEW MEXICO OFFICE OF STATE ENGINEER

Locator Tool Report



WR File Number: C-POD5

Scale: 1:19,134

Northing/Easting: UTM83(92) (Meter): N: 3,589,716

E: 603,822

Northing/Easting: SPCS83(92) (Feet): N: 523,986

E: 676,391

GW Basin: Carlsbad

Locator Tool Report

General Information:

Application ID: 29 Date: 08-04-2014 Time: 15:42:16

WR File Number: C-POD6
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 23.4 Seconds N
Longitude: 103 Degrees 53 Minutes 44.4 Seconds W

Universal Transverse Mercator Zone: 13N


NAD 1983(92) (Meters)	N: 3,589,726	E: 603,813
NAD 1983(92) (Survey Feet)	N: 11,777,293	E: 1,981,011
NAD 1927 (Meters)	N: 3,589,524	E: 603,862
NAD 1927 (Survey Feet)	N: 11,776,629	E: 1,981,171

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,721	E: 206,156
NAD 1983(92) (Survey Feet)	N: 524,018	E: 676,362
NAD 1927 (Meters)	N: 159,702	E: 193,603
NAD 1927 (Survey Feet)	N: 523,957	E: 635,180

NEW MEXICO OFFICE OF STATE ENGINEER

Locator Tool Report



WR File Number: C-POD6

Scale: 1:19,134

Northing/Easting: UTM83(92) (Meter): N: 3,589,726

E: 603,813

Northing/Easting: SPCS83(92) (Feet): N: 524,018

E: 676,362

GW Basin: Carlsbad

Locator Tool Report

General Information:

Application ID:29 Date: 08-04-2014 Time: 15:43:00

WR File Number: C-POD7
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 23.7 Seconds N
Longitude: 103 Degrees 53 Minutes 44.7 Seconds W

Universal Transverse Mercator Zone: 13N

NAD 1983(92) (Meters)	N: 3,589,736	E: 603,804
NAD 1983(92) (Survey Feet)	N: 11,777,325	E: 1,980,981
NAD 1927 (Meters)	N: 3,589,534	E: 603,853
NAD 1927 (Survey Feet)	N: 11,776,662	E: 1,981,142

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,731	E: 206,147
NAD 1983(92) (Survey Feet)	N: 524,050	E: 676,333
NAD 1927 (Meters)	N: 159,712	E: 193,594
NAD 1927 (Survey Feet)	N: 523,990	E: 635,151

Locator Tool Report

General Information:

Application ID:29 Date: 08-04-2014 Time: 15:43:36

WR File Number: C-POD8
Purpose: OTHER

Applicant First Name: VIRGILIO COCIANNI
Applicant Last Name: SCHLUMBERGER TECH CORP

GW Basin: CARLSBAD
County: EDDY

Critical Management Area Name(s): NONE
Special Condition Area Name(s): NONE
Land Grant Name: NON GRANT

PLSS Description (New Mexico Principal Meridian):

SW 1/4 of SE 1/4 of NE 1/4 of NE 1/4 of Section 32, Township 21S, Range 30E.

Coordinate System Details:

Geographic Coordinates:

Latitude: 32 Degrees 26 Minutes 24.0 Seconds N
Longitude: 103 Degrees 53 Minutes 45.0 Seconds W

Universal Transverse Mercator Zone: 13N


NAD 1983(92) (Meters)	N: 3,589,745	E: 603,796
NAD 1983(92) (Survey Feet)	N: 11,777,355	E: 1,980,953
NAD 1927 (Meters)	N: 3,589,543	E: 603,845
NAD 1927 (Survey Feet)	N: 11,776,692	E: 1,981,114

State Plane Coordinate System Zone: New Mexico East

NAD 1983(92) (Meters)	N: 159,740	E: 206,138
NAD 1983(92) (Survey Feet)	N: 524,080	E: 676,305
NAD 1927 (Meters)	N: 159,722	E: 193,586
NAD 1927 (Survey Feet)	N: 524,020	E: 635,123

NEW MEXICO OFFICE OF STATE ENGINEER

Locator Tool Report



WR File Number: C-POD8

Scale: 1:19,134

Northing/Easting: UTM83(92) (Meter): N: 3,589,745

E: 603,796

Northing/Easting: SPCS83(92) (Feet): N: 524,080

E: 676,305

GW Basin: Carlsbad



PROJECT NUMBER:

469935.14.04.02

BORING NUMBER:

EW-03

SHEET 1 OF 2

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.89, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with continuous core

WATER LEVEL : not measured

START : 8/22/14 10:07

END : 8/22/14 12:05

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
	0.0		Soil removed with hand auger during utility clearance	
5				Soil logged from continuous core
	5.0		SANDY SILT (ML) light reddish brown (5YR 6/3), dry, low plasticity, cohesive, mottled white-caliche	Headspace=0.0 ppm
			SILT (ML) white / pinkish gray (5YR 8/1), dry, low plasticity, cohesive, mottled with light red nodules and mottled white-caliche, nodules get fewer grading down core	Headspace=0.0 ppm
10			No recovery	Headspace=0.0 ppm
	3.0		SILT (ML) white / pinkish gray (5YR 8/1), dry, low plasticity, cohesive, mottled with light red nodules (as above) with less grading deeper	Headspace=0.0 ppm
15			SILTY SAND (SM) reddish brown / moderate brown (5YR 4/4), dry, very loose, mostly very fine grained - up to 10% medium and coarse grained	Headspace=0.0 ppm
	4.0		SANDY LEAN CLAY (CL) reddish brown (2.5YR 5/4), dry, noncohesive, non plastic, mottled grey 1" layer of coarse gravel at top of interval	Headspace=0.0 ppm
			No recovery	
			LEAN CLAY (CL) white / pinkish gray (5YR 8/1), partially cemented caliche, laminated, trace black organic stringers	Headspace=0.0 ppm
20			SANDY SILT (ML) reddish brown (2.5YR 4/4), dry, low plasticity, cohesive, very fine sand, few (5%) fine gravel, laminated	
	3.0		POORLY GRADED SAND (SP) light reddish brown (2.5YR 7/3), moist, loose to dense at shoe, 5% fine gravel	
			No recovery	
			WELL GRADED GRAVEL WITH CLAY (GW-GC) reddish brown (2.5YR 5/4), moist, low plasticity, coarse gravel to 4 cm diameter, grading to gravelly clay (CL)	Headspace=0.0 ppm
25			SILT (ML) red (2.5YR 5/6), low plasticity, cohesive, laminated, 2% medium gravel	Headspace=0.0 ppm
	5.0		LEAN CLAY (CL) red (2.5YR 5/6), low plasticity, cohesive, dense, 2% medium gravel	
			POORLY GRADED SAND (SP) reddish brown (2.5YR 5/4), wet, partially cemented, 5-7% fine gravel	
			WELL GRADED GRAVEL WITH CLAY AND SAND (GW-GC) light reddish brown (2.5YR 7/3) to reddish brown (2.5YR 4/4) interbedded with silt, wet, low plasticity, cohesive, silt is stiff and has 5% sand and gravel	
30			SILT (ML) red (2.5YR 4/6), wet, low plasticity, cohesive, medium stiff	Headspace=0.0 ppm
	5.0		SILT (ML) red (2.5YR 4/6), moist, low plasticity, cohesive, very soft, 2% medium gravel	
			WELL GRADED GRAVEL WITH CLAY AND SAND (GW-GC) pale red (2.5YR 7/2), wet, very loose, partially cemented at top	Headspace=0.0 ppm
			SILT (ML) red (2.5YR 4/6), moist, low plasticity, cohesive, very soft, 2% medium gravel	
35				

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB: COMMERCIAL_PROJECT.GPJ: CH2M GEOTECH_12_CG.GDT: 2/11/15



PROJECT NUMBER:

469935.14.04.02

BORING NUMBER:

EW-03

SHEET 2 OF 2

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.89, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with continuous core

WATER LEVEL : not measured

START : 8/22/14 10:07

END : 8/22/14 12:05

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION	COMMENTS
			SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DRILLING DETAILS
	5.0		SILT (ML) reddish brown (2.5YR 4/4), wet, low plasticity, cohesive, dense, 5-10% clay SILT (ML) reddish brown (2.5YR 5/3), wet, low plasticity, cohesive, soft, 1" medium gravel layers (white) at 36' and 37.5'	Headspace=0.0 ppm
40			SILTY SAND (SM) reddish brown (2.5YR 4/4), wet, medium dense, 2% medium gravel, mottled grey, very fine sand	Headspace=0.0 ppm
	5.0		CLAYEY SAND (SC) light red (2.5YR 6/6), wet, loose, blocky, very fine sand LEAN CLAY (CL) white (2.5YR 8/1), wet, medium plastic, cohesive, very soft CLAYEY SAND (SC) reddish brown (2.5YR 4/4), wet, loose, predominantly very fine sand with 5% fine gravel	
45			LEAN CLAY WITH SAND (CL) variagated reddish brown (2.5YR 4/4), white (2.5YR 8/1), and grey (5YR 6/1) wet, low plasticity, cohesive, soft	
	4.5		GRAVELLY SILT WITH SAND (ML) pinkish gray / grayish orange pink (5YR 7/2), wet, partially cemented No recovery CALICHE pinkish white (5YR 8/2), wet, cemented to partially cemented	
50			LEAN CLAY WITH SAND (CL) yellowish red / light brown (5YR 5/6), wet, low plasticity, cohesive, stiff, 10% silt, laminated	
	5.0		POORLY GRADED SAND (SP) light reddish brown (2.5YR 6/4), wet, loose, predominantly fine grained POORLY GRADED SAND (SP) light reddish brown (2.5YR 6/4), wet, loose, mostly fine grained POORLY GRADED SAND WITH SILT (SP-SM) reddish yellow (5YR 6/6), wet, loose, thinly bedded, fine grained POORLY GRADED SAND (SP) light greenish gray (10Y 8/1), wet, partially cemented, fine to medium grained	
55			POORLY GRADED SAND WITH CLAY (SP-SC) reddish yellow (5YR 6/6), wet, loose, thinly bedded, fine grained LEAN CLAY (CL) white / yellowish gray (5Y 8/1), wet, non plastic, noncohesive, 5% fine sand	
	5.0		POORLY GRADED SAND (SP) white / yellowish gray (5Y 8/1), wet, very loose, predominantly fine and medium sand, laminated, 5-7% lean clay LEAN CLAY (CL) reddish brown (5YR 5/4), wet, low plasticity, cohesive, medium dense, gravel to 4 cm diameter speckled throughout	
60			Boring terminated at 60.0 ft bgs.	
65				
70				

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB; COMMERCIAL_PROJECT.GPJ; CH2M GEOTECH_12_CG.GDT; 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-1

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/21/14 09:36

END : 8/21/14 09:52

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION	COMMENTS
			SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DRILLING DETAILS
5			SILT (ML) pale red (2.5YR 7/2), dry, non plastic, noncohesive, like flour	Soil logged from auger cuttings Headspace=4.7 ppm
10			SILT (ML) pale red (2.5YR 7/2), dry, non plastic, noncohesive, like flour, with white clay/caliche chunks	 Headspace=0.2 ppm
15			LEAN CLAY (CL) light reddish brown (2.5YR 6/3), dry, low plasticity, cohesive, trace (5-7%) medium to coarse sand, white clay/caliche chunks (15%)	 Headspace=0.0 ppm
20			LEAN CLAY (CL) reddish brown (2.5YR 4/4), moist, low plasticity, cohesive, few (10-12%) fine to coarse sand	 Headspace=0.0 ppm
25			SILT (ML) reddish brown (2.5YR 5/4), wet, low plasticity, cohesive, few (10-12%) fine to coarse sand	 Headspace=0.0 ppm
30			SILT (ML) reddish brown (2.5YR 5/4), wet, low plasticity, cohesive, few (10-12%) fine to coarse sand, trace rust colored mottles	 Headspace=0.0 ppm
35			Boring terminated at 31.5 ft bgs.	

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB; COMMERCIAL_PROJECT.GPJ; CH2M GEOTECH_12_CG.GDT; 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-2

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/21/14 08:00

END : 8/21/14 08:19

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
5			Soil removed with hand auger during utility clearance	Soil logged from auger cuttings
			SILT (ML) light reddish brown (2.5YR 6/4), dry, non-plastic, noncohesive	Headspace=0.0 ppm
10			SILT (ML) reddish brown (2.5YR 5/4), dry, medium plasticity, cohesive, trace (5-7%) white clay nodules and caliche chunks, little medium to coarse sand	
15			Not Logged	
20			LEAN CLAY (CL) reddish brown (2.5YR 4/4), moist, low plasticity, noncohesive, little (8-12%) fine to coarse angular sand	Headspace=0.0 ppm
25			SILT (ML) reddish brown (2.5YR 4/3), wet, non plastic, noncohesive, trace (5-7%) fine to coarse sand	
30				
35			Boring terminated at 31.5 ft bgs.	

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB: COMMERCIAL_PROJECT.GPJ: CH2M GEOTECH_12_CG.GDT: 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-3

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/20/14 16:13

END : 8/20/14 04:43

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION	COMMENTS
			SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DRILLING DETAILS
5			SILT (ML) pale red (2.5YR 7/2), dry, non plastic, noncohesive, almost like flour	Soil logged from auger cuttings Headspace=0.0 ppm
10			SILT (ML) pale red (2.5YR 7/2), dry, non plastic, noncohesive, almost like flour, trace fine gravel, 5-7% clay	Headspace=0.0 ppm
15			LEAN CLAY (CL) reddish brown (2.5YR 5/3), dry, low plasticity, cohesive, few fine to medium gravel, trace fine to coarse sand	Headspace=0.0 ppm
20			Not logged	
25			SILT (ML) reddish brown (2.5YR 5/3), wet, low plasticity, cohesive, trace fine to medium gravel, few fine to coarse sand	
30			SILT (ML) reddish brown (2.5YR 5/3), wet, low plasticity, cohesive, trace fine to medium gravel, few fine to coarse sand	
35			Boring terminated at 32.0 ft bgs.	

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB; COMMERCIAL_PROJECT.GPJ; CH2M GEOTECH_12_CG.GDT; 2/11/15



PROJECT NUMBER:

469935.14.04.02

BORING NUMBER:

IJ-4

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.250-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/20/14 14:52

END : 8/20/14 15:10

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
5			SILT (ML) light reddish brown (2.5YR 7/3), dry, non plastic, noncohesive, trace medium gravel	Soil logged from auger cuttings Headspace=0.0 ppm
10			SILT (ML) light reddish brown (2.5YR 7/3), dry, non plastic, noncohesive, trace medium gravel, with white caliche-like nodules/chunks up to 2.54 cm diameter though some are very soft and friable	Headspace=0.1 ppm
15			LEAN CLAY (CL) light reddish brown (2.5YR 7/3), low plasticity, cohesive, abundant white nodules/chunks as above	Headspace=0.1 ppm
20			LEAN CLAY (CL) reddish brown (2.5YR 5/3), moist, low plasticity, cohesive, 5% fine to coarse sand	Headspace=0.0 ppm
25			SILT (ML) reddish brown (2.5YR 5/3), moist, low plasticity, cohesive, 5-7% fine to coarse sand	Headspace=0.0 ppm
30			LEAN CLAY (CL) reddish brown (2.5YR 5/3), wet, low plasticity, cohesive, 5-7% fine to coarse sand, 10% silt	Headspace=0.0 ppm
35			Boring terminated at 31.0 ft bgs.	

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB; COMMERCIAL_PROJECT.GPJ; CH2M GEOTECH_12_CG.GDT; 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-5

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/19/14 11:51

END : 8/19/2014

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
5			SILT (ML) light reddish brown (2.5YR 6/3), dry, non plastic, noncohesive, few medium sands	Soil logged from auger cuttings Headspace=0.1 ppm
			SILT (ML) reddish brown (2.5YR 5/4), dry, non plastic, noncohesive, few medium sands, 5-7% clay	Headspace=0.2 ppm
10			LEAN CLAY (CL) light reddish brown (2.5YR 6/3), moist, non plastic, noncohesive, trace fine sands	Headspace=0.1 ppm
15			LEAN CLAY (CL) reddish brown (2.5YR 4/4), wet, non plastic, cohesive, few medium sand	Headspace=0.2 ppm
20			SILT (ML) reddish brown (2.5YR 5/3), wet, low plasticity, cohesive, 10% clay	Headspace=0.1 ppm
25			SILT (ML) reddish brown (2.5YR 5/4), wet, low plasticity, cohesive, few well graded sands	Headspace=0.6 ppm
30			Boring terminated at 31.5 ft bgs.	
35				

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB: COMMERCIAL_PROJECT.GPJ: CH2M GEOTECH_12_CG.GDT: 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-6

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/19/14 10:44

END : 8/19/14 10:58

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION	COMMENTS
			SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DRILLING DETAILS
5			SANDY SILT (ML) reddish brown (2.5YR 4/3), dry, non plastic, noncohesive, roots	Soil logged from auger cuttings Headspace=0.1 ppm
10			SILT (ML) pale red (2.5YR 6/2), dry, non plastic, noncohesive, clay nodules up to 2.5 cm - white with mottled grey and reddish brown when broken	Headspace=0.1 ppm
15			LEAN CLAY (CL) pale red (2.5YR 6/2), dry, low plasticity, noncohesive, white clay nodules to 1 cm, few coarse sand, trace fine gravel	Headspace=0.2 ppm
20			LEAN CLAY (CL) reddish brown (2.5YR 4/4), moist, low plasticity, noncohesive, trace fine to medium sand	Headspace=0.2 ppm
25			SILT (ML) reddish brown (2.5YR 4/3), wet, low plasticity, cohesive, few fine gravel	Headspace=0.3 ppm
30			SILT (ML) reddish brown (2.5YR 5/4), wet, low plasticity, cohesive, few fine gravel	Headspace=0.3 ppm
35			Boring terminated at 31.0 ft bgs.	

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB; COMMERCIAL_PROJECT.GPJ; CH2M GEOTECH_12_CG.GDT; 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-7

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/19/14 10:00

END : 8/19/14 10:12

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
5			No recovery, soil removed with hand auger during utility clearance	Soil logged from auger cuttings
			SILT (ML) light reddish brown (2.5YR 7/3), dry, non plastic, noncohesive, 10-15% fine and medium sands, 5% fine gravel	Headspace=0.2 ppm
10			LEAN CLAY (CL) reddish brown (2.5YR 5/3), dry, low plasticity, noncohesive, 5-10% silt, 5% medium sands	Headspace=0.2 ppm
15			LEAN CLAY WITH SAND (CL) reddish brown (2.5YR 5/4), moist, low plasticity, cohesive, fine to coarse sands, few fine angular gravel with 2.5YR 5/6, dark red nodules	Headspace=0.1 ppm
20			SILT (ML) reddish brown (2.5YR 5/4), wet, medium plasticity, cohesive, few coarse sand	Headspace=0.2 ppm
25			SILT (ML) reddish brown (2.5YR 5/4), wet, medium plasticity, cohesive, few coarse sand, few fine gravel	Headspace=0.1 ppm
30			Boring terminated at 31.0 ft bgs.	
35				

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB: COMMERCIAL_PROJECT.GPJ: CH2M GEOTECH_12_CG.GDT: 2/11/15



PROJECT NUMBER:
469935.14.04.02

BORING NUMBER:
IJ-8

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)




DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : not measured

START : 8/19/14 08:50

END : 8/19/14 09:06

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
5			No recovery, soil removed with hand auger during utility clearance	Soil logged from auger cuttings
10			Not logged	
15			LEAN CLAY (CL) light reddish brown (2.5YR 6/3), dry, low plasticity, noncohesive, 10-15% clay, little medium gravel	
20			LEAN CLAY (CL) reddish brown (2.5YR 5/3), moist, low plasticity, noncohesive, few medium sands	Headspace=0.1 ppm
25			SILT (ML) weak red (2.5YR 4/2), wet, low plasticity, noncohesive, few medium sands, 5-10% fine sand	Headspace=0.0 ppm
30			SILT (ML) reddish brown (2.5YR 4/4), wet, medium plasticity, cohesive, 5-7% fine sand, trace coarse sand	Headspace=0.0 ppm
35			Boring terminated at 30.5 ft bgs.	

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB; COMMERCIAL_PROJECT.GPJ; CH2M GEOTECH_12_CG.GDT; 2/11/15



PROJECT NUMBER:

469935.14.04.02

BORING NUMBER:

MW-34

SHEET 1 OF 1

Soil Boring Log

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.89, (estim)

DRILLING METHOD AND EQUIPMENT : 4.25 ID HSA With Continuous Core

WATER LEVEL : not measured

START : 8/21/14 13:30

END : 8/21/14 14:50

LOGGER : Aleeca Forsberg

DEPTH BELOW GROUND SURFACE (ft)	RECOVERY (ft)	GRAPHIC LOG	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DRILLING DETAILS
	0.0		No recovery, soil removed with hand auger during utility clearance	Soil logged from continuous core
5				
	5.0		SILT (ML) light reddish gray (2.5YR 7/1), dry, non plastic, noncohesive, caliche-like throughout	
			SILT (ML) light reddish gray (2.5YR 7/1), as above, less caliche-like	
			LEAN CLAY (CL) white (2.5YR 8/1), dry, non plastic, noncohesive, hard	
10			SILT (ML) light reddish gray (2.5YR 7/1), dry, non plastic, noncohesive, caliche-like throughout	
	3.0		No recovery	
			SILT (ML) red (2.5YR 5/6), dry, non plastic, noncohesive, white caliche-like throughout, laminated at top 2 ft, chunky at bottom foot	
15			No recovery	Headspace=0.0 ppm
	4.5		POORLY GRADED SAND (SP) yellowish red / light brown (5YR 5/6), moist, laminated, very loose, laminated mottled-oxidized, 5-10% silt, very fine sand	
			WELL GRADED GRAVEL WITH CLAY (GW-GC) light reddish brown / light brown (5YR 6/4), moist, subrounded gravel	
20			SILT (ML) pinkish gray / grayish orange pink (5YR 7/2), moist, low plasticity, cohesive, 5% clay	Headspace=0.0 ppm
	2.5		No recovery	
			SILT (ML) reddish brown (2.5YR 4/4), wet, low plasticity, cohesive, soft, 10% medium gravel	
25			CALICHE pale red (2.5YR 7/2), dry, hard	Headspace=0.0 ppm
			LEAN CLAY (CL) reddish brown (2.5YR 4/4), moist, low plasticity, cohesive, stiff	
	2.5		POORLY GRADED SAND (SP) pink (2.5YR 8/4), dry, non plastic, very loose, very fine	
			No recovery	
			SILT (ML) light reddish brown / light brown (5YR 6/4), wet, low plasticity, cohesive soft	
30			SILTY SAND (SM) light reddish brown (5YR 6/3), wet, very loose, predominantly fine sand	
			SILT (ML) light reddish brown (5YR 6/4) to reddish brown (5YR 5/4), wet, low plasticity, cohesive, 10-12% fine to medium sand	
			No recovery	
35				
			Boring terminated at 36.5 ft bgs.	
40				

NEW SOIL BORING LOG: CH2M GEOTECH_12_COMMERCIAL_GLB: COMMERCIAL_PROJECT.GPJ: CH2M GEOTECH_12_CG.GDT: 3/2/15



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
EW-03

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.89, (estim)

DRILLING METHOD AND EQUIPMENT : 6.25-in ID HSA with center plug

WATER LEVEL : 18.75 ft bgs (measured before development)

START : 8/22/14 14:38

END : 8/23/2014

LOGGER : A. Forsberg

Well pad is 5 feet diameter, concrete vault

NOTES:

ALL DEPTHS ARE REPORTED AS
DEPTH IN FEET BELOW GROUND
SURFACE UNLESS OTHERWISE
NOTED.

COMMENTS:

Borehole overdrilled with CME-85
6.25 ID HSA with center plug

WELL CONSTRUCTION & SCREEN DETAILS


BOREHOLE DIAMETER: 10.5 inches

FILTER PACK TYPE: FILTER PACK, 8-16 silica sand

WELL CASING: BLANK, 4" SCH40 PVC

SCREEN LENGTH: 40 feet

SCREEN DESCRIPTION: 4" SCH40 PVC 0.040
wire-wrapped Slot



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-1

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 17.20 ft bgs (measured before development)

START : 8/21/14 09:56

END : 8/23/14 08:10

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-2

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 17.42 ft bgs (measured on 8/21/14)

START : 8/21/14 08:21

END : 8/21/2014

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-3

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 16.68 ft bgs (measured on 8/21/14)

START : 8/20/14 16:50

END : 8/21/14 10:25

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-4

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 16.74 ft bgs (measured before well development)

START : 8/20/14 15:21

END : 8/20/14 15:40

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-5

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 15.00 ft bgs (measured after well development)

START : 8/20/14 07:53

END : 8/20/14 09:03

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-6

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 16.60 ft bgs (measured before well development)

START : 8/20/14 09:24

END : 8/20/2014

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-7

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 15.86 ft bgs (measured on 8/21/14)

START : 8/20/14 11:20

END : 8/20/14 14:06

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
IJ-8

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.90, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25-in ID HSA with center plug

WATER LEVEL : 15.14 ft bgs (measured on 8/21/14)

START : 8/20/14 12:43

END : 8/20/2014

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



PROJECT NUMBER:
469935.14.04.02

WELL NUMBER:
MW-34

Well Completion Diagram

PROJECT : Former Dowell Schlumberger Facility

LOCATION : Artesia, New Mexico

ELEVATION : not measured

TOC : not measured

DRILLING CONTRACTOR AND DRILL RIG : National Exploration Wells and Pumps, CME 85

COORDINATES : N 32.44, E -103.89, (estim)


DRILLING METHOD AND EQUIPMENT : 4.25 ID HSA With Continuous Core

WATER LEVEL : 18.10 ft bgs

START : 8/21/14 13:30

END : 8/22/2014

LOGGER : A. Forsberg



WELL DIAGRAM IS NOT TO SCALE



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-1 MW-34				OSE FILE NUMBER(S) C-3774			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY Sugar Land		STATE TX	ZIP 77478
	WELL LOCATION (FROM GPS)	DEGREES LATITUDE 32.		MINUTES 439	SECONDS 42826	N	* ACCURACY REQUIRED: ONE TENTH OF A SECOND	
		LONGITUDE 103.		894	5949	W	* DATUM REQUIRED: WGS 84	
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-21-14		DRILLING ENDED 8-21-14		DEPTH OF COMPLETED WELL (FT) 32	BORE HOLE DEPTH (FT) 36.5	DEPTH WATER FIRST ENCOUNTERED (FT) NA	
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)						STATIC WATER LEVEL IN COMPLETED WELL (FT) NA	
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0	17	8 1/4	PVC	Flush	4	40	
	17	27	8 1/4	PVC	Flush	4	40	.040
	27	32	8 1/4	PVC	Flush	4	40	
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 1 OF 2

4. HYDROGEOLOGIC LOG OF WELL	DEPTH (feet bgl)		THICKNESS (feet)	COLOR AND TYPE OF MATERIAL ENCOUNTERED - INCLUDE WATER-BEARING CAVITIES OR FRACTURE ZONES (attach supplemental sheets to fully describe all units)	WATER BEARING? (YES / NO)	ESTIMATED YIELD FOR WATER- BEARING ZONES (gpm)
	FROM	TO				
				See Attached	☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
	METHOD USED TO ESTIMATE YIELD OF WATER-BEARING STRATA: ☐ PUMP				TOTAL ESTIMATED	
	☐ AIR LIFT ☐ BAILER ☐ OTHER - SPECIFY:				WELL YIELD (gpm):	

5. TEST; RIG SUPERVISION	WELL TEST	TEST RESULTS - ATTACH A COPY OF DATA COLLECTED DURING WELL TESTING, INCLUDING DISCHARGE METHOD, START TIME, END TIME, AND A TABLE SHOWING DISCHARGE AND DRAWDOWN OVER THE TESTING PERIOD.
	MISCELLANEOUS INFORMATION:	
	PRINT NAME(S) OF DRILL RIG SUPERVISOR(S) THAT PROVIDED ONSITE SUPERVISION OF WELL CONSTRUCTION OTHER THAN LICENSEE: Mark Green	

6. SIGNATURE	THE UNDERSIGNED HEREBY CERTIFIES THAT, TO THE BEST OF HIS OR HER KNOWLEDGE AND BELIEF, THE FOREGOING IS A TRUE AND CORRECT RECORD OF THE ABOVE DESCRIBED HOLE AND THAT HE OR SHE WILL FILE THIS WELL RECORD WITH THE STATE ENGINEER AND THE PERMIT HOLDER WITHIN 20 DAYS AFTER COMPLETION OF WELL DRILLING:	
	 SIGNATURE OF DRILLER / PRINT SIGNED NAME	7-8-14 DATE

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER	
LOCATION			PAGE 2 OF 2

PROJECT NUMBER
469935.04.02BORING NUMBER
BW-34

SHEET 1 OF 1

SOIL BORING LOG

PROJECT Dowell-Schulmberger Arksia LOCATION Artesia, NM
 ELEVATION NM DRILLING CONTRACTOR NEWP / I Sapier
 DRILLING METHOD AND EQUIPMENT CME 85, 4.25 in HSA w/ cont core
 WATER LEVELS 18.1 ft bgs @ install START 8/21/13 FINISH 8/21/13 LOGGER A. J. Saper

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
5	1'-12"		5'	NA	NOT LOGGED hand augered for utility clearance	
10	12'-15"		0'		NO RECOVERY	
15	15'-18"		3'		SILT (ML) 2.5 YR 7/10 reddish brown, clay, non plastic, non cohesive, calcite-like throughout SILT (ML) 2.5 YR 7/10 reddish brown, clay, non plastic, non cohesive, calcite-like throughout SILT (ML) 2.5 YR 7/10 reddish brown, clay, non plastic, non cohesive, calcite-like throughout SILT (ML) 2.5 YR 7/10 reddish brown, clay, non plastic, non cohesive, calcite-like throughout	PI17=0.0 ppm
20	18'-21"		4.5'		NO RECOVERY	
25	21'-24"		2.5'	NA	NO RECOVERY	
30	24'-27"		2.5'	NA	NO RECOVERY	
35	27'-30"		2.5'	NA	NO RECOVERY	
40	30'-33"		2.5'	NA	NO RECOVERY	
45	33'-36"		2.5'	NA	NO RECOVERY	
50	36'-39"		2.5'	NA	NO RECOVERY	
55	39'-42"		2.5'	NA	NO RECOVERY	
60	42'-45"		2.5'	NA	NO RECOVERY	
65	45'-48"		2.5'	NA	NO RECOVERY	
70	48'-51"		2.5'	NA	NO RECOVERY	
75	51'-54"		2.5'	NA	NO RECOVERY	
80	54'-57"		2.5'	NA	NO RECOVERY	
85	57'-60"		2.5'	NA	NO RECOVERY	
90	60'-63"		2.5'	NA	NO RECOVERY	
95	63'-66"		2.5'	NA	NO RECOVERY	
100	66'-69"		2.5'	NA	NO RECOVERY	
105	69'-72"		2.5'	NA	NO RECOVERY	
110	72'-75"		2.5'	NA	NO RECOVERY	
115	75'-78"		2.5'	NA	NO RECOVERY	
120	78'-81"		2.5'	NA	NO RECOVERY	
125	81'-84"		2.5'	NA	NO RECOVERY	
130	84'-87"		2.5'	NA	NO RECOVERY	
135	87'-90"		2.5'	NA	NO RECOVERY	
140	90'-93"		2.5'	NA	NO RECOVERY	
145	93'-96"		2.5'	NA	NO RECOVERY	
150	96'-99"		2.5'	NA	NO RECOVERY	
155	99'-102"		2.5'	NA	NO RECOVERY	
160	102'-105"		2.5'	NA	NO RECOVERY	
165	105'-108"		2.5'	NA	NO RECOVERY	
170	108'-111"		2.5'	NA	NO RECOVERY	
175	111'-114"		2.5'	NA	NO RECOVERY	
180	114'-117"		2.5'	NA	NO RECOVERY	
185	117'-120"		2.5'	NA	NO RECOVERY	
190	120'-123"		2.5'	NA	NO RECOVERY	
195	123'-126"		2.5'	NA	NO RECOVERY	
200	126'-129"		2.5'	NA	NO RECOVERY	
205	129'-132"		2.5'	NA	NO RECOVERY	
210	132'-135"		2.5'	NA	NO RECOVERY	
215	135'-138"		2.5'	NA	NO RECOVERY	
220	138'-141"		2.5'	NA	NO RECOVERY	
225	141'-144"		2.5'	NA	NO RECOVERY	
230	144'-147"		2.5'	NA	NO RECOVERY	
235	147'-150"		2.5'	NA	NO RECOVERY	
240	150'-153"		2.5'	NA	NO RECOVERY	
245	153'-156"		2.5'	NA	NO RECOVERY	
250	156'-159"		2.5'	NA	NO RECOVERY	
255	159'-162"		2.5'	NA	NO RECOVERY	
260	162'-165"		2.5'	NA	NO RECOVERY	
265	165'-168"		2.5'	NA	NO RECOVERY	
270	168'-171"		2.5'	NA	NO RECOVERY	
275	171'-174"		2.5'	NA	NO RECOVERY	
280	174'-177"		2.5'	NA	NO RECOVERY	
285	177'-180"		2.5'	NA	NO RECOVERY	
290	180'-183"		2.5'	NA	NO RECOVERY	
295	183'-186"		2.5'	NA	NO RECOVERY	
300	186'-189"		2.5'	NA	NO RECOVERY	
305	189'-192"		2.5'	NA	NO RECOVERY	
310	192'-195"		2.5'	NA	NO RECOVERY	
315	195'-198"		2.5'	NA	NO RECOVERY	
320	198'-201"		2.5'	NA	NO RECOVERY	
325	201'-204"		2.5'	NA	NO RECOVERY	
330	204'-207"		2.5'	NA	NO RECOVERY	
335	207'-210"		2.5'	NA	NO RECOVERY	
340	210'-213"		2.5'	NA	NO RECOVERY	
345	213'-216"		2.5'	NA	NO RECOVERY	
350	216'-219"		2.5'	NA	NO RECOVERY	
355	219'-222"		2.5'	NA	NO RECOVERY	
360	222'-225"		2.5'	NA	NO RECOVERY	
365	225'-228"		2.5'	NA	NO RECOVERY	
370	228'-231"		2.5'	NA	NO RECOVERY	
375	231'-234"		2.5'	NA	NO RECOVERY	
380	234'-237"		2.5'	NA	NO RECOVERY	
385	237'-240"		2.5'	NA	NO RECOVERY	
390	240'-243"		2.5'	NA	NO RECOVERY	
395	243'-246"		2.5'	NA	NO RECOVERY	
400	246'-249"		2.5'	NA	NO RECOVERY	
405	249'-252"		2.5'	NA	NO RECOVERY	
410	252'-255"		2.5'	NA	NO RECOVERY	
415	255'-258"		2.5'	NA	NO RECOVERY	
420	258'-261"		2.5'	NA	NO RECOVERY	
425	261'-264"		2.5'	NA	NO RECOVERY	
430	264'-267"		2.5'	NA	NO RECOVERY	
435	267'-270"		2.5'	NA	NO RECOVERY	
440	270'-273"		2.5'	NA	NO RECOVERY	
445	273'-276"		2.5'	NA	NO RECOVERY	
450	276'-279"		2.5'	NA	NO RECOVERY	
455	279'-282"		2.5'	NA	NO RECOVERY	
460	282'-285"		2.5'	NA	NO RECOVERY	
465	285'-288"		2.5'	NA	NO RECOVERY	
470	288'-291"		2.5'	NA	NO RECOVERY	
475	291'-294"		2.5'	NA	NO RECOVERY	
480	294'-297"		2.5'	NA	NO RECOVERY	
485	297'-300"		2.5'	NA	NO RECOVERY	
490	300'-303"		2.5'	NA	NO RECOVERY	
495	303'-306"		2.5'	NA	NO RECOVERY	
500	306'-309"		2.5'	NA	NO RECOVERY	
505	309'-312"		2.5'	NA	NO RECOVERY	
510	312'-315"		2.5'	NA	NO RECOVERY	
515	315'-318"		2.5'	NA	NO RECOVERY	
520	318'-321"		2.5'	NA	NO RECOVERY	
525	321'-324"		2.5'	NA	NO RECOVERY	
530	324'-327"		2.5'	NA	NO RECOVERY	
535	327'-330"		2.5'	NA	NO RECOVERY	
540	330'-333"		2.5'	NA	NO RECOVERY	
545	333'-336"		2.5'	NA	NO RECOVERY	
550	336'-339"		2.5'	NA	NO RECOVERY	
555	339'-342"		2.5'	NA	NO RECOVERY	
560	342'-345"		2.5'	NA	NO RECOVERY	
565	345'-348"		2.5'	NA	NO RECOVERY	
570	348'-351"		2.5'	NA	NO RECOVERY	
575	351'-354"		2.5'	NA	NO RECOVERY	
580	354'-357"		2.5'	NA	NO RECOVERY	
585	357'-360"		2.5'	NA	NO RECOVERY	
590	360'-363"		2.5'	NA	NO RECOVERY	
595	363'-366"		2.5'	NA	NO RECOVERY	
600	366'-369"		2.5'	NA	NO RECOVERY	
605	369'-372"		2.5'	NA	NO RECOVERY	
610	372'-375"		2.5'	NA	NO RECOVERY	
615	375'-378"		2.5'	NA	NO RECOVERY	
620	378'-381"		2.5'	NA	NO RECOVERY	
625	381'-384"		2.5'	NA	NO RECOVERY	
630	384'-387"		2.5'	NA	NO RECOVERY	
635	387'-390"		2.5'	NA	NO RECOVERY	
640	390'-393"		2.5'	NA	NO RECOVERY	
645	393'-396"		2.5'	NA	NO RECOVERY	
650	396'-399"		2.5'	NA	NO RECOVERY	
655	399'-402"		2.5'	NA	NO RECOVERY	
660	402'-405"		2.5'	NA	NO RECOVERY	
665	405'-408"		2.5'	NA	NO RECOVERY	
670	408'-411"		2.5'	NA	NO RECOVERY	
675	411'-414"		2.5'	NA	NO RECOVERY	
680	414'-417"		2.5'	NA	NO RECOVERY	
685	417'-420"		2.5'	NA	NO RECOVERY	
690	420'-423"		2.5'	NA	NO RECOVERY	
695	423'-426"		2.5'	NA	NO RECOVERY	
700	426'-429"		2.5'	NA	NO RECOVERY	
705	429'-432"		2.5'	NA	NO RECOVERY	
710	432'-435"		2.5'	NA	NO RECOVERY	
715	435'-438"		2.5'	NA	NO RECOVERY	
720	438'-441"		2.5'	NA	NO RECOVERY	
725	441'-444"		2.5'	NA	NO RECOVERY	
730	444'-447"		2.5'	NA	NO RECOVERY	
735	447'-450"		2.5'	NA	NO RECOVERY	
740	450'-453"		2.5'	NA	NO RECOVERY	
745	453'-456"		2.5'	NA	NO RECOVERY	
750	456'-459"		2.5'	NA	NO RECOVERY	
755	459'-462"		2.5'	NA	NO RECOVERY	
760	462'-465"		2.5'	NA	NO RECOVERY	
765	465'-468"		2.5'	NA	NO RECOVERY	
770	468'-471"		2.5'	NA	NO RECOVERY	
775	471'-474"		2.5'	NA	NO RECOVERY	
780	474'-477"		2.5'	NA	NO RECOVERY	
785	477'-480"		2.5'	NA	NO RECOVERY	
790	480'-483"		2.5'	NA	NO RECOVERY	
795	483'-486"		2.5'	NA	NO RECOVERY	
800	486'-489"		2.5'	NA	NO RECOVERY	
805	489'-492"		2.5'	NA	NO RECOVERY	
810	492'-495"		2.5'	NA	NO RECOVERY	
815	495'-498"		2.5'	NA	NO RECOVERY	
820	498'-501"		2.5'	NA	NO RECOVERY	
825	501'-504"		2.5'	NA	NO RECOVERY	
830	504'-507"		2.5'	NA	NO RECOVERY	
835	507'-510"		2.5'	NA	NO RECOVERY	
840	510'-513"		2.5'	NA	NO RECOVERY	
845	513'-516"		2.5'	NA	NO RECOVERY	
850	516'-519"		2.5'	NA	NO RECOVERY	
855	519'-522"		2.5'	NA	NO RECOVERY	
860	522'-525"		2.5'	NA	NO RECOVERY	
865	525'-528"		2.5'	NA	NO RECOVERY	
870	528'-531"		2.5'	NA	NO RECOVERY	
875	531'-534"		2.5'	NA	NO RECOVERY	
880	534'-537"		2.5'	NA	NO RECOVERY	
885	537'-540"		2.5'	NA	NO RECOVERY	
890	540'-543"		2.5'	NA	NO RECOVERY	
895	543'-546"		2.5'	NA	NO RECOVERY	
900	546'-549"		2.5'	NA	NO RECOVERY	
905	549'-552"		2.5'	NA	NO RECOVERY	
910	552'-555"		2.5'	NA	NO RECOVERY	
915	555'-558"		2.5'	NA	NO RECOVERY	
920	558'-561"		2.5'	NA	NO RECOVERY	
925	561'-564"		2.5'	NA	NO RECOVERY	
930	564'-567"		2.5'	NA	NO RECOVERY	
935	567'-570"		2.5'	NA	NO RECOVERY	
940	570'-573"		2.5'	NA	NO RECOVERY	
945	573'-576"		2.5'	NA	NO RECOVERY	
950	576'-579"		2.5'	NA	NO RECOVERY	
955	579'-582"		2.5'	NA	NO RECOVERY	
960	582'-585"		2.5'	NA	NO RECOVERY	
965	585'-588"		2.5'	NA	NO RECOVERY	
970	588'-591"		2.5'	NA	NO RECOVERY	
975	591'-594"		2.5'	NA	NO RECOVERY	
980	594'-597"		2.5'	NA	NO RECOVERY	
985	597'-600"		2.5'	NA	NO RECOVERY	
990	600'-603"		2.5'	NA	NO RECOVERY	
995	603'-606"		2.5'	NA	NO RECOVERY	
1000	606'-609"		2.5'	NA	NO RECOVERY	

COHESIVE, 10-12% fine to med sand



CH2MHILL

PROJECT NUMBER

A69935.04.04.02

WELL NUMBER

MW-34

SHEET 1

OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: DOWELL-Schlumberger-Artesian

LOCATION: Artesian, NM

ELEVATION: NM

DRILLING CONTRACTOR: WDC NEWP / I Sapiens


DRILLING METHOD AND EQUIPMENT USED: 3" CHE-85 1 1/2" W. 6.25" ID augers

START: 2/22/14

END: 2/22/14

LOGGER: A. Forsberg

WATER LEVELS: 18.1 ft bgs



1- Ground elevation at well

NM

2- Top of casing elevation

NM

3- Wellhead protection cover type

stove pipe 8 in x 5 ft

a) drain tube?

NO

b) concrete pad dimensions:

24 x 4" x 4"

depth of surface concrete

N/A

4- Dia./type surface casing

N/A

5- Dia./type of well casing

4 in SCH 40 PVC

6- Type/slot/size of screen

4 in 0.010 in slot 8 ft 40 PVC

7- Type screen filter quantity used

1020 Colorado silica sand
24 x 50 lb bags

8- Type of seal quantity used

3/8 in bentonite chips
2 x 50 lb bags

9- Grout

a) Grout mix used

3 x 50 lb bags Portland Type I, 15 lbs high yield beads, 15 gal H2O

b) Method of placement

free pour

c) Vol. of surface casing grout

N/A

d) Vol. of well casing grout

Development method

swab and bail + over pump

Development time

2 hrs

Estimated purge volume

55 u/sib, 100 pump

Comments drilled to 35 ft. tagged DTW, pulled well up to set screen from 17-27 ft bgs to account for high H2O

Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-1 EW-03			OSE FILE NUMBER(S) C-3773				
	WELL OWNER NAME(S) Schlumberger Technology Corporation			PHONE (OPTIONAL)				
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land			CITY STATE ZIP Sugar Land TX 77478				
	WELL LOCATION (FROM GPS) LATITUDE 32. 439 42826 N LONGITUDE 103. 894 5949 W			* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84				
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-22-14		DRILLING ENDED 8-22-14		DEPTH OF COMPLETED WELL (FT) 55		BORE HOLE DEPTH (FT) 61	DEPTH WATER FIRST ENCOUNTERED (FT) NA
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)					STATIC WATER LEVEL IN COMPLETED WELL (FT) NA		
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl) FROM TO		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	0 15		12 1/4	PVC	Flush	4	40	
	15 55		12 1/4	PVC	Flush	4	40	.040
	55 60		12 1/4	PVC	Flush	4	40	
3. ANNULAR MATERIAL	DEPTH (feet bgl) FROM TO		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION	PAGE 1 OF 2	

4. HYDROGEOLOGIC LOG OF WELL

WR-20 WELL RECORD & LOG (Version 06/08/2012)

SOIL BORING LOG

PROJECT

Dowell-Schlumberger-Artena

LOCATION

Artena, NM

ELEVATION

NM

DRILLING CONTRACTOR

NEWPI Sapien

DRILLING METHOD AND EQUIPMENT

HME-85, 4.25 in ID cont. core augers

WATER LEVELS

NM

START

8/22/14 1007

FINISH

8/22/14 1205

LOGGER

A. Forstner

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
5	5-7	CL-1	5		NOT LOGGED soil removed by hand Auger	
10	7-10				SILT (CL) sandy, silty (CL) silty w/ light reddish brown, clay, low plastic, cohesive, mottled white - calcareous	
	10-12		0		SILT (CL) clayey white, dry, low plastic, cohesive, mottled w/ light red (above), nodules get less grading down	PID=0.0
13.5-14.5	12-13.5	CL-2	3		NO recovery	PID=0.0
14.5-15	13-14.5				SILT (CL) same as above (07-10)	PID=0.0
	15-16				SILT (CL) same as above (07-10)	PID=0.0
	16-17				NO recovery	PID=0.0
	17-18	CL-3	4		NO recovery	PID=0.0
20	18-20				NO recovery	PID=0.0
	20-22	CL-4	3		NO recovery	PID=0.0
25	22-23				NO recovery	PID=0.0
	23-24				NO recovery	PID=0.0
	24-25				NO recovery	PID=0.0
	25-26				NO recovery	PID=0.0
	26-27	CL-5	5		NO recovery	PID=0.0
30	27-30				NO recovery	PID=0.0



CH2MHILL

PROJECT NUMBER

460032-14.04.02

WELL NUMBER

EW-08

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dowell-Schlumberger, Artesia

ELEVATION: NM


DRILLING METHOD AND EQUIPMENT USED: CHE-BB w/ 6.25 in ID MCDR pump

WATER LEVELS: 18.75 ft bgs where development START: 2/22/14 END: 2/23/14

LOCATION: Artesia, NM

DRILLING CONTRACTOR: WEEVEP / I Superon

LOGGER: ASD/Silver



1- Ground elevation at well

NM

2- Top of casing elevation

NM

3- Wellhead protection cover type

Shell placed sand

a) drain tube?

NA

b) concrete pad dimensions;
depth of surface concrete

NA

4- Dia./type surface casing

NA

5- Dia./type of well casing

4 in sch 40

6- Type/slot/size of screen

0.040 slot 1/2 4 in sch 40

7- Type screen filter
quantity used8-16 colorado silica
24 x 50 lb bags8- Type of seal
quantity used70 in bentonite chips
4

9- Grout

a) Grout mix used

5 lbs gal

b) Method of placement

1 gal 130, 300 lbs Portland
free pour

c) Vol. of surface casing grout

NA

2 bags used

d) Vol. of well casing grout

Development method

build & sub + over pump

Development time

6.5 hrs

Estimated purge volume

55 gal w/sab + 330 gal

Comments during pumping, pulled pump
up 5-10 ft when turbidity was
able to be measured by instruments

Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-1 IJ-1				OSE FILE NUMBER(S) C-3772			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY Sugar Land		STATE TX	ZIP 77478
	WELL LOCATION (FROM GPS)	DEGREES LATITUDE 32.	MINUTES 439	SECONDS 7252 N	* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84			
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-21-14		DRILLING ENDED 8-21-14		DEPTH OF COMPLETED WELL (FT) 30	BORE HOLE DEPTH (FT) 31.5	DEPTH WATER FIRST ENCOUNTERED (FT) NA	
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)						STATIC WATER LEVEL IN COMPLETED WELL (FT) NA	
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl) FROM TO		BORE HOLE DIAM. (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	0 20.3		8 1/4	PVC	Flush	2	40	
	20.3 30.3		8 1/4	PVC	Flush	2	40	.040
3. ANNULAR MATERIAL	DEPTH (feet bgl) FROM TO		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION	PAGE 1 OF 2	

4. HYDROGEOLOGIC LOG OF WELL

WR-20 WELL RECORD & LOG (Version 06/08/2012)

LOCATION

POD NUMBER

TRN NUMBER

PAGE 2 OF 2



CH2MHILL

PROJECT NUMBER

460935.1A.04.02

WELL NUMBER

IT-1

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dowell-Schlumberger, Artesia

ELEVATION: NM

DRILLING METHOD AND EQUIPMENT USED: CHEGG, w/ 4.25 in ID HSA w/ core plug

WATER LEVELS: ~~20.3~~ 17.2 ft bgs


LOCATION: Artesia, NM

DRILLING CONTRACTOR: WOODNEW IT Sapien

START: 8/21/14

END: 8/21/14

LOGGER: A. Forsberg



- 1- Ground elevation at well NM
- 2- Top of casing elevation NM
- 3- Wellhead protection cover type 8" x 5 ft steel stove pipe
 - a) drain tube? NO
 - b) concrete pad dimensions: 2 ft x 4 ft
depth of surface concrete 4"
- 4- Dia./type surface casing NM
- 5- Dia./type of well casing 2 in SCH 40 PVC
- 6- Type/slot/size of screen 2 in SCH 40, 0.040 WR slot
- 7- Type screen filter quantity used 8-16 Colorado silica sand
10 x 50 lb bags
- 8- Type of seal quantity used 3 lb in bentonite chips
1.5 x 50 lb bags
- 9- Grout
 - a) Grout mix used 17 bags 4:1:3 & 3 x 90 lb fast set grout
 - b) Method of placement dry pack
 - c) Vol. of surface casing grout
 - d) Vol. of well casing grout
- Development method Surficial + pump
- Development time 20 gal s/b + 50 gal
- Estimated purge volume 2.5 hrs

Comments _____

Illustration not to scale.

31.3
17.2

PROJECT NUMBER 469035.1A.04.02	BORING NUMBER JT-1	SHEET 1	OF 1
SOIL BORING LOG			

PROJECT Dowell-Schlumberger - Artesian LOCATION Artesia, NM
 ELEVATION NM DRILLING CONTRACTOR NEWP E. Simpson
 DRILLING METHOD AND EQUIPMENT CHE-85 HSA 1 1/4" RS in augers & CTR plug
 WATER LEVELS NM START 2/21/14 0930 FINISH 2/21/14 0952 LOGGER Arden Sherry

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
5					SILT (CL), 2.5% R 712 pale red, dry, non plastic, non cohesive, like flour,	Soil logged from augers B2=0.0 PID=41.7 ppm 0938
10					SILT (CL), same as above, w/ white clay/claylike chunks	PID=0.2 ppm 0940
15					CLAY (CL) 2.5% R 413 light reddish brown, dry, low plastic, cohesive, trace (5-7%) med to coarse sand, white clay/claylike chunks (15%)	PID=0.0 0942
20					CLAY (CL) 2.5% R 414 reddish brown, moist, low plastic, cohesive, few (10-12%) fine to coarse sand	PID=0.0 0945
25					SILT (CL) 2.5% R 514 reddish brown, wet, low plastic, cohesive, PDI 2:1, fine to coarse sand.	PID=0.0 0946
30					SILT (CL) 2.5% R 514 reddish brown, wet, low plastic, cohesive, 10-12%, fine to coarse sand, trace rust colored nodules.	PID=0.0 0950



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-2 IJ-2				OSE FILE NUMBER(S) C-3772					
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)					
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY Sugar Land		STATE TX	ZIP 77478		
	WELL LOCATION (FROM GPS)		DEGREES LATITUDE 32.		MINUTES 439		SECONDS 6595 N			
		LONGITUDE 103.		895		2709 W		* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84		
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE										
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske				NAME OF WELL DRILLING COMPANY National EWP			
	DRILLING STARTED 8-21-14		DRILLING ENDED 8-21-14		DEPTH OF COMPLETED WELL (FT) 30		BORE HOLE DEPTH (FT) 31.5		DEPTH WATER FIRST ENCOUNTERED (FT) NA	
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)							STATIC WATER LEVEL IN COMPLETED WELL (FT) NA		
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:									
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger									
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)		CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)		CASING CONNECTION TYPE		CASING INSIDE DIAM. (inches)	
	FROM	TO							CASING WALL THICKNESS (inches)	
									SLOT SIZE (inches)	
	0		20.3		8 1/4		PVC		Flush	
	20.3		30.3		8 1/4		PVC		Flush	
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)		LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL		AMOUNT (cubic feet)		METHOD OF PLACEMENT	
	FROM	TO								
					See Attached					


FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 1 OF 2

4. HYDROGEOLOGIC LOG OF WELL	DEPTH (feet bgl)		THICKNESS (feet)	COLOR AND TYPE OF MATERIAL ENCOUNTERED - INCLUDE WATER-BEARING CAVITIES OR FRACTURE ZONES (attach supplemental sheets to fully describe all units)	WATER BEARING? (YES / NO)	ESTIMATED YIELD FOR WATER- BEARING ZONES (gpm)
	FROM	TO				
				See Attached	☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
	METHOD USED TO ESTIMATE YIELD OF WATER-BEARING STRATA: ☐ PUMP ☐ AIR LIFT ☐ BAILER ☐ OTHER – SPECIFY:				TOTAL ESTIMATED WELL YIELD (gpm):	

5. TEST; RIG SUPERVISION	WELL TEST	TEST RESULTS - ATTACH A COPY OF DATA COLLECTED DURING WELL TESTING, INCLUDING DISCHARGE METHOD, START TIME, END TIME, AND A TABLE SHOWING DISCHARGE AND DRAWDOWN OVER THE TESTING PERIOD.
	MISCELLANEOUS INFORMATION:	
	PRINT NAME(S) OF DRILL RIG SUPERVISOR(S) THAT PROVIDED ONSITE SUPERVISION OF WELL CONSTRUCTION OTHER THAN LICENSEE: Mark Green	

6. SIGNATURE	THE UNDERSIGNED HEREBY CERTIFIES THAT, TO THE BEST OF HIS OR HER KNOWLEDGE AND BELIEF, THE FOREGOING IS A TRUE AND CORRECT RECORD OF THE ABOVE DESCRIBED HOLE AND THAT HE OR SHE WILL FILE THIS WELL RECORD WITH THE STATE ENGINEER AND THE PERMIT HOLDER WITHIN 20 DAYS AFTER COMPLETION OF WELL DRILLING:	
	 SIGNATURE OF DRILLER / PRINT SIGNEE NAME	9-8-14 DATE

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 2 OF 2

SOIL BORING LOG

PROJECT Duwell Schlumberger Artesia LOCATION Artesia, NM
 ELEVATION _____ DRILLING CONTRACTOR NEWP / Sapien
 DRILLING METHOD AND EQUIPMENT CHE-BE, HSA 4.25 in ID augers w/ CHE plug
 WATER LEVELS KM START 8/2/14 0800 FINISH 8/2/14 0819 LOGGER A. F. V. Skelton

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
5					NOT LOGGED	2' delayed from auger with logs
10					CLAY (ML) 2.5 YR 6/4 reddish brown, clay, non plastic, non cohesive	PI = 0.0 ppm
15					CLAY (ML) 2.5 YR 6/4 reddish brown, dry, med plastic, cohesive 5% white clay nodules & calcareous chunks, sil. silt, fine to coarse sand	PI = 0.0
20					NOT LOGGED - Missed a 5' section	PI = 0.0
25					CLAY (ML) 2.5 YR 4/4 reddish brown, moist, low plastic, non cohesive fine to coarse angular sand (6-12%)	PI = 0.0
30					CLAY (ML) 2.5 YR 4/3 reddish brown, wet, low plastic, non cohesive trace (5-7%) fine to coarse sand	PI = 0.3



CH2M HILL

PROJECT NUMBER

469935.14.04.02

WELL NUMBER

IJ-2

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dowell-Schlumberger - Artesia

ELEVATION: NM

DRILLING METHOD AND EQUIPMENT USED: NEWPOME-615, HSH 14.25 in ID 4 CTR plug

WATER LEVELS: 17.42 on 8/21


LOCATION: Artesia, NM
DRILLING CONTRACTOR: WOC NEWP J. Sapien

START: 8/21/14 END: 8/21/14

LOGGER: A Fox Sierra

TD @ 110 on 8/21 29.72 bags

0821



1- Ground elevation at well

2- Top of casing elevation

3- Wellhead protection cover type Bin X 5 ft steel casing

a) drain tube?

b) concrete pad dimensions:

depth of surface concrete

4- Dia./type surface casing

5- Dia./type of well casing

6- Type/slot/size of screen

7- Type screen filter
quantity used8- Type of seal
quantity used

9- Grout

a) Grout mix used

b) Method of placement

c) Vol. of surface casing grout

d) Vol. of well casing grout

Development method

Development time

Estimated purge volume

Comments

2 in SCH 40 PVC

8-16 sand

2 in SCH 40 O.CAO well
10 x 50 lb bags3/8 in bentonite chips
1.5 x 50 lb bags

10 lbs high yield bento, 3 x 90 lbs portland

15 lbs H₂O
free pour

WOC NEWP + Overpump

35 min

25 gal + 25 gal

Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-3 IJ-3				OSE FILE NUMBER(S) C-3772			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY Sugar Land		STATE TX	ZIP 77478
	WELL LOCATION (FROM GPS)	DEGREES LATITUDE 32.		MINUTES 439	SECONDS 5935	N	* ACCURACY REQUIRED: ONE TENTH OF A SECOND	
		LONGITUDE 103.		895	3684	W	* DATUM REQUIRED: WGS 84	
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-20-14		DRILLING ENDED 8-20-14		DEPTH OF COMPLETED WELL (FT) 30	BORE HOLE DEPTH (FT) 31.5	DEPTH WATER FIRST ENCOUNTERED (FT) NA	
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)						STATIC WATER LEVEL IN COMPLETED WELL (FT) NA	
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0	20.3	8 1/4	PVC	Flush	2	40	
	20.3	30.3	8 1/4	PVC	Flush	2	40	.040
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 1 OF 2

4. HYDROGEOLOGIC LOG OF WELL

WR-20 WELL RECORD & LOG (Version 06/08/2012)

PAGE 2 OF 2

SOIL BORING LOG

PROJECT Dowell Schlumberger ArtesianLOCATION Artesian, NMELEVATION NMDRILLING CONTRACTOR NEWP / I SapronDRILLING METHOD AND EQUIPMENT CHE 85 HSA w/ 4.25 in ID w/ CTR PIVOTWATER LEVELS NMSTART 8/20/14 1613 FINISH 8/20/14 1643LOGGER APR Slaves

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS	SOIL DESCRIPTION	COMMENTS
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
				6"-6"-6" (N)	SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
5					SILT (ML) 2.542 7/2, pale pink, dry, low plastic, non cohesive, almost like flour	PID=0.0ppm soil logged from augers
10					same as above, trace fine gravel 5-7% clay	1615 PID=0.0ppm
15					(FAN CLAY (CL) 2.542 5/3, reddish brown, dry, low plastic, cohesive, few fine to med gravel, trace fine to coarse sand	1616 B250.0 PID=0.0ppm
20					Not logged. Went to get camera for photo of frayed cable	1619
25					SILT (ML) 2.542 5/3, reddish brown, wet, low plastic, cohesive, trace fine to med gravel, few fine to coarse sand	1621
30					SILT (ML) 2.542 5/3 reddish brown, same as above	1626
35						1628

frayed cable on downhole hammer - removed hammer by



CH2MHILL

PROJECT NUMBER

460035.14.04.02

WELL NUMBER

IS-3

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dowell-Schlumberger Artesia

ELEVATION: NM

DRILLING METHOD AND EQUIPMENT USED:

WATER LEVELS: N/A 1068 hrs on 8/21

LOCATION: Artesia, NM

DRILLING CONTRACTOR: WDC NEWP / I Capion

START: 8/20/14

END: 8/21/14

LOGGER: A. Forsberg

TD=27.74 (on 8/21)

10650

1025




Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-4 IJ-4				OSE FILE NUMBER(S) C-3772			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY STATE ZIP Sugar Land TX 77478			
	WELL LOCATION (FROM GPS)	DEGREES		MINUTES		SECONDS		* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84
		LATITUDE	32.	439	5275	N		
	LONGITUDE	103.	895	5466	W			
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-19-14		DRILLING ENDED 8-19-14		DEPTH OF COMPLETED WELL (FT) 30		BORE HOLE DEPTH (FT) 31.5	
							DEPTH WATER FIRST ENCOUNTERED (FT) NA	
							STATIC WATER LEVEL IN COMPLETED WELL (FT) NA	
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)							
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0	20.3	8 1/4	PVC	Flush	2	40	
20.3	30.3	8 1/4	PVC	Flush	2	40	.040	
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION	PAGE 1 OF 2	

4. HYDROGEOLOGIC LOG OF WELL	DEPTH (feet bgl)		THICKNESS (feet)	COLOR AND TYPE OF MATERIAL ENCOUNTERED - INCLUDE WATER-BEARING CAVITIES OR FRACTURE ZONES (attach supplemental sheets to fully describe all units)	WATER BEARING? (YES / NO)	ESTIMATED YIELD FOR WATER- BEARING ZONES (gpm)
	FROM	TO				
				See Attached	☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
	METHOD USED TO ESTIMATE YIELD OF WATER-BEARING STRATA: ☐ PUMP ☐ AIR LIFT ☐ BAILER ☐ OTHER - SPECIFY:				TOTAL ESTIMATED WELL YIELD (gpm):	

5. TEST; RIG SUPERVISION	WELL TEST	TEST RESULTS - ATTACH A COPY OF DATA COLLECTED DURING WELL TESTING, INCLUDING DISCHARGE METHOD, START TIME, END TIME, AND A TABLE SHOWING DISCHARGE AND DRAWDOWN OVER THE TESTING PERIOD.
	MISCELLANEOUS INFORMATION:	
	PRINT NAME(S) OF DRILL RIG SUPERVISOR(S) THAT PROVIDED ONSITE SUPERVISION OF WELL CONSTRUCTION OTHER THAN LICENSEE: Mark Green	

6. SIGNATURE	THE UNDERSIGNED HEREBY CERTIFIES THAT, TO THE BEST OF HIS OR HER KNOWLEDGE AND BELIEF, THE FOREGOING IS A TRUE AND CORRECT RECORD OF THE ABOVE DESCRIBED HOLE AND THAT HE OR SHE WILL FILE THIS WELL RECORD WITH THE STATE ENGINEER AND THE PERMIT HOLDER WITHIN 20 DAYS AFTER COMPLETION OF WELL DRILLING:	
	 SIGNATURE OF DRILLER / PRINT SIGNEE NAME	<u>8-8-14</u> DATE

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER

POD NUMBER

TRN NUMBER

LOCATION

PAGE 2 OF 2

PROJECT NUMBER

A09035-14.0A.02

BORING NUMBER

IT-4

SHEET

OF 1

SOIL BORING LOG

PROJECT Daniel-Schlumberger, ArtesiaLOCATION Artesia, NMELEVATION NMDRILLING CONTRACTOR NEWP / I SapienDRILLING METHOD AND EQUIPMENT CHE-B5 HSA w/ 4.25 in ID augers & CTR pipingWATER LEVELS NMSTART 8/10/14 1452FINISH 8/10/14 1510LOGGER A Forstner

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS	SOIL DESCRIPTION	COMMENTS
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
				6"-6" (N)	SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
					SILT (CL) 2.5YR 7/3 light reddish brown, dry. Non plastic, non cohesive trace med gravel	PID=0.0ppm Soil logged from augers
5					same as above, w/ white calc-like nodules/chunks up to 2.5cm diam. though some are very soft & friable	PID=0.1ppm
10					LEAN CLAY (CL) 2.5YR 7/3, light reddish brown, low plastic, cohesive, abundant white nodules/chunks as above	1454 PID=0.1ppm
15					LEAN CLAY (CL) 2.5YR 5/3, reddish brown, moist, low plastic, cohesive, 5% fine to coarse sand	1456 PID=0.0ppm
20					SILT (CL) 2.5YR 5/3, reddish brown, moist, low plastic, cohesive, 5-7% fine to coarse sand	1458 PID=0.0ppm
25					LEAN CLAY (CL) 2.5YR 5/3, reddish brown, wet, low plastic, cohesive, 5-7% fine to coarse sand, 10% silt	1459 PID=0.0ppm Note throttle cable disconnected stop drilling to fix
30						1510



CH2MHILL

PROJECT NUMBER

4600351A.CA.02

WELL NUMBER

IJ-A

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dowell-Schlumberger-Artesia

LOCATION: Artesia, NM

ELEVATION: NM

DRILLING CONTRACTOR: W.D. NEWP IT Systems

DRILLING METHOD AND EQUIPMENT USED:

CME-85


HSA W4.25 in ID w/ Chipping

WATER LEVELS: 16.74 on 8/21

START: 8/20/14

END: 8/20/14

LOGGER: A. Persberg



1- Ground elevation at well

NM

2- Top of casing elevation

NM

3- Wellhead protection cover type

8' x 5' ft Steel (casing)

a) drain tube?

NO

b) concrete pad dimensions;

4' x 4' x 4"

depth of surface concrete

NA

4- Dia./type surface casing

NA

5- Dia./type of well casing

2 in SCH 40 PVC

6- Type/slot/size of screen

0.090 slot WR, 2 in SCH 40 PVC

7- Type screen filter quantity used

8 lb sand
10.5 x 50 lb bags

8- Type of seal quantity used

3 lb in bentonite chips
1.5 x 50 lb bags

9- Grout

a) Grout mix used

15 lbs high yield bentonite
3 x 90 lb bags portland, 17 gal H₂O

b) Method of placement

free pour

c) Vol. of surface casing grout

NA

d) Vol. of well casing grout

Development method

bul & swab + over pump

Development time

35 min + 20 min

Estimated purge volume

Comments

Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-5 IJ-5			OSE FILE NUMBER(S) C-3772				
	WELL OWNER NAME(S) Schlumberger Technology Corporation			PHONE (OPTIONAL)				
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land			CITY STATE ZIP Sugar Land TX 77478				
	WELL LOCATION (FROM GPS)	DEGREES MINUTES SECONDS		* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84				
		LATITUDE	32. 439 4281 N					
LONGITUDE	103. 895 5596 W							
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske		NAME OF WELL DRILLING COMPANY National EWP			
	DRILLING STARTED 8-19-14	DRILLING ENDED 8-19-14	DEPTH OF COMPLETED WELL (FT) 30	BORE HOLE DEPTH (FT) 31.5	DEPTH WATER FIRST ENCOUNTERED (FT) NA			
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)				STATIC WATER LEVEL IN COMPLETED WELL (FT) NA			
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0	20.3	8 1/4	PVC	Flush	2	40	
	20.3	30.3	8 1/4	PVC	Flush	2	40	.040
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				



FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION	PAGE 1 OF 2	

4. HYDROGEOLOGIC LOG OF WELL	DEPTH (feet bgl)		THICKNESS (feet)	COLOR AND TYPE OF MATERIAL ENCOUNTERED - INCLUDE WATER-BEARING CAVITIES OR FRACTURE ZONES (attach supplemental sheets to fully describe all units)	WATER BEARING? (YES / NO)	ESTIMATED YIELD FOR WATER- BEARING ZONES (gpm)
	FROM	TO				
				See Attached	☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
					☐ Y ☐ N	
	METHOD USED TO ESTIMATE YIELD OF WATER-BEARING STRATA: ☐ PUMP				TOTAL ESTIMATED	
	☐ AIR LIFT ☐ BAILER ☐ OTHER - SPECIFY:				WELL YIELD (gpm):	

5. TEST; RIG SUPERVISION	WELL TEST	TEST RESULTS - ATTACH A COPY OF DATA COLLECTED DURING WELL TESTING, INCLUDING DISCHARGE METHOD, START TIME, END TIME, AND A TABLE SHOWING DISCHARGE AND DRAWDOWN OVER THE TESTING PERIOD.
	MISCELLANEOUS INFORMATION:	
	PRINT NAME(S) OF DRILL RIG SUPERVISOR(S) THAT PROVIDED ONSITE SUPERVISION OF WELL CONSTRUCTION OTHER THAN LICENSEE: Mark Green	

6. SIGNATURE	THE UNDERSIGNED HEREBY CERTIFIES THAT, TO THE BEST OF HIS OR HER KNOWLEDGE AND BELIEF, THE FOREGOING IS A TRUE AND CORRECT RECORD OF THE ABOVE DESCRIBED HOLE AND THAT HE OR SHE WILL FILE THIS WELL RECORD WITH THE STATE ENGINEER AND THE PERMIT HOLDER WITHIN 20 DAYS AFTER COMPLETION OF WELL DRILLING:	
	 SIGNATURE OF DRILLER / PRINT SIGNEE NAME	 DATE

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER	
LOCATION			PAGE 2 OF 2

PROJECT NUMBER
460033.04.04.02BORING NUMBER
IJ-5

SHEET

OF

SOIL BORING LOG

PROJECT Dwell Schlumberger Artesia LOCATION Artesia, NM
 ELEVATION NM DRILLING CONTRACTOR NEWP I Capen
 DRILLING METHOD AND EQUIPMENT CME 85 +ISA, 4.25-in ID w/ CTR PIVOT
 WATER LEVELS NM START 8/12/14 1151 FINISH 8/12/14 1200 LOGGER ATV Sker

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
5					SILT (ML) 2.5 YR 6/3, light reddish brn, dry, non plastic, non cohesive, few med sands	PID=0.1 ppm Soil logged from augers
10					SILT (ML) 2.5 YR 6/4, reddish brn, dry, non plastic, non cohesive, few med sands, 5-7% clay	1152 PID=0.2 ppm
15					CLAY (CL) 2.5 YR 6/3, light reddish brn, non plastic non plastic, non cohesive, trace fine sands	1155 PID=0.1 ppm
20					CLAY (CL) 2.5 YR 4/4, reddish brn, wet, low plastic, cohesive, few med sands	1157 PID=0.2 ppm
25					SILT (ML) 2.5 YR 6/3, reddish brown, wet, low plastic, non cohesive, 10% clay	1200 PID=0.1 ppm Some lighter rig chatter @ 122 ft logs
30					SILT (ML) 2.5 YR 6/4, reddish brown, wet, low plastic, cohesive, few well graded sands	1202 PID=0.6



CH2MHILL

PROJECT NUMBER

469235.14.04.02

WELL NUMBER

IT-5

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dwell-schlumberger - Artesia

LOCATION: Artesia, NM

ELEVATION: NM


DRILLING CONTRACTOR: WDC LEMP / Inspection

DRILLING METHOD AND EQUIPMENT USED: CHE-85, HSA w/ 4.25-in ID augers

WATER LEVELS: 15 ft bgl - after well

START: 8/20/14 END: 8/20/14

LOGGER: Kfir Slonev



- 1- Ground elevation at well NM
- 2- Top of casing elevation NM
- 3- Wellhead protection cover type 8 in x 5 ft steel casing
 - a) drain tube? NO
 - b) concrete pad dimensions: depth of surface concrete
- 4- Dia./type surface casing N/A
- 5- Dia./type of well casing 2-in SCH 40
- 6- Type/slot/size of screen 0.040 wire wrapped
- 7- Type screen filter quantity used 816 sand 10 x 50 lb bags
- 8- Type of seal quantity used 3/4 in bentonite chips 2 x 50 lb bags
- 9- Grout
 - a) Grout mix used 2 x 90 lb bags w/ 10 gal H₂O + 10 lb bentonite yield bentonite
 - b) Method of placement freepour
 - c) Vol. of surface casing grout NA
 - d) Vol. of well casing grout NA
- Development method Swirl flow over pump
- Development time 5 min
- Estimated purge volume 55 gal + 100 gal

Comments _____



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-6 U-6				OSE FILE NUMBER(S) C-3772			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY STATE ZIP Sugar Land TX 77478			
	WELL LOCATION (FROM GPS)		DEGREES MINUTES SECONDS LATITUDE 32. 439 2955 N LONGITUDE 103. 895 6532 W		* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84			
	DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE							
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-19-14		DRILLING ENDED 8-19-14		DEPTH OF COMPLETED WELL (FT) 30		BORE HOLE DEPTH (FT) 31.5	
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)		DEPTH WATER FIRST ENCOUNTERED (FT) NA					
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:						STATIC WATER LEVEL IN COMPLETED WELL (FT) NA	
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0 20.3		8 1/4	PVC	Flush	2	40	
	20.3 30.3		8 1/4	PVC	Flush	2	40	.040
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 1 OF 2

4. HYDROGEOLOGIC LOG OF WELL

5. TEST: RIG SUPERVISION

5. SIGNATURE

PROJECT NUMBER <u>403935.14.04.02</u>	BORING NUMBER <u>IF-6</u>	SHEET <u>1</u>	OF <u>1</u>
SOIL BORING LOG			

PROJECT Dowell-Schlumberger ARK 19 LOCATION Artesia, NM
 ELEVATION NM DRILLING CONTRACTOR NEWP - I Sapien
 DRILLING METHOD AND EQUIPMENT CHE 85 HST w/ 4" plug 4.25 in ID augers
 WATER LEVELS NM START 8/10/14 10:00 FINISH 8/10/14 10:58 LOGGER APR Sherry

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
					SANDY SILT (ML) 2.5YR 4/3, reddish brn, dry, non-piste, non-cohesive, roots	PID=0.1ppm Soil logged from augers
5					SILT (ML) 2.5YR 6/2, pink, dry, non-piste, non-cohesive, Clay nodules up to 2.5 cm - white w/ mottled grey & reddish brown when broken	1046 PID=0.1ppm
10					CLAY (CL) 2.5YR 6/2, pale red, dry, non-piste, noncohesive, white clay nodules to 1cm, few coarse sand, trace med fine gravel.	1046 PID=0.2ppm
15					CLAY (CL) 2.5YR 4/4 reddish brn, moist, low piste, noncohesive, trace fine to med sand	1050 PID=0.2ppm BZ=0.0ppm
20					SILT (ML) 2.5YR 4/3 reddish brn, wet, lowpiste, cohesive, few of fine gravel	1052 PID=0.3ppm
25					SILT (ML) 2.5YR 5/4, reddish brn, wet, lowpiste, cohesive, few fine gravel	1053 PID=0.3ppm



CH2MHILL

PROJECT NUMBER

469935.14.04.02

WELL NUMBER

IFB

SHEET 1

OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Dowell-Schlumberger Artesia

LOCATION: ARKSTH, NM

ELEVATION: NM

DRILLING CONTRACTOR: WENNERUP / I SAICH

DRILLING METHOD AND EQUIPMENT USED:


CHEERS, HSA w/ 4.25" ID

WATER LEVELS: 10.6 ft bgs before development

START 8/29/14 0724

END: 8/29/14

LOGGER: Aferstern



1- Ground elevation at well

NM

2- Top of casing elevation

NM

3- Wellhead protection cover type

8 in x 6 ft steel casing - ABOVE ground

a) drain tube?

NO

b) concrete pad dimensions;

4' x 4' x 4"

depth of surface concrete

4- Dia./type surface casing

NA

5- Dia./type of well casing

2 in SCH 40

6- Type/slot/size of screen

0.040 wire wrap

7- Type screen filter quantity used

8-16 colorado silica 11 x 50 lb bags

8- Type of seal quantity used

3/8 in bentonite chips 1 3/4 x 50 lb bags

9- Grout

a) Grout mix used

15 lbs high yield grout, 17 gal H₂O, 2 x 90 lb bags Portland

b) Method of placement

Free pour

c) Vol. of surface casing grout

NA

d) Vol. of well casing grout

Development method

swab/bail + over pump

Development time

Estimated purge volume

45 gal + 150 gal

Comments

Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-7 U-7				OSE FILE NUMBER(S) C-3772			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY STATE ZIP Sugar Land TX 77478			
	WELL LOCATION (FROM GPS)	DEGREES	MINUTES	SECONDS	N	* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84		
		LATITUDE 32.	439	1961				
	LONGITUDE 103.	895	7469	W				
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-19-14		DRILLING ENDED 8-19-14		DEPTH OF COMPLETED WELL (FT) 30		BORE HOLE DEPTH (FT) 31.5	
					DEPTH WATER FIRST ENCOUNTERED (FT) NA			
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)						STATIC WATER LEVEL IN COMPLETED WELL (FT) NA	
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0	20.3	8 1/4	PVC	Flush	2	40	
	20.3	30.3	8 1/4	PVC	Flush	2	40	.040
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 1 OF 2

4. HYDROGEOLOGIC LOG OF WELL

5. TEST; RIG SUPERVISION

6. SIGNATURE

PROJECT NUMBER

469935.14.04.02

BORING NUMBER

IT-7

SHEET

OF 1

SOIL BORING LOG

PROJECT Dowell-Schlumberger Artesia LOCATION Artesia, NM
 ELEVATION 1111 DRILLING CONTRACTOR NEW P I Sapen
 DRILLING METHOD AND EQUIPMENT HSA w/ 4 1/2-in ID augers w/ CTR plugs
 WATER LEVELS NPI START 8/12/14 1000 FINISH 8/13/14 1012 LOGGER A Forsberg

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)			
					NOT LOGGED	Soil logged from augers
5					SLT (ML) 2.5YR 1/3 light reddish brown, dry, non-plstc, non cohesive, 10-15 % fine & med sands, 5% fine gravel	B2 = 0.0 ppm PID = 0.2 ppm
10					CLAY (CL) 2.5YR 5/4 reddish brown, dry, low plstc, non cohesive, 5-10% silt 5% med sands	1003 am PID = 0.2 ppm
15					CLAY w/ sand (CL-SP) 2.5YR 5/4 reddish brown, moist, low plstc, cohesive, fine to coarse silts, few fine gravel (angular) w/ 2.5YR silt, dark red, nodules	1006 am PID = 0.1 ppm
20					SLT (ML) 2.5YR 5/4, reddish brown, wet, med plstc, cohesive, few coarse sand	1008 am PID = 0.2 ppm
25					SLT (ML) 2.5YR 5/4, reddish brn, wet, med plstc, cohesive, few coarse sand, few fine gravel	1010 am PID = 0.1 ppm



CH2MHILL

PROJECT NUMBER

469935.1A.04.02

WELL NUMBER

IJ-7

SHEET 1 OF 1

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT: Duwell-Schlumberger-Arksga

LOCATION: Arksga, NM

ELEVATION: NM

DRILLING CONTRACTOR: NEWP / Sapien

DRILLING METHOD AND EQUIPMENT USED: CME-45 w/ 4.25-in augers

WATER LEVELS: 16.86 on 8/21

START: 8/21/14

END: 9/20/14

LOGGER: A. Forsberg




Illustration not to scale.



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NUMBER (WELL NUMBER) Pod-8 IJ-8				OSE FILE NUMBER(S) C-3772			
	WELL OWNER NAME(S) Schlumberger Technology Corporation				PHONE (OPTIONAL)			
	WELL OWNER MAILING ADDRESS 105 Industrial Boulevard Sugar Land				CITY STATE ZIP Sugar Land TX 77478			
	WELL LOCATION (FROM GPS)	DEGREES		MINUTES		SECONDS		* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84
		LATITUDE	32.	439	0301	N		
	LONGITUDE	103.	895	8366	W			
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE								
2. DRILLING & CASING INFORMATION	LICENSE NUMBER WD-1210		NAME OF LICENSED DRILLER Bryan Nydoske			NAME OF WELL DRILLING COMPANY National EWP		
	DRILLING STARTED 8-19-14		DRILLING ENDED 8-19-14		DEPTH OF COMPLETED WELL (FT) 30		BORE HOLE DEPTH (FT) 31.5	
	DEPTH WATER FIRST ENCOUNTERED (FT) NA		STATIC WATER LEVEL IN COMPLETED WELL (FT) NA					
	COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☐ SHALLOW (UNCONFINED)							
	DRILLING FLUID: ☐ AIR ☐ MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: ☐ ROTARY ☐ HAMMER ☐ CABLE TOOL ☒ OTHER - SPECIFY: Auger							
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
	0	20.3	8 1/4	PVC	Flush	2	40	
	20.3	30.3	8 1/4	PVC	Flush	2	40	.040
3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT		
	FROM	TO						
				See Attached				

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER	POD NUMBER	TRN NUMBER
LOCATION		PAGE 1 OF 2

4. HYDROGEOLOGIC LOG OF WELL

WR-20 WELL RECORD & LOG (Version 06/08/2012)

LOCATION PAGE 2 OF 2

PROJECT NUMBER 469935.14.CA.02	BORING NUMBER JJ8	SHEET 7	OF 1
SOIL BORING LOG			

PROJECT D-5 Artesia LOCATION Artesia, NM
 ELEVATION NM DRILLING CONTRACTOR NEWP
 DRILLING METHOD AND EQUIPMENT HSA (IME 85 4/4 in ID @ 110 RPM) 146 I. Sapien Driller
 WATER LEVELS NM START 0850 8/9/14 FINISH 0906 8/9/14 LOGGER A. Forsberg

DEPTH BELOW SURFACE (FT)	SAMPLE			STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION	COMMENTS
	INTERVAL	NUMBER AND TYPE	RECOVERY (FT)		SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
					NOT LOGGED	Soil lagged from outside of augers
5					NOT LOGGED	
10					LEAN CLAY (CL), 2.54 R 2/3, light reddish brown, dry, low plastic, cohesive, 10-15% clay, little med gravel	
15					LEAN CLAY (CL), 2.54 R 2/3 reddish brown, moist, low plastic, noncohesive, few med sands	VOCs = 0.1 ppm BZ = 0.0 ppm
20					SILT (ML) 2.54 R 2/3, weak red, wet, low plastic, noncohesive, few med sand, 5-10% fine sand.	0.002 VOCs = 0.0
25					SILT (ML) 2.54 R 2/3 reddish brown, wet, med plastic, cohesive, 5-10% fine sand, trace coarse sand	0.004 VOCs = 0.0
30						

GROUND WATER MONITORING WELL COMPLETION DIAGRAM

PROJECT:

ELEVATION:

DRILLING METHOD AND EQUIPMENT USED:

WATER LEVELS:	5.4	m	8	2
---------------	-----	---	---	---


LOCATION :

DRILLING CONTRACTOR : ~~WDC~~ NEWP I Sapion

CHE-85 w/4.25 in ID HSAangers

START: 8/20/14 END: 8/20/14

LOGGER: A. J. S. S. S.



1. Ground elevation at well
NM
2. Top of casing elevation
NM
3. Wellhead protection cover type
6 in x 5 ft steel casing
a) drain tube?
NO
b) concrete pad dimensions;
4' x 4' x 4"
depth of surface concrete
4. Dia./type surface casing
NA
5. Dia./type of well casing
2 in SCH 40 PVC
6. Type/slot/size of screen
2 in SCH 40 0.090 slot wire
7. Type screen filter
sand
quantity used
10 x 50 lb bags
8. Type of seal
grout
quantity used
3/8 in bentonite chips
1.5 x 50 lb bags
9. Grout
a) Grout mix used
fells gel, 3/8 in bentonite chips
b) Method of placement
free pour
c) Vol of surface casing grout
NA
d) Vol. of well casing grout
- Development method
snubbing + over pump
- Development time
- Estimated purge volume
5 gal + 40 gal

Comments

Illustration not to scale.