3R - 162

GENERAL CORRESPONDENCE

YEAR(S):



Certified Mail: #7002 0510 0000 0307 2393

January 14, 2004

Mr. William C. Olson New Mexico Oil Conservation Division 1220 St. Francis Dr. Santa Fe, NM 87504 RECEIVED

JAN 20 2004

Oil Conservation Division Environmental Bureau

RE: Well Abandonment at Closed Sites

Dear Mr. Olson:

El Paso Field Services (EPFS) hereby submits for your records abandonment forms for sites that have been approved for closure. As stipulated as a condition of final closure the monitoring wells at the sites listed below have been plugged and abandoned in accordance with EPFS' approved monitoring well abandonment plan. The forms documenting the plugging and abandoning of monitoring wells listed below are attached to this letter. In addition three monitoring wells were abandoned as approved at the Blanco Plant.

Charley Pah #4	TMW-1	Navajo
Rementa et al #1	MW-1, 2 and 3	Navajo
D-Loop Line Drip	MW-1, 2 and 3	Federal
Ohio C Government #3	MW-1	Federal
WD Heath B #5	MW-1	Federal
Lat 3B-39 Line Drip	MW-1, 2 and 3	Non-Federal
Blanco Plant	MW-10, 17 and 18	Non-Federal

If you have any questions concerning the attached well abandonment forms or require additional information please call me at (505) 599-2124.

Sincerely,

Scott T. Pope P.G.

Senior Environmental Scientist

Attachments: as stated

xc: Mr. Denny Foust, NMOCD, Aztec - w / enclosures; 1st Class Mail

Mr. Bill Liesse, BLM – w / enclosures (federal sites only), 1st Class Mail

Mr. Bill Freeman, Navajo EPA – w/ enclosures (Navajo Sites Only), 1st Class Mail

Mr. James Walker, USEPA - w / enclosures (Navajo Sites Only), 1st Class Mail

Monitor Well Abandonment Record

1, 3 ***********************************
Name: EPFS city: Farnington State: NM
Address: 614 Reilly Ave zip: 87401 Phone: 1505)599-2120
2. Monitor Well Location:
Location Name: EL PASO CHARLEY PAHTHY Monitor Well I.D.: TMW-1
1/4 of, K 1/4 of, Section 1/2 Township 1/1/2 Range 09 W
County: Meter # 71531
3. Description:
Well depth: 24.90 ft. Casing material (circle one): Steel Plastic Concrete
Depth to water: 10.84 ft. Installation type (circle one): Drilled Driven Augered
Casing diameter: 2 in.
Depth of casing: 22-10 ft. GROUND LEVEL
4. Abandonment Method:
Well Casing: Removed Abandoned in place (Cut 3 below surface)
Plugging Method: No. of Bags of Cement: No. of Bags of Bentonite Powder: No. of Bags of Bentonite Pellets: Pressure grouting Bentonite pellets A //8 Bentonite Pellets:
Signature: Seonación Tena Title: De 11-03
Printed Name: / fanoccio Tenci Title: /) CI // AV