

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

API #30-006-20007

34. Indicate Type of Lease State ☐ Fee ☒
3. State Oil & Gas Lease No. N/A
7. Unit Agreement Name N/A
8. Farm or Lease Name EXXON MINERAL FEE
9. Well No. #1
10. Field and Pool, or Wildcat WILDCAT
12. County CIBOLA

SUNDARY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator AUSTRA-TEX OIL COMPANY
3. Address of Operator 909 NE LOOP 410 SUITE 600 SAN ANTONIO, TEXAS 78209
4. Location of Well UNIT LETTER F 1650 FEET FROM THE NORTH LINE AND 1980 FEET FROM WEST THE LINE, SECTION 23 TOWNSHIP 12N RANGE 4W MAPAL.
15. Elevation (Show whether DF, RT, GR, etc.) 6645 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1708.

1. Drill 8-1/2" hole f/532-3243 feet.
2. Reduce hole size from 8-1/2" to 7-7/8" at 3243 feet.
3. Drill 7-7/8" hole from 3243 to 5723 feet. TD well @ 0830 hrs on 9-1-87.
4. run logs: DIL/SFL/SP/FDC/CNL/CAL/GR plus sidewall cores. No Shows.
5. set cement plugs at: 5090', 4500', 3200', 1710', 1270', 582' & surface. Cement each plug w/30 sks class "B" Neat. Displace w/8.8 ppg drill mud.
6. Oil Conservation Division rep. (Roy Johnson) at well site during plugging operations.
7. Preparing to clear location of debris and reclaim location.

FORMATION TOPS:

Dakota	150 feet	Carmel	1355 feet
Morrison	260 feet	Windgate	1390 feet
Summerville	1100 feet	Chinle	1420 feet
Todilito	1220 feet	Glorieta	2912 feet
Entrada	1280 feet	Yeso	3102 feet

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

DRILLED BY R. Johnson TITLE Drilling Manager DATE 3 September 87
APPROVED BY R. Johnson TITLE DISTRICT SUPERVISOR DATE 9-9-87
CONDITIONS OF APPROVAL, IF ANY: