

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-007-20118

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR 'A'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Coalbed Methane

2. Name of Operator

SONAT RATON, L.L.C.

3. Address of Operator

P.O. Box 190; Raton, NM 87740

4. Well Location

Unit Letter M : 1281.84 feet from the South line and 824.69 feet from the West line

Section 36

Township 32 N

Range 19 E

NMPM Colfax

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8245.73'(GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

07/31/99: MIRU Thornton Rig #2. Spud well at 1:00 P.M. Drill 11" hole to 364'.

08/01/99: Ran and set 8-5/8", 23#, WC-50 casing at 352'.

Cement with 100 sx - Circ. 22 sx to surface.

08/03/99: T.D. 7-7/8" hole @ 2580'.

08/04/99: Run open hole logs. RDMO Thornton Rig #2. MIRU completion Rig. Ran and set 5 1/2", 15.5#, M-50 casing at 2541.

Cement with 300 sx. No cement to surface.

08/16/99: Ran CBL. Found TOC at 1400' with good cement below.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Wael W. Putscher TITLE Petroleum Engr. Advisor DATE 8/31/99

Type or print name Wael W. Putscher

Telephone No. 505-445-4620

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 9/2/99

Conditions of approval, if any: