

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20268
1. Type of Well: Oil Well ☐ Gas Well ☐ Other ☒ Coalbed Methane		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 190, Raton, NM 87740		7. Lease Name or Unit Agreement Name: VPR D
4. Well Location Unit Letter <u>N</u> : <u>519.4</u> feet from the <u>South</u> line and <u>1942.8</u> feet from the <u>West</u> line Section <u>26</u> Township <u>31N</u> Range <u>17E</u> NMPM COLFAX County		8. Well No. 50
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8327' (GL)		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐	REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐
OTHER: ☐	OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

01/13/02 Spud @ 11:30 p.m. Drill 11" surface hole to 335'. Run 10 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 324'.

01/14/02 Halliburton mixed and pumped 85 sx Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 55 psi with 6% salt, 5#/sx gilsonite, and .3% versaset. Circulate 4 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

01/15/02 Drill 7 7/8" hole from 335' - 1780'. Reached TD 1780' at 6:00 a.m.
MIRU Schlumberger & log well.

01/16/02 MIRU Leed. Ran 54 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 1744'.

01/16/02 MIRU Halliburton. Mix and pump 20 bbls gel pre flush at 3 bpm with 15 psi, 5 gal LGC-8, 120# magmafiber, 100# barcarb with 5 bbls water spacer. Pumped 212 sx Midcon II PP, 13 ppg, yield 2.03 at 3 bpm with 25 psi, 6% salt, 2 lb/sx Granulite, 5 lb/sx Gilsonite, .2% Versaset and .1% Super CBL. Plug down @ 11:15 a.m. with 1350 psi. Circulated 13 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Ordemann TITLE Engineer DATE 02-05-02

Type or print name William M. Ordemann Telephone No. (505) 445-6724
(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 2/7/02
Conditions of approval, if any: