

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. 30-007-20348

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR A

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190 RATON, NM 87740

8. Well No. 91

9. Pool name or Wildcat

4. Well Location

Unit Letter F : 2520.8 feet from the North line and 1411.8 feet from the West line
Section 34 Township 32N Range 20E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
7939' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: COMPLETION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

05/18/02 HES ran cement bond log. TOC at 1750'.

HES squeezed perfs at 1705'. Mixed and pumped 267 sks Midcon II with 6% salt, 5#/sk granulate, 2#/sk gilsonite, .3% versaset, .3% super CBL, and 1/4 #/sk floccle at 3 bpm, 10 psi. Circulated 14 bbls of cement to surface.

06/26/02 HES perf'd 1st stage: 2058'-2060', 2077'-2079' 3 SPF 10 Holes

HES frac'd 1st stage: Pumped 2.4 bbls HCL acid with 510 lbs of 16/30 Brady sand at 5.0 bpm, ATP 4547 psi, ISIP 3040 psi.

HES perf'd 2nd stage: 1876'-1878' 3 SPF 5 Holes

HES frac'd 2nd stage: Pumped 2.4 bbls HCL acid with 21,200 lbs of 16/30 Brady sand at 8 bpm, ATP 2170 psi, ISIP 196 80 psi.

HES perf'd 3rd stage: 1238'-1240' 3 SPF 5 Holes

HES frac'd 3rd stage: Pumped 2.4 bbls HCL acid with 11,200 lbs of 16/30 Brady sand at 7.9 bpm, ATP 1982 psi, ISIP 36 psi.

HES perf'd 4th stage: 1192'-1194' 3 SPF 5 Holes

HES frac'd 4th stage: Pumped 2.4 bbls HCL acid with 10,700 lbs of 16/30 Brady sand at 7.8 bpm, ATP 2347 psi, ISIP 77 psi.

HES perf'd 5th stage: 1165'-1167' 3 SPF 5 Holes

HES frac'd 5th stage: Pumped 2.4 bbls HCL acid with 20,200 lbs of 16/30 Brady sand at 8 bpm, ATP 1880 psi, ISIP 260 psi.

07/01/02 Installed rods, tubing, and pump. Well is ready to be put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 08/15/02

Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)
APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 8/21/02

Conditions of approval, if any: