

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20357
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name: VPR A
1. Type of Well: Oil Well ☐ Gas Well ☒ Other X Coalbed Methane		
2. Name of Operator EL PASO ENERGY RATON, L.L.C.	8. Well No.	56X
3. Address of Operator P.O. Box 190, Raton, NM 87740	9. Pool name or Wildcat	
4. Well Location Unit Letter _____ P : <u>691.1</u> feet from the <u>South</u> line and <u>1110.4</u> feet from the <u>East</u> line Section <u>23</u> Township <u>32N</u> Range <u>20E</u> NMPM COLFAX County		
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 7674' (GL)		

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

04/21/02 Spud in @ 10:30 a.m. Drill 11" surface hole to 330'. Ran 11 jts of 8 5/8", J-55, 23 ppf ST&C casing to 324'. Halliburton mixed and pumped 85 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 60 psi with 6% salt, 5#/sx gilsonite, .3% versaset. Circulated 3 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.

04/22/02 Drill 7 7/8" hole f/ 330' - 2095'. Reached TD 2095'. MIRU Schlumberger & log well. Ran 50 jts of 5 1/2", M-50, 15.5 ppf LT &C casing to 2062'. Halliburton mixed and pump 20 bbls gel pre flush at 4 bpm at 10 psi, 315 sks Midcon II, 13.0 ppg, yield 2.04, with 6% salt, .3% versaset, 5#/sx gilsonite, and .3% Super CBL. Plug down @ 10:30 p.m. with 1300 psi. Circulated 15 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 04/23/02

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 4/26/02
Conditions of approval, if any: