

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐	7. Unit Agreement Name
Name of Operator Public Lands Exploration Co., Inc.			8. Farm or Lease Name Barbara
Address of Operator 4835 LBJ Freeway, Suite 635, Dallas, Texas 75234			9. Well No. 2
Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>17</u> TOWNSHIP <u>11N</u> RANGE <u>26E</u> NMPM.			10. Field and Pool, or Wildcat Wildcat
11. Elevation (Show whether DF, RT, GR, etc.) 4768.0' GL			12. County Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

REFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
RELL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOBS ☐	
OTHER ☐	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12" hole at 10:07 P. M., 8-27-80, TD 26.7'. Set 26.7' of 8 5/8" 23# casing. Cemented with 5 sacks of neat cement containing 2% calcium chloride from TD to surface. Drilled well to 913' with 7 7/8" bit and from 913' to 993' TD with 6 1/4" bit. Received permission to plug well from Mr. Carl G. Ulvog on February 10, 1981. He recommended a 66 sack cement plug be set from 993' TD back to 734' and a 13 sack plug from 40' back to surface. Attempted to clean out well to TD but was unable to get below 965'. A 66 sack cement plug was set from 965' back to 734'. Checked and found top of cement was below 735'. A 17 sack cement plug was set from 700' back to 641' and a 13 sack plug from 40' back to surface. Installed marker and filled pit. Location is ready for inspection.

Cored well as follows: 679' - 705'; 705' - 731'; 731' - 758'; 758' - 784';
784' - 810'; 810' - 836'; 836' - 862'; 862' - 887' and
887' - 913'.

Cementing operations completed Feb. 16, 1981.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

By Charles C. Day TITLE Agent DATE April 7, 1981

APPROVED BY _____ TITLE PETROLEUM GEOLOGIST DATE _____

CONDITIONS OF APPROVAL, IF ANY: