

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES REQUIRED	
DISTRIBUTION	
SANTA FE	☒
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-77

10. Indicate Type of Well
State ☐ Other ☒
3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.

1. OIL ☐ GAS ☒ OTHER: C02
2. Name of Operator: Amoco Production Company
3. Address of Operator: P.O. Box 606, Clayton, NM 88415
4. Location of Well: UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 14 TOWNSHIP 18-N RANGE 33-N N.M.P.M.
7. Unit Agreement Name: Bravo Dome Carbon Dioxide Gas Unit
8. Term or Lease Name: Bravo Dome Carbon Dioxide Gas Unit
9. Well No.: 1833 141F
10. Field and Pool or Kilobbl: Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area
15. Elevation (Show whether DF, RT, GR, etc.): 4743' G.L.
16. County: Harding

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OWS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 10-14-84 Aztec Rig 56 spudded a 12 1/4" hole at 6:00pm drilling to a td of 708 ft. Ran and set 9-5/8" casing at 708'. Cemented with 390 sacks Class H cement with additives. Plugged down at 11:30pm. Circulated 160 sacks Class H cement to reserve pit. Wait on Cement for 12 hours. Tested casing to 600 psi x Ok. On October 19, 1984, ran and set 7" casing at 2805'. Cemented with 700 sacks Class H cement with additives. Plugged down at 1:30pm on 10-19-84. Circulated 35 sacks cement to reserve pit. Rig released 4:30pm on 10-19-84.

2-NMOC, SF 1-J.R.Barnett HOU.Rm.21.156 1-F.J.Nash HOU RM.4.206 1-WF,C 1-WF,H 1-Susp
-JSM 1-Amerada Hess 1-Amerigas 1-Cities Service 1-Conoco 1-C02 in Action 1-Sun
-Excelsior 1-Tex 1-Exxon

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: John S. McElyea TITLE: Asst. Adm. Analyst DATE: 10-23-84
APPROVED BY: DATE: 10-29-84
CONDITIONS OF APPROVAL, IF ANY: TITLE: DIRECTOR