

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Tucumcari, New Mexico January 28, 1952

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the _____
Ray Oil Company & T. A. Kirk-Hoover Well No. 1 in NWSE

Company or Operator _____ Lease _____
of Sec. 30, T. 11N, R. 28E, N. M. P. M., Wildcat Field.
Quay County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Intend to: Pull out free 7" casing; build homemade bridging plug above bottom of cemented 8" casing, 2450'; cut off 8" with collar ripper in vicinity of 2000' & pull entire string out; build homemade bridging plug above bottom of cemented 10", 1425'; cut off 10" with collar ripper in vicinity of 1200' & pull out 10", up to 800'; build homemade plug & cement off salt water interval (1020-1050'); allow cement to set and pull out remainder of 10"; cut off 13 3/8" in vicinity of 450', fill same with heavy pit mud and then proceed to pull out all of 13 3/8" shot free; let mud set while tearing down rig; fill 18" conductor pipe with 10 sacks cement; Set 4'x4" surface marker as called for by Oil Conservation Commission.

NOTE: Above homemade bridging plugs will be followed by 5-6' Calseal mix and 5-6' Portland cement (common).

Approved 30 January, 19 52
except as follows:

OIL CONSERVATION COMMISSION,

By Engene A. ...
Title geologist

RAY OIL COMPANY

Company or Operator

By E. D. HumphreyPosition Drilling Superintendent

Send communications regarding well to

Name RAY OIL COMPANYAddress 6212 Lemmon AvenueDallas, Texas