

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 20811
SANTA FE, NEW MEXICO 87501

Form O-101
Revised 12-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

10. Indicate Type of Lease	State ☐ Free ☒
11. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION AND PERMIT FOR PROPOSALS FOR SUCH PROPOSALS.

1. OIL WELL ☐ GAS WELL ☒ OTHER: CO2	7. Unit Agreement Name Bravo Dome Carbon Dioxide Gas Unit
2. Name of Operator Amoco Production Company	8. Field or Lease Name Bravo Dome Carbon Dioxide Gas Unit
3. Address of Operator P.O. Box 606, Clayton, NM 88415	9. Well No. 1835 121G
4. Location of Well UNIT LETTER <u>G</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18-N</u> RANGE <u>35-E</u> N.M.P.M.	10. Field and Pool, or Kilobbls Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area
15. Elevation (Show whether DF, RT, GR, etc.) 4470' G.L.	12. County Union

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On September 13, 1984, Aztec Rig 56 spudded a 12 1/4" hole at 5:00pm. On September 15 ran 9 5/8" casing set at 727 feet. Cemented with 390 sacks Class H cement with additives. Plugged down at 6:15 am on September 14, 1984. Tagged cement at 676 feet and tested casing at 600 PSI and ok. Wait on cement for 12 hours. On September 17 ran 7" casing and set at 2682 feet. Cemented with 750 sacks Class H Cement and circulated 228 sacks to pit. Plugged down at 3:30 pm on September 17, 1984. Rig released 6:30pm on September 17, 1984.

0+2-NMOCD,SF 1-J.R.Barnett HOU.Rm.21.156 1-F.J.Nash HOU RM.4.206 1-WF,C 1-WF,H 1-Susp
1-JSM 1-Amerada Hess 1-Amerigas 1-Cities Service 1-Conoco 1-CO2 in Action 1-Sun
1-Excelsior 1-Tex 1-Exxon

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John S McElroy TITLE Asst. Adm. Analyst DATE 9-18-84
APPROVED BY David C. Calhoun TITLE OIL AND GAS INSPECTOR DATE 9-20-84
CONDITIONS OF APPROVAL, IF ANY: