

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

MAR 22 1973

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. CIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Michael P. Grace II ✓	8. Farm or Lease Name Grace-Atlantic
3. Address of Operator P. O. Box 1418, Carlsbad, New Mexico	9. Well No. 1
4. Location of Well UNIT DEPTH <u>J</u> 1980 FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM <u>East</u> LINE, SECTION <u>24</u> TOWNSHIP <u>22S</u> RANGE <u>26E</u> NMPM.	10. Field and Pool, or Wildcat Und. S. Carlsbad Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3162 GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/12/73 Ran 128 jts. 29#, 78 jts. 26#, 79 jts. 23# and 54 jts. 32# 7" casing and set @ 11,768'. Cemented With 100 sks. Halliburton lt. & 400 sks Class "W". Plug down @ 2 p.m. under 1250 psig. 128 bbls. slurry cmt. Height @ 8500' W.O.C. 2 1/2 hrs.

273jts 1 1/2" 15.50# C-75 PH6 Hydril Tubing set @ 11,000' Tested to 6000#  
Baker 83 FA 47 Pkr seal assembly set @ 11,000'  
Perforated 11,420' - 11,440' 1/4 spf.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael P. Grace II TITLE Agent DATE March 20, 1973

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE APR 26 1973

CONDITIONS OF APPROVAL, IF ANY: