Form 9-330
(Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE* (See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 990, Farmington, New Mexico

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface 1550'S, 990'W
At top prod. interval reported below
At total depth

5. LEASE DESIGNATION AND SERIAL NO.
I-149-Ind-8473

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo Contract

7. UNIT AGREEMENT NAME
Huerfanito Unit

8. FARM OR LEASE NAME
Huerfanito Unit

9. WELL NO.
82 (MD)

10. FIELD AND POOL, OR WILDCAT
Blanco M.V. & Basin Dakota

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
Sec. 25, T-27-N, R-9-W N.M.P.M.

14. PERMIT NO. | DATE ISSUED

12. COUNTY OR PARISH: San Juan | 13. STATE: New Mexico

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
9-19-65	9-30-65	10-9-65	6270' GL	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
6880'	C.O. 6835'	2	→	0-6880	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*
4470-4560 (Mesa Verde)
6536-6736' (Dakota)

25. WAS DIRECTIONAL SURVEY MADE
Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN
I/ES, FDC/GR, Temp. Survey

27. WAS WELL CORED
No

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.40#	298'	13 3/4"	300 Sacks	
7" & 5.5"	23 & 15.5#	6880'	7 7/8"	1100 cu. ft.	

RECEIVED
NOV 4 1965
OIL CON. COM.
DIST. 3

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 3/8"	6715'	4600'
1 1/4"	4548'	

31. PERFORATION RECORD (*Interval, size and number*)
4470-78, 4496-4504 w/2 SPF; 4523-27, 4556-60 w/4 SPF
6536-40 w/4 SPF; 6602-10, 6620-28, 6708-16 w/1 SPF; 6732-36 w/2 SPF
All shots w/4" carriers & SDJ

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4470-4560	44,940 gal. water, 40,000# sand
6536-6736	50,400 gal. water, 30,000# sand 500 gal. acid

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
	Flowing	Shut-In

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
MV-10-27-65 Dak-10-20-65	3	3/4"					

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
MV-579 Dak-2151	MV-1101			MV 8200; Dak 2734		

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*)

TEST WITNESSED BY
MV- H. E. McAnally
Dak-D. R. Roberts

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED ORIGINAL SIGNED E. S. OBERLY TITLE Petroleum Engineer DATE 11-3-65

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Pictured Cliffs	2160	
Lewis	2230	
Cliff House	3732	
Menefee	3810	
Point Lookout	4452	
Mancos	4600	
Gallup	5630	
Greenhorn	6450	
Graneros	6490	
Dakota	6598	

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-683636