Permit Information:

Well Name: Convoy 28 State Com No. 706H

OCD – HOBBS 12/06/2017 RECEIVED

Location:

SL: 539' FNL & 2322' FEL, Section 28, T-24-S, R-33-E, Lea Co., N.M. BHL: 230' FSL & 2430' FEL, Section 33, T-24-S, R-33-E, Lea Co., N.M.

Casing Program:


Hole		Csg				DF _{min}	DF _{min}	\mathbf{DF}_{\min}
Size	Interval	OD	Weight	Grade	Conn	Collapse	Burst	Tension
17.5"	0 - 1,250'	13.375"	54.5#	J55	STC	1.125	1.25	1.60
12.25"	0-4,000'	9.625"	40#	J55	LTC	1.125	1.25	1.60
12.25"	4,000' - 5,000'	9.625"	40#	HCK55	LTC	1.125	1.25	1.60
8.75"	0 - 11,500'	7.625"	29.7#	HCP110	FXL	1.125	1.25	1.60
6.75"	0'-22,576'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

	No.	Wt.	Yld	
Depth	Sacks	lb/gal	Ft ³ /ft	Slurry Description
1250'	697	13.5	1.74	Lead: Class 'C' + 4.00% Bentonite + 2.00% CaCl2
				(TOC @ Surface)
	333	14.8	1.35	Tail: Class 'C' + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2%
				Sodium Metasilicate + 2.0% KCl (1.06 lb/sk)
5,000'	692	12.7	2.22	Lead: Class C + 0.15% C-20 + 11.63 pps Salt + 0.1% C-51 +
				0.75% C-41P (TOC @ Surface)
	303	14.8	1.32	Tail: Class C + 0.13% C-20
11,500'	375	10.8	3.67	Lead: Class C + 0.40% D013 + 0.20% D046 + 0.10% D065 +
				0.20% D167 (TOC @ 4,500')
	400	14.8	2.38	Tail: Class H + 94.0 pps D909 + 0.25% D065 + 0.30% D167
				+ 0.02% D208 + 0.15% D800
22,576'	950	14.8	1.31	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 +
				0.40% C-17 (TOC @ 11,000')

Mud Program:

Depth	Туре	Weight (ppg)	Viscosity	Water Loss
0 - 1250'	Fresh - Gel	8.6-8.8	28-34	N/c
1,250' - 5,000'	Brine	10.0-10.2	28-34	N/c
5,000'-11,500'	Oil Base	8.7-9.4	58-68	N/c - 6
11,500'-22,576'	Oil Base	10.0-11.5	58-68	3 - 6
Lateral				



Lateral: 22,576' MD, 12,494' TVD

BH Location: 230' FSL & 2430' FEL Section 33 T-24-S, R-33-E