District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 OCD - HOBBS 04/27/2020 DECEIVED

Submit Original to Appropriate District Office

GAS CAPTURE PLAN

| Date: 09/23/2019 | | |
|-----------------------------------|-----------------------|--------------------------|
| □ Original | Operator & OGRID No.: | EOG Resources, Inc. 7377 |
| ☐ Amended - Reason for Amendment: | | |
| | | |

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

| Well Name | API | Well Location (ULSTR) | Footages | Expected MCF/D | Flared or Vented | Comments |
|-----------------------------|-----------------------------|-----------------------|-------------------------|----------------|------------------|-------------------|
| Getty 5 Fed Com 701H | 30-025-**** | P-5-25S-33E | 259' FSL & 513' FEL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 702H | 30-025-**** | P-5-25S-33E | 259' FSL & 546' FEL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 703H | 30-025-**** | O-5-25S-33E | 275' FSL & 2613' FEL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 704H | 30-025-**** | N-5-25S-33E | 275' FSL & 2644' FWL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 705H | 30-025-**** | N-5-25S-33E | 275' FSL & 2611' FWL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 706H | 30-025-**** | M-5-25S-33E | 275' FSL & 1139' FWL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 707H | 30-025-**** | M-5-25S-33E | 275' FSL & 1106' FWL | ±3500 | None Planned | APD Submission |
| Getty 5 Fed Com 708H *** | 30-025-**** 47152 | M-5-25S-33E | 275' FSL & 1073' FWL | ±3500 | None Planned | APD Submission |

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Lucid Energy. Enterprise & Regency Field Services and will be connected to EOG Resources low/high pressure gathering system located in Lea County, New Mexico. EOG Resources provides (periodically) to Lucid Energy, Enterprise & Regency Field Services a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, EOG Resources and Lucid Energy, Enterprise & Regency Field Services have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Lucid Energy, Enterprise & Regency Field Services Processing Plant located in Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **Lucid Energy, Enterprise & Regency Field Services** system at that time. Based on current information, it is **EOG Resources'** belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines