Submit 1 Copy To Appropriate District Office	State of New Mexico	CD- RECEIVED 11/24/20 Form C-103
District I (575) 202 (1(1	Energy, Minerals and Natural Resources	Revised July 18, 2013
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, minerals and reading resources	WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	3002544469
<u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	Santa Fe, NM 87505	STATE × FEE 6. State Oil & Gas Lease No.
$\frac{District IV}{1220 \text{ S. St. Francis Dr., Santa Fe, NM}}$		313956
87505		
	ES AND REPORTS ON WELLS LS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICA	TION FOR PERMIT" (FORM C-101) FOR SUCH	NEPTUNE 10 STATE COM
PROPOSALS.) 1. Type of Well: Oil Well X G	as Well 🗍 Other	8. Well Number 206H
2. Name of Operator		9. OGRID Number
EOG RESOURCES		7377
3. Address of Operator		10. Pool name or Wildcat
5509 Champion Drive, Midla	nd, Texas 79703	98135 WC025 G09 S243310P
4. Well Location		Cmily Follis
Unit Letter_P:	250feet from the _SOUTH line and _55	
Section 10	Township 24S Range 33E	NMPM County LEA CO,NM
	11. Elevation (Show whether DR, RKB, RT, GR, etc. 3606 GL)
	3000 GL	
12 Check Ar	propriete Doy to Indicate Nature of Notice	Report or Other Data
12. Check Ap	propriate Box to Indicate Nature of Notice,	Report of Other Data
NOTICE OF INT	ENTION TO: SUE	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🗌	PLUG AND ABANDON	
	CHANGE PLANS COMMENCE DR	
	MULTIPLE COMPL CASING/CEMEN	Т ЈОВ
CLOSED-LOOP SYSTEM		sg- resubmitted NMOCD never rev'd⊡X
	ted operations. (Clearly state all pertinent details, and	
	c). SEE RULE 19.15.7.14 NMAC. For Multiple Co	
proposed completion or recor	npletion.	
proposed completion or recor	npletion.	
proposed completion or recor 2-12-2020 20" Conductor @ 115'	npletion.	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole	npletion.	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD	npletion.	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg),Trail w/225 sx Class C (1.34 yld, 14.8 ppg)	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement),Trail w/225 sx Class C (1.34 yld, 14.8 ppg)	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppc Test casing to 1,500 psi for 30 min Circ 711 sx cemel 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132	ı),Trail w/225 sx Class C (1.34 yld, 14.8 ppg) ti to surface	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25	ı),Trail w/225 sx Class C (1.34 yld, 14.8 ppg) ti to surface	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement wi 1,240 sx Class C (1.73 yld, 13.5 ppc Test casing to 1,500 psi for 30 min Circ 711 sx cemel 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132 Casing shoe @ 5,128' MD Ran 9-5/8", 40#, HCK-55 LTC (4,029' - 5,128')	ı),Trail w/225 sx Class C (1.34 yld, 14.8 ppg) nt to surface ' TVD	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.54 J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25	i),Trail w/225 sx Class C (1.34 yld, 14.8 ppg) It to surface 'TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc	rormal drilling ops.
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.54 J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25	i), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) It to surface ' TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) : cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with I	normal drilling ops.
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 00 05 if of 30 min 5 good Did not circ Based on conversation w/ NMOCD (3/36/2020) and t No additional verification or remediation required. page	i), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) It to surface ' TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) c cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with 1 je 1 of 2	normal drilling ops.
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132 Casing shoe @ 5,128' MD Ran 9-5/8", 40#, HCK-55 LTC (4,029' - 5,128') Lead ement w/ 1,005 sx Class C (2.32 yld, 12.7 ppg), Test casing to 2,000 psi for 30 min - good.Did not circ Based on conversation w/ NMOCD (3/36/2020) and t	i), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) It to surface ' TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) : cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with I	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132 Casing shoe @ 5,128' MD Ran 9-5/8", 40#, J-55 LTC (4',029') Ran 9-5/8", 40#, J-55 LTC (4',029') Ran 9-5/8", 40#, HCK-55 LTC (4',029') Lead ement w/ 1,005 sx Class C (2.32 yld, 12.7 ppg), Test casing to 2,000 psi for 30 min - good Did not circ Based on conversation w/ NMOCD (3/36/2020) and t No additional verification or remediation required. page Spud Date:	I), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) It to surface Trail w/410 sx Class C (1.42 yld, 14.8 ppg) cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with the pe 1 of 2	
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132 Casing shoe @ 5,128' MD Ran 9-5/8", 40#, HCK-55 LTC (4,029' - 5,128') Lead ement w/ 1,005 sx Class C (2.32 yld, 12.7 ppg), Test casing to 2,000 psi for 30 min - good Did not circ Based on conversation w/ NMOCD (3/36/2020) and t No additional verification or remediation required. page Spud Date: 3-13-2020	i), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) tt to surface ' TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) c cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc the calculated TOC EOG was given approval by the NMOCD to proceed with the ge 1 of 2 Rig Release Date: 04-07-20	20
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132 Casing shoe @ 5,128' MD Ran 9-5/8", 40#, HCK-55 LTC (4,029' - 5,128') Lead ement w/ 1,005 sx Class C (2.32 yld, 12.7 ppg), Test casing to 2,000 psi for 30 min - good Did not circ Based on conversation w/ NMOCD (3/36/2020) and t No additional verification or remediation required. page Spud Date: 3-13-2020	I), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) It to surface Trail w/410 sx Class C (1.42 yld, 14.8 ppg) cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with the pe 1 of 2	20
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.54' J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole Ran 9-5/8", 40#, J-55 LTC (0' - 4,029) Ran 9-5/8", 40#, J-55 LTC (0' - 4,0	a), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) t to surface 'TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with the ge 1 of 2 Rig Release Date: 04-07-20 prove is true and complete to the best of my knowledge	20 ge and belief.
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 1st Intermediate Hole @ 5,143' MD, 5,132 Casing shoe @ 5,128' MD Ran 9-5/8", 40#, HCK-55 LTC (4,029' - 5,128') Lead ement w/ 1,005 sx Class C (2.32 yld, 12.7 ppg), Test casing to 2,000 psi for 30 min - good Did not circ Based on conversation w/ NMOCD (3/36/2020) and t No additional verification or remediation required. page Spud Date: 3-13-2020	a), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) t to surface 'TVD Trail w/410 sx Class C (1.42 yld, 14.8 ppg) cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc he calculated TOC EOG was given approval by the NMOCD to proceed with the ge 1 of 2 Rig Release Date: 04-07-20 prove is true and complete to the best of my knowledge	20 ge and belief.
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.54' J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-13-2020 I hereby certify that the information ab SIGNATURE <i>Mill</i>	a), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) t to surface Trail w/410 sx Class C (1.42 yld, 14.8 ppg) c cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc the calculated TOC EOG was given approval by the NMOCD to proceed with r the calculated TOC EOG was given approval by the NMOCD to proceed with r ge 1 of 2 Rig Release Date: 04-07-20 to ve is true and complete to the best of my knowledge TITLE Regulatory Admini	20 e and belief. strator
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.54' J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cement 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole 3-25-2020 12-1/4" hole Ran 9-5/8", 40#, J-55 LTC (0' - 4,029) Ran 9-5/8", 40#, J-55 LTC (0' - 4,0	a), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) t to surface Trail w/410 sx Class C (1.42 yld, 14.8 ppg) c cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc the calculated TOC EOG was given approval by the NMOCD to proceed with r the calculated TOC EOG was given approval by the NMOCD to proceed with r ge 1 of 2 Rig Release Date: 04-07-20 to ve is true and complete to the best of my knowledge TITLE Regulatory Admini	20 e and belief. strator
2-12-2020 20" Conductor @ 115' 3-13-2020 17-1/2" hole 3-13-2020 Surface Hole @ 1,488' MD, 1,487' TVD Casing shoe @ 1,468' MD Ran 13-3/8' 54.5# J-55 STC Lead Cement w/ 1,240 sx Class C (1.73 yld, 13.5 ppg Test casing to 1,500 psi for 30 min Circ 711 sx cemer 3-25-2020 12-1/4" hole 3-25-2020 13 hole Spud Date: 3-13-2020 I hereby certify that the information ab SIGNATURE	a), Trail w/225 sx Class C (1.34 yld, 14.8 ppg) t to surface Trail w/410 sx Class C (1.42 yld, 14.8 ppg) c cement to surface, circ 10 bbl spacer to surface, TOC @ 155' by Calc the calculated TOC EOG was given approval by the NMOCD to proceed with r the calculated TOC EOG was given approval by the NMOCD to proceed with r ge 1 of 2 Rig Release Date: 04-07-20 to ve is true and complete to the best of my knowledge TITLE Regulatory Admini	20 e and belief. strator

Conditions of Approval (if any):