	UNITED STATE EPARTMENT OF THE I UREAU OF LAND MANA	NTERIOR	OCD Hobbs	OMB N Expires	FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010	
SUNDRY NOTICES AND REPORTS ON WE Do not use this form for proposals to drill or to re			HOBB	S OCD ^{5.} Lease Serial No. NMNM14812		
abandoned well. Use form 3160-3 (APD) for such proposals.				6 If Indian, Allottee	or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side. 7. If Unit or CA/Agreement, Name and/or Notestand Structure						
I. Type of Well ☐ Gas Well ☐ Other			8. Well Name and No. WERTA FEDERAL 3			
2. Name of Operator Contact: SORINA L F APACHE CORPORATION E-Mail: sorina.flores@apachecor			5	9. API Well No. 30-025-40799		
3a. Address 3b. Phone No 303 VETERANS AIRPARK LN #3000 Ph: 432-8 MIDLAND, TX 79705 Fx: 432-81				10. Field and Pool, or DRINKARD	10. Field and Pool, or Exploratory DRINKARD	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State		
Sec 35 T19S R38E 335FSL 990FEL / 32.610367 N Lat, 103.113922 W Lon				LEA COUNTY, NM		
12. CHECK APPF	ROPRIATE BOX(ES) TO	D INDICATE NATU	JRE OF NOTIC	E, REPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	□ ^{Acidize}	Deepen		roduction (Start/Resume)	□ Water Shut-Off	
□ Subsequent Report	□ Alter Casing	□ Fracture Tre		eclamation	□ Well Integrity	
-	Casing Repair	New Constr	-	ecomplete	🗙 Other Change to Original A	
□ Final Abandonment Notice	 Change Plans Convert to Injection 	Plug and Al Plug Back		emporarily Abandon 'ater Disposal	PD	
testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) BOND#: BLM-CO-1463 / NMB000736 APACHE REQUESTS APPROVAL TO REDUCE SURF HOLE SIZE FROM PERMITTED 12-1/4" TO 11" & TO ADJUST LEAD CMT VOLUM ACCORDINGLY. THE FOLLOWING CMT INFO IS FROM THE APPROVED APD WITH DHE EXCAPTION OF THE LEAD CMT VOLUME WHICH HAS BEEN ADJUSTED FO RTHE 11" HOLE (DEPTH IS 1660'). CURRENT #STUMPTES PUD IS 10/15/2012. 8-5/8" SURF CMT (100% EXCESS CMT TO SURF) LEAD: 350SX CLASS C W/2% CACL2, 0.13# CF, 3# LCM1, 0.005 GPS FP-6L, 4% BENTONITE (13.5 PPG, 1.75 YLD) COMP STRENGTH: 12 HR - 500 PSI 24 HR - 782 PSI						
Electronic Submission #154784 verified by the BLM Well Information System For APACHE CORPORATION, sent to the Hobbs Committed to AFMSS for processing by KURT SIMMONS on 10/24/2012 () Name(Printed/Typed) SORINA L FLORES Title SUPV DRLG SERVICES						
Signature (Electronic Submission) D.			10/15/2012			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
<u> </u>	·····	<u></u>			<u> </u>	
Approved By		Title			Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds lead or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations there applies the subject lease which would entitle the applicant to conduct operations there applies the subject lease which would entitle the applicant to conduct operations there applies the subject lease which would entitle the applicant to conduct operations there applies the subject lease which would entitle the applicant to conduct operations there applies the subject lease to conduct operations there applies the subject lease which would entitle the applicant to conduct operations there applies the subject lease to conduct operations the subject lease to conduct operations there applies the subject lease to conduct operations the subject lease to con				<u></u>		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						
** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **						

NOV 2 9 2012

.

. - --.2

32. Additional remarks, continued

TAIL: 200 SX CL C W/1% CACL2, 0.13# CF, 0.005 GPS FP-6L (14.8 PPG, 1.34 YLD) COMP STRENGTH: 12HR - 755 PSI 24HR - 1347 PSI