

District I - (575) 393-6161
District II - (575) 748-1283
District III - (505) 334-6178
District IV - (505) 476-3460

HOBS OCD

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

MAY 13 2013

WELL API NO. 30-025-40119
5. Indicate Type of Lease STATE [] FEE [x]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Dayton Hardy (306597)
8. Well Number 008
9. OGRID Number 873
10. Pool name or Wildcat 6660 / 60240 / 19190 / 62700
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3498' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [x] Gas Well [] Other []
2. Name of Operator Apache Corporation
3. Address of Operator 303 Veterans Airpark Lane, Suite 3000 Midland, TX 79705
4. Well Location Unit Letter J : 2310 feet from the South line and 2160 feet from the East line
Section 20 Township 21S Range 37E NMPM County Lea
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3498' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [] PLUG AND ABANDON [x]
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []

OTHER: PREP TO P&A [x]

OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Apache intends to perform the following in preparation of plugging and abandoning the well:

- 1. RIH w/retrieving head. Circulate sand off RBP @ 5030'. Release RBP & POOH.
2. RIH w/CIBP and set at 6840'. Cap plug w/35' cmt to P&A the Abo perfs (6862' - 7108'). TOC @ 6805'.
3. RIH w/CIBP and set @ 6580'. Cap plug w/35' cmt to P&A the Drinkard perfs (6607' - 6747'). TOC @ 6545'.
4. RIH w/CIBP and set @ 6170'. Cap plug w/35' cmt to P&A Tubb perfs (6219' - 6311'). TOC @ 6135'.
5. RIH w/2-7/8" prod tbg open ended to 6000'. RIH w/rods. POOH LD rods. (Leave 6000' of 2-7/8" prod tbg in well).
6. SWI. RDMO. (Guinn will finish P&A).

In the event that you cannot get CIBP's to the desired depths, RIH w/the tbg open ended and set 25 sx cmt plugs above the Abo, Drinkard & Tubb perfs so that the TOC is tagged at least at the depths indicated above each set of perfs.

Spud Date:

5/20/2011

Rig Release Date:

6/1/2011

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Reesa Holland Fisher

TITLE Sr. Staff Reg Tech

DATE 5/9/2013

Type or print name Reesa Holland Fisher

E-mail address: Reesa.Holland@apachecorp.com

PHONE: 432/818-1062

For State Use Only

APPROVED BY:

[Signature]

TITLE

[Signature]

DATE

5-23-2013

Conditions of Approval (if any):

MAY 23 2013