

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Hobbs
HOBBS OCD

JUN 10 2013

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		7. If Unit or CA Agreement, Name and No.	
1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other SWD <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		8. Lease Name and Well No. <u>(39946)</u> Pintail 3 Federal SWD #1	
2. Name of Operator COG Operating LLC.		9. API Well No. 30-025-41208	
3a. Address 2208 West Main Street Artesia, NM 88210	3b. Phone No. (include area code) 575-748-6940	10. Field and Pool, or Exploratory <u>(97003)</u> Cherry Canyon SWD; Delaware	
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface 2500' FSL & 1400' FEL <u>Unit Letter J</u> (NWSE) Sec 3-T26S-R32E At proposed prod. Zone		11. Sec., T.R.M. or Blk and Survey or Area Sec. 3 - T26S - R32E	
14. Distance in miles and direction from nearest town or post office* Approximately 23 miles from Malaga		12. County or Parish Lea County	13. State NM
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) 1240'	16. No. of acres in lease 1218.62	17. Spacing Unit dedicated to this well N/A	
18. Distance from location* to nearest well, drilling, completed, applied for, on this lease, ft. 2356'	19. Proposed Depth MD: 6,600' TVD: 6,600'	20. BLM/BIA Bond No. on file NMB000740 & NMB000215	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3273' GL	22. Approximate date work will start* 7/1/2013	23. Estimated duration 30 days	

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature <i>M. Sanders</i>	Name (Printed/Typed) <u>Monti Sanders</u> Mayte Reyes	Date 4/5/2013
Title Regulatory Analyst		
Approved by (Signature) <i>/S/ JEANETTE MARTINEZ</i>	Name (Printed/Typed) <i>/S/ JEANETTE MARTINEZ</i>	Date JUN - 5 2013
Title <i>fm</i> FIELD MANAGER	Office CARLSBAD FIELD OFFICE	

Application approval does not warrant or certify that the applicant holds legan or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

SWD-1396

Carlsbad Controlled Water Basin (Continued on page 2)

Approval Subject to General Requirements
& Special Stipulations Attached

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

JUN 12 2013

dm

COG Operating LLC
DRILLING AND OPERATIONS PROGRAM
Pintail 3 Federal SWD 1
SHL: 2500' FSL & 1400' FEL
Section 3 T26S R32E
Lea County, New Mexico

In conjunction with Form 3160-3, Application for Permit to Drill subject well, COG Operating LLC submits the following eleven items of pertinent information in accordance with BLM requirements.

1. Geological surface formation: Permian
2. The estimated tops of geologic markers & estimated depths at which anticipated water, oil or gas formations are expected to be encountered are as follows:

Fresh Water	320'	
Rustler	890'	
Top of Salt	1,261'	
Base of Salt	4,356'	
Delaware	4,571'	
Bone Spring	8,730'	Oil
TD TVD	6,600'	
TD MD	6,600'	

No other formations are expected to give up oil, gas or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 13-3/8" casing at 915' and circulating cement back to surface. All intervals will be isolated by setting 7" casing to total depth and tying back cement to a minimum of 500' into the 9-5/8" csg.

3. Proposed Casing Program: All casing is new and API approved

Hole Size	Depths	Section	OD Casing	New/Used	Wt	Collar	Grade	Collapse Design Factor	Burst Design Factor	Tension Design Factor
17 1/2"	0' – 915'	Surface	13 3/8"	New	54.5#	STC	J-55	1.125	1.125	1.6
12 1/4"	0' – 3,500'	Intrmd	9 5/8"	New	36#	BTC	J-55	1.125	1.125	1.6
12 1/4"	3500' – 4450'	Intrmd	9 5/8"	New	40#	BTC	J-55	1.125	1.125	1.6
8 3/4"	4450'–6600'	Disposal	7"	New	26#	LTC	J-55	1.125	1.125	1.6

- 522
COX
- While running all casing strings, the pipe will be kept a minimum of 1/3 full at all times to avoid approaching the collapse pressure of casing.

4. Proposed Cement Program

- a. 13-3/8" Surface
- Lead: 375 sx Class C + 4% Gel + 2% CaCl₂
(13.5 ppg / 1.75 cuft/sx)
- Tail: 250 sx Class C + 2% CaCl₂
(14.8 ppg / 1.34 cuft/sx)
- **Calculated w/50% excess on OH volumes
- b. 9 5/8" Intermediate:
- Lead: 875 sx Class C + 4% Gel + 2% CaCl₂
(13.5 ppg / 1.75 cuft/sx)
- Tail: 100 sx Class C + 2% CaCl₂
(14.8 ppg / 1.34 cuft/sx)
- **Calculated w/35% excess on OH volumes
- c. 7" Disposal:
- Lead: 300 sx 50:50:10 H
(11.9 ppg / 2.51 cuft/sx)
- Tail: 275 sx Super H
(13 ppg / 1.69 cuft/sx)
- **Calculated w/35% excess on OH volumes

- The above cement volumes could be revised pending the caliper measurement.
- The 9-5/8" intermediate string is designed to circulate to surface.
- The 7" string will tie back a minimum of 500' into the 9-5/8" csq.

a. **Control:**

Nipple up on 13 3/8 with annular preventer tested to 50% of rated working pressure by independent tester and the rest of the 2M system tested to 2000 psi. *see COA*

Nipple up on 9 5/8 with 3M system tested to 3000 psi by independent tester.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and a minimum 3" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 3000 psi WP rating. A remotely operated choke will be installed before drilling out intermediate shoe.

6. Estimated BHP & BHT:

TD = 3020 psi

TD= 124°F

7. Mud Program: The applicable depths and properties of this system are as follows:

Depth	Type System	Mud Weight	Viscosity (sec)	Waterloss (cc)
0' – 915'	Fresh Water	8.4	29	N.C.
915' – 4,450'	Brine	10	29	N.C.
4,450' – 6,600'	Cut Brine	8.8 – 9.2	29	N.C.

- The necessary mud products for weight addition and fluid loss control will be on location at all times.
- A visual and electronic mud monitoring system will be rigged up prior to spud to detect changes in the volume of mud system. The electronic system consists of a pit volume total, stroke counter and flow sensor at flow line.
- If weight and/or viscosity are introduced to the mud system a daily mud check will be performed by mud contractor, along with tourly check by rig personnel.
- After setting intermediate casing, a third party gas unit detection system will be installed at the flow line.

8. Auxiliary Well Control and Monitoring Equipment:

- a. A Kelly cock will be in the drill string at all times.
- b. A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor at all times.
- c. Hydrogen Sulfide detection equipment will be in operation after drilling out the 13 3/8" casing shoe until the retrievable bridge plug is set into the 9-5/8" casing. Breathing equipment will be on location upon drilling the 13 3/8" shoe until total depth is reached.

9. Testing, Logging and Coring Program:

- a. Drill stem tests will be based on geological sample shows.
- b. If open hole electrical logging is performed, the program will be:
 - i. Total Depth to Intermediate Casing: Dual Laterolog-Micro Laterolog and Gamma Ray. Compensated Neutron – Z Density log with Gamma Ray and Caliper.
 - ii. Total Depth to Surface: Compensated Neutron with Gamma Ray
 - iii. No coring program is planned
 - iv. No additional testing is planned in the drilling phase.
 - v. The Delaware Sand disposal interval will be swab tested after the completion to ensure that there are no commercial hydrocarbon shows within the injection interval. There are no plans to fracture treat the injection interval.


10. Potential Hazards:

- a. No abnormal pressures or temperatures are expected. There is no known presence of H₂S in this area. If H₂S is encountered the operator will comply with the provisions of Onshore Oil and Gas Order No. 6. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. No H₂S is anticipated to be encountered.


11. Anticipated starting date and Duration of Operations:

- a. Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as soon as possible after BLM approval and as soon as a rig will be available. Move in operations and drilling is expected to take 30 days.


2,000 psi BOP Schematic




3,000 psi BOP Schematic



2M Choke Manifold Equipment



3M Choke Manifold Equipment



Design Plan
Operating and Maintenance Plan
Closure Plan
Pintail 3 Federal SWD 1
SHL: 2500' FSL & 1400' FEL
Section 3 T26S R32E
Lea County, New Mexico

COG Operating LLC will be using all above ground steel pits for fluid and cuttings while drilling. If any tank develops a leak we will have immediate visual discovery, we would then transfer the fluid to another tank then remove any contaminated soil and dispose of it in the cuttings bins for transportation. All leaks should be kept to less than 5 barrels. Rig crews will monitor the tanks at all times.

Equipment List:

- 2- Mongoose Shale Shakers
- 1- 414 Centrifuge
- 1- 518 Centrifuge
- 2- Roll Off Bins w/ Tracks
- 2- 500 BBL Frac Tanks

During drilling operations all liquids, drilling fluids and cuttings will be hauled off via CRI (Controlled Recovery Inc.) Permit R-9166 or any other approved facility.