(August 2007)	UNITED STA		OCD Hobbs	FORM APPROVED OMB No. 1004-0137
Form 3160-5 (August 2007))	DEPARTMENT OF TH			Expires: July 31, 2010 5. Lease Serial No.
, 2013 - ···	BUREAU OF LAND MA			NMLC032581A
BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELL Do not use this form for proposals to drill or to re-ent SUNDRY NOTICES AND REPORTS ON WELL AUG Do not use this form for proposals to drill or to re-ent SUNDRY NOTICES AND REPORTS ON WELL Do not use this form 3160-3 (APD) for such prop		enter an	6. If Indian, Allottee or Tribe Name	
	T IN TRIPLICATE - Other i		<u> </u>	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well				NMNM71070
Oil Well Gas Well	Other /			8. Well Name and No.
2. Name of Operator	. /			Sholes A-19 #1 9. API Well No.
Primal Energy Corpor 3a. Address		one No. (include area cod	(e)	30-025-11658
21021Springbrook, Spring,TX 77379 281-821-5600				10. Field and Pool, or Exploratory Area
	., T., R., M., or Survey Description)			Jalmat (Tan-Yates-7Rvrs)
L, Sec. 19, T-25-S, R-3	7-E ∮			11. County or Parish, State
2310 FSL & 330 FWL	V ADDRODDIATE DOVOCA	TO INIDIO A TELEVISION	TIME OF NOTICE	Lea Co. NM
TYPE OF SUBMISSIC	K APPROPRIATE BOX(ES)	IO INDICATE NA	·	
I ILE OL PORMISSIO		٦,	TYPE OF ACTION	
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Start/Res	
		New Construction	Recomplete	☐ Well Integrity ☐ Other
Subsequent Report		Plug and Abandon	Temporarily Abando	
Final Abandonment Notice		Plug Back	Water Disposal	
13. Describe Proposed or Comp	oleted Operation (clearly state all per	rtinent details, including	estimated starting date of	f any proposed work and approximate duration there true vertical depths of all pertinent markers and zor
05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'.	ng equipment. 05/09/13 lbit. rigged up swival. Wasbipe. Washed down to 2212/05/14/13 RIH and pumped Re-spot 65 sx cement @ Circulated well w/ mud lad	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat M len fluid. POH w	ig out cellar, NU B down to 2089' to th t of 2 3/8 fish. RIH LCM and 2 % CA AcKelveyw/ BLM). / tbg. Perf'd csg @	bg fish in hole. POH. 05/13/13 RIH w. w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/. Pull out of cement. WOC. 05/15/13/1405'. RIH and set packer @ 904'.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat Mo	dy for final inspection.) Ing equipment. 05/09/13 Ing equipment. 05/09/13 Ing equipment. 05/09/13 Ing equipment. 05/09/13 Ing equipment Ing eq	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat M len fluid. POH w en ended and spo 542'. Set packer (@ 592-492, (per cred up on casing f wellhead. Verifi	ag out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA AcKelveyw/ BLM). It the Perf'd csg @ tted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled ted cement at surfa	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat Mo	dy for final inspection.) Ing equipment. 05/09/13 Ibit. rigged up swival. Washoipe. Washed down to 2212 Ibit. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope It 1126'. Perf'd csg @ @ 5 It and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off	POH w/ rods. Du hed and worked 2'. POH w/ 3 foot 65 sx cement w/ 2086' (per Pat M len fluid. POH w en ended and spo 542'. Set packer of @ 592-492, (per ared up on casing f wellhead. Verifien. cleaned locati	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA AcKelveyw/ BLM). I tbg. Perf'd csg @ tted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled ed cement at surfaton and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat Mo	dy for final inspection.) Ing equipment. 05/09/13 bit. rigged up swival. Washinger. Washed down to 2212 05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 50 and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadments.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat M len fluid. POH w en ended and spo 542'. Set packer a © 592-492, (per ared up on casing f wellhead. Verifi en. cleaned locati	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/13/1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. It packer. Spotted 25 sx cement @ 124/140ce. Welded on Above Ground Dry ed as to plugging of the well bore. Ity under bond is retained until
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat Mo	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washoipe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut offed cellar. Removed deadment.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat M len fluid. POH w en ended and spo 542'. Set packer a © 592-492, (per ared up on casing f wellhead. Verifi en. cleaned locati	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat McHole Marker. Backfilled)	dy for final inspection.) Ing equipment. 05/09/13 bit. rigged up swival. Washinger. Washed down to 2212 15/14/13 RIH and pumped of the compact of the com	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat M len fluid. POH w en ended and spo 542'. Set packer a © 592-492, (per ared up on casing f wellhead. Verifi en. cleaned locati	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/13/1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. It packer. Spotted 25 sx cement @ 124/140ce. Welded on Above Ground Dry ed as to plugging of the well bore. Ity under bond is retained until
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat McHole Marker. Backfilled)	dy for final inspection.) Ing equipment. 05/09/13 bit. rigged up swival. Washinger. Washed down to 2212 05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 50 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH wen ended and spot 542'. Set packer @ 592-492, (per red up on casing wellhead. Verifien. cleaned location of the control	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat McHole Marker. Backfilled)	dy for final inspection.) Ing equipment. 05/09/13 bit. rigged up swival. Washinger. Washed down to 2212 15/14/13 RIH and pumped of the compact of the com	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat M len fluid. POH w en ended and spo 542'. Set packer a © 592-492, (per ared up on casing f wellhead. Verifi en. cleaned locati	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ender POH. Perf'd csg @ 63' to surface, (per Pat McHole Marker. Backfilled)	dy for final inspection.) Ing equipment. 05/09/13 bit. rigged up swival. Washinger. Washed down to 2212 05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 50 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH wen ended and spot 542'. Set packer @ 592-492, (per red up on casing wellhead. Verifien. cleaned location of the control	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washoipe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men ended and spot 542'. Set packer @ 592-492, (per red up on casing wellhead. Verifien. cleaned location of the control	ig out cellar, NU B down to 2089' to the tof 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). If the Perf'd csg @ otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled led cement at surfation and moved off.	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/13/1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124/16ce. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washoipe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men ended and spot 542'. Set packer @ 592-492, (per red up on casing wellhead. Verifien. cleaned location of the control	down to 2089' to the of 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). It to 1500 psi. Pulled bed cement at surfation and moved off. Acceptation of the control of the c	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until exception is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and washp Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille 14. I hereby certify that the foregon Name (Printed/Typed) Signature Approved by Conditions of approval, if any, are the applicant holds legal or equitable	dy for final inspection.) Ing equipment. 05/09/13 bit. rigged up swival. Washire. Washed down to 2212 05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 50 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment of the cellar correct.) THIS SPACE FOR THIS	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH wen ended and spot 542'. Set packer @ 592-492, (per gred up on casing wellhead. Verifien. cleaned location. Cleaned location of warrant or certify that of warrant or certify that	down to 2089' to the of 2 3/8 fish. RIH LCM and 2 % CA McKelveyw/ BLM). I tbg. Perf'd csg @ Otted 25 sx cement of 247'. Pressured Pat McKalvey w/ To 1500 psi. Pulled of cement at surfation and moved off. Acceptation in Acceptatio	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/13/1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124/16ce. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille 14. I hereby certify that the foregon Name (Printed/Typed) Signature Approved by Conditions of approval, if any, are the applicant holds legal or equitab applicant to conduct operations the	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washolpe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment of the company of this notice does not be title to those rights in the subject least reon.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH we nended and spot 542'. Set packer (@ 592-492, (per ared up on casing wellhead. Verifien. cleaned location. Cleaned location of warrant or certify that the which would entitle the	down to 2089' to the of 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). It tog. Perf'd csg @ Otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled ed cement at surfation and moved off. Acceptation in the company of the compan	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/13 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille 14. I hereby certify that the forego Name (Printed/Typed) Signature Approved by Conditions of approval, if any, are the applicant holds legal or equitab applicant to conduct operations the Title 18 U.S.C. Section 1001 and T States any false, fictitious or fraudy	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washolpe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment of the company of this notice does not be title to those rights in the subject least reon.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH we nended and spot 542'. Set packer (@ 592-492, (per ared up on casing wellhead. Verifien. cleaned location. Cleaned location of warrant or certify that the which would entitle the	down to 2089' to the of 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). It tog. Perf'd csg @ Otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled ed cement at surfation and moved off. Acceptation in the company of the compan	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until exception is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille 14. I hereby certify that the foregon Name (Printed/Typed) Signature Approved by Conditions of approval, if any, are the applicant holds legal or equitab applicant to conduct operations the	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washolpe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment of the company of this notice does not be title to those rights in the subject least reon.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH we nended and spot 542'. Set packer (@ 592-492, (per ared up on casing wellhead. Verifien. cleaned location. Cleaned location of warrant or certify that the which would entitle the	down to 2089' to the of 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). It tog. Perf'd csg @ Otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled ed cement at surfation and moved off. Acceptation in the company of the compan	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.
determined that the site is rea 05/08/13 MIRU pluggi 05/10/13 RIH w/ 4 3/4 fishing tools and wash Pulled off fish. POH. (BLM). WOC. NO TAC Tagged plug @ 1527'. (Pressured up on casing 05/16/13 Tagged plug packer. RIH open ende POH. Perf'd csg @ 63' to surface, (per Pat Mc Hole Marker. Backfille 14. I hereby certify that the forego Name (Printed/Typed) Signature Approved by Conditions of approval, if any, are the applicant holds legal or equitab applicant to conduct operations the Title 18 U.S.C. Section 1001 and T States any false, fictitious or fraudy	dy for final inspection.) ng equipment. 05/09/13 bit. rigged up swival. Washolpe. Washed down to 2212/05/14/13 RIH and pumped G. Re-spot 65 sx cement @ Circulated well w/ mud ladd. POH w/ packer. RIH ope @ 1126'. Perf'd csg @ @ 5 d and spotted 25 sx cment. Set packer @ 10'. Pressu Kalvey). 05/17/13 Cut off d cellar. Removed deadment of the company of this notice does not be title to those rights in the subject least reon.	POH w/ rods. Du hed and worked 2'. POH w/ 3 food 65 sx cement w/ 2086' (per Pat Men fluid. POH we nended and spot 542'. Set packer (@ 592-492, (per ared up on casing wellhead. Verifien. cleaned location. Cleaned location of warrant or certify that the which would entitle the	down to 2089' to the of 2 3/8 fish. RIH LCM and 2 % CA Ackelveyw/ BLM). It tog. Perf'd csg @ Otted 25 sx cement @ 247'. Pressured Pat McKalvey w/ to 1500 psi. Pulled ed cement at surfation and moved off. Acceptation in the company of the compan	OP. POH w/ tbg. bg fish in hole. POH. 05/13/13 RIH w w/ fishing tools and jars to 2220'. ACL @ 2081'. (Ok'd by Jim Amos w/ Pull out of cement. WOC. 05/15/12 1405'. RIH and set packer @ 904'. @ 1463-1350, (Per Jim Amos). up on casing to 1700 psi. POH w' BLM). WOC. Tagged plug @ 373'. I packer. Spotted 25 sx cement @ 124 ace. Welded on Above Ground Dry ed as to plugging of the well bore. by under bond is retained until c restoration is completed.