

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
HOBBS OCD
OIL CONSERVATION DIVISION
220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
June 19, 2008

WELL API NO. 30-025-40110
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-1510
7. Lease Name or Unit Agreement Name Camel State
8. Well Number 1
9. OGRID Number 013837
10. Pool Name or Wildcat Wildcat; Bone Springs

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Mack Energy Corporation	
3. Address of Operator P.O. Box 960 Artesia, NM 88210	
4. Well Location Unit Letter <u>P</u> <u>330</u> feet from the <u>South</u> line and <u>330</u> feet from the <u>East</u> line Section <u>10</u> Township <u>19S</u> Range <u>36E</u> NMPM County <u>Lea</u>	
11. Elevation (Show whether DR, RKB, RT, GR etc.) 3757' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIALWORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Notify OCD 24 hours prior to starting plugging operations.

CIBP's @ 7770', 7595', 7400', 5300' w/35' cement caps.

- 1) Set 25sx plug from 2870-2970'. Covering base of salt. WOC and tag.
- 2) Set 25sx plug from 1575-1675'. Covering top of salt and surface shoe. WOC and tag.
- 3) Circulate cement from 60' to surface. 100'
- 4) Clean location and install P & A marker.

Note: Circ. well with salt gel mud consisting of at least 9.5# Brine with 25 pounds of gel per barrel after the bottom plug is set.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Sherrell

TITLE Production Clerk

DATE 10/24/13

Type or print name Jerry W. Sherrell

E-mail address: jerrys@mec.com

PHONE: (575)748-1288

For State Use Only

APPROVED BY: [Signature]

TITLE Dist. MGR

DATE 10-28-2013

Conditions of Approval (if any):

OCT 29 2013

RM

Mack Energy Corporation
Camel State #1 30-025-40110

Before

After



8 5/8 @ 1620' cmt
w/810sx, circ 141sx

CIBP @ 5300' w/35' cmt cap
Perfs @ 5376-5396'


CIBP @ 7400' s/35' cmt cap

CIBP @ 7595' w/35' cmt cap
Perfs @ 7607-7693'

CIBP @ 7770' w/ 35' cmt cap
Perfs @ 7795-7898'

5 1/2 @ 9016' cmt
w/2075sx, circ 466sx

TD @ 9020'



100' to surface
8 5/8 @ 1620' cmt
w/810sx, circ 141sx

✓
CIBP @ 5300' w/35' cmt cap
Perfs @ 5376-5396'

CIBP @ 7400' s/35' cmt cap

CIBP @ 7595' w/35' cmt cap
Perfs @ 7607-7693'

CIBP @ 7770' w/ 35' cmt cap
Perfs @ 7795-7898'

5 1/2 @ 9016' cmt
w/2075sx, circ 466sx

TD @ 9020'