Form 3160-5 (March 2012)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2014 5. Lease Serial No.			
SU	NDRY NOTICES	AND REPORTS ON W	/ELLS	NMNM17432		
Do not use this form t abandoned well. Use F		or proposals to drill or to re-enter an orm 3160-3 (APD) for such proposeded		6. If Indian, Allottee or Tribe Name		
		ner instructions on page 2	HORP2 COD	7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well		SEP 2 2 2014		8. Well Name and No.		
Oil Well Gas Well	Other	~	- · · · · · · · · · · · · · · · · · · ·	9. API Well No.		
Legacy Reserves Operating LP 3a. Address PO Box 10848, Midland, TX 79702 4. Location of Well (Footage, Sec., T., R., M., or Survey Descript		3b. Phone No. (include area cod	de) RECEIVED	30-005-21097 10. Field and Pool, or Exploratory Area Chaves; Queen Gas Area SE 11. County or Parish, State		
		432-689-5200				
Sec 29, T-13-S, R-31-E 198			ng -103.8419172			
	PROPRIATE BOX	(ES) TO INDICATE NA		E, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	l		TYPE OF ACTIO			
Notice of Intent	Acidize		Production (Start/			
	Alter Casing	Fracture Treat	Reclamantion	Well Integrity		
Subsequent Report	Change Plans	Plug and Abandon	Temporarily Aba			
Final Abandonment Notice	Convert to Injectio		Water Disposal			
99/09/14 ND wellhead, NU luid. Spotted 20 sx cement 19/10/14 Tagged plug @ 22 ement w/2 % CACL @ 1'	w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o	acker and POH w/ tbg 2600-2230. POH w/ g to 1770'. Pressure te	tbg to 1300'. We sted casing and l	ed to 2600'. Circualted hole w/ mud laden OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL		
99/09/14 ND wellhead, NU luid. Spotted 20 sx cement 99/10/14 Tagged plug @ 22 cement ŵ/ 2 % CACL @ 1' @ 1160-790. POH w/ tbg t 99/11/14 Tagged plug @ 78 surface. Moved off. 99/16/14 Moved in backho Backfilled cellar. Removed Installed Closed-Loop Syst	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan	acker and POH w/ tbg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC ag out cellar. Cut off v ed location and move	tbg to 1300'. We sted casing and 1 'agged plug @ 13 'L @ 410 to surfa vellhead. Welded d off.	OC. held 500 psi for 30 minutes. Spotted 25 sx		
99/09/14 ND wellhead, NU luid. Spotted 20 sx cement 99/10/14 Tagged plug @ 22 ement w/ 2 % CACL @ 1' @ 1160-790. POH w/ tbg t 99/11/14 Tagged plug @ 75 surface. Moved off. 99/16/14 Moved in backho Backfilled cellar. Removed (nstalled Closed-Loop Syst ocation according to Rule	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan 19.15.17.	acker and POH w/ tbg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC g out cellar. Cut off v ed location and move ks. Hauled contents f	tbg to 1300'. We sted casing and h 'agged plug @ 13 L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u>	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal		
9/09/14 ND wellhead, NU luid. Spotted 20 sx cement 9/10/14 Tagged plug @ 22 cement w/ 2 % CACL @ 1' @ 1160-790. POH w/ tbg t 09/11/14 Tagged plug @ 78 surface. Moved off. 09/16/14 Moved in backho Backfilled cellar. Removed Installed Closed-Loop Syst location according to Rule	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan 19.15.17.	acker and POH w/ thg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC g out cellar. Cut off v ed location and move ks. Hauled contents f Printed/Typed)	tbg to 1300'. We sted casing and h 'agged plug @ 13 L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> orms require <u>B</u>	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal <u>BLM APPROVAL.</u>		
9/09/14 ND wellhead, NU luid. Spotted 20 sx cement 9/10/14 Tagged plug @ 22 ement w/ 2 % CACL @ 1' @ 1160-790. POH w/ tbg t 9/11/14 Tagged plug @ 78 Surface. Moved off. 9/16/14 Moved in backho Backfilled cellar. Removed Installed Closed-Loop Syst ocation according to Rule	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan 19.15.17.	acker and POH w/ tbg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC ag out cellar. Cut off v ed location and move ks. Hauled contents ks. Hauled contents f Printed/Typed) Title	tbg to 1300'. We sted casing and h 'agged plug @ 13 L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> prms require <u>B</u>	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal		
9/09/14 ND wellhead, NU luid. Spotted 20 sx cement 9/10/14 Tagged plug @ 22 ement w/ 2 % CACL @ 17 @ 1160-790. POH w/ tbg t 09/11/14 Tagged plug @ 78 fourface. Moved off. 09/16/14 Moved in backho Backfilled cellar. Removed installed Closed-Loop Syst ocation according to Rule	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40's e and welder. Du deadmen. Clean em with steel tan 19.15.17.	acker and POH w/ thg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC g out cellar. Cut off v ed location and move ks. Hauled contents f Printed/Typed)	tbg to 1300'. We sted casing and h 'agged plug @ 13 'L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> prms require <u>B</u> <u>PRODUCTIO</u> 09/17/2014	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal <u>BLM APPROVAL.</u> N SUPERINTENDENT		
 9/09/14 ND wellhead, NU luid. Spotted 20 sx cement 9/10/14 Tagged plug @ 22 cement w/ 2 % CACL @ 1' @ 1160-790. POH w/ tbg tr 09/11/14 Tagged plug @ 75 courface. Moved off. 09/16/14 Moved in backho Backfilled cellar. Removed (installed Closed-Loop Syst ocation according to Rule 4. Thereby certify that the foregoing is FREDDIE GIBBS Signature Additional	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40's e and welder. Du deadmen. Clean em with steel tan 19.15.17.	acker and POH w/ thg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC g out cellar. Cut off v ed location and move ks. Hauled contents ks. Hauled contents for <i>Printed/Typed</i> Title	tbg to 1300'. We sted casing and h 'agged plug @ 13 'L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> prms require <u>B</u> <u>PRODUCTIO</u> 09/17/2014	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal <u>BLM APPROVAL.</u> N SUPERINTENDENT		
 99/09/14 ND wellhead, NU huid. Spotted 20 sx cement 99/10/14 Tagged plug @ 22 cement w/ 2 % CACL @ 1' @ 1160-790. POH w/ tbg tr 99/11/14 Tagged plug @ 75 courface. Moved off. 99/16/14 Moved in backho Backfilled cellar. Removed (installed Closed-Loop Syst ocation according to Rule 4. I hereby certify that the foregoing is FREDDIE GIBBS Signature Additional Statement of the systement of	BOP. Release pa w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan 19.15.17. true and correct. Name (<u>bu</u> <u>M</u> <u>u</u> THIS SPA(acker and POH w/ thg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC ag out cellar. Cut off v ed location and move iks. Hauled contents f ks. Hauled contents f C Printed/Typed) Title Date CE FOR FEDERAL C	tbg to 1300'. We sted casing and h 'agged plug @ 13 'L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> production 09/17/2014 OR STATE OFF	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal <u>BLM APPROVAL.</u> N SUPERINTENDENT		
 99/09/14 ND wellhead, NU 1uid. Spotted 20 sx cement 19/10/14 Tagged plug @ 22 22 23 24 25 26 27 27 27 28 29 29 20 29 20 20 21 20 20 21 21 21 22 24 25 26 27 27 28 29 29 29 20 29 29 20 20 21 21 22 23 24 24 25 26 27 27 28 29 29 29 20 20 21 21 22 23 24 24 25 26 27 26 27 27 28 29 29 29 20 21 26 27 27 28 29 29 29 20 20 21 21 22 26 27 27 28 29 29 29 20 20 21 21 21 21 22 22 23 24 24 24 25 26 27 27 27 28 29 29 29 20 20 21 21 21 21 22 22 23 24 25 26 27 27 27 28 29 29 20 20 21 21 21 22 23 24 24 25 26 27 27 27 28 29 29 20 21 	BOP. Release pr w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan 19.15.17. true and correct. Name (bu M J THIS SPAC	acker and POH w/ thg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC ag out cellar. Cut off v ed location and move iks. Hauled contents ks. Hauled contents for <i>Printed/Typed</i> Title Date CE FOR FEDERAL O re does not warrant or certify subject lease which would	tbg to 1300'. We sted casing and h 'agged plug @ 13 'L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> production 09/17/2014 DR STATE OFF	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal <u>BLM APPROVAL.</u> N SUPERINTENDENT		
 99/09/14 ND wellhead, NU 10/14 Tagged plug @ 22 cement w/2 % CACL @ 1' @ 1160-790. POH w/ tbg t 09/11/14 Tagged plug @ 78 surface. Moved off. 09/16/14 Moved in backho Backfilled cellar. Removed Installed Closed-Loop Syst location according to Rule 14. Thereby certify that the foregoing is FREDDIE GIBBS Signature Advance Approved by Conditions of approval, if any, are attach hat the applicant holds legal or equitable mille the applicant to conduct operation	BOP. Release pr w 2 % CACL @ 253'. POH w/ tb 770-1400. Pull o o 410. ND BOP. 87'. Spotted 40 s e and welder. Du deadmen. Clean em with steel tan 19.15.17. true and correct. Name (bu M M THIS SPA(acker and POH w/ thg 2600-2230. POH w/ g to 1770'. Pressure te ut of cement. WOC. T x cement w/ 2% CAC g out cellar. Cut off v ed location and move ks. Hauled contents f ks. Hauled contents f <i>C</i> <i>Printed/Typed</i> <i>Title</i> <i>Date</i> CE FOR FEDERAL O <i>ate</i> it a crime for any person known in the formation of the second se	tbg to 1300'. We sted casing and h 'agged plug @ 13 'L @ 410 to surfa vellhead. Welded d off. from Closed-Loo OCD Condition Accepted for <u>R</u> DCD CONDITION ACCEPTED FOR <u>CONTECTION</u> 09/17/2014 DR STATE OFF	OC. held 500 psi for 30 minutes. Spotted 25 sx 360'. Spotted 25 sx cement w/ 2% CACL ace. rigged down, verified cement at I on "Below Ground Dry Hole Marker". op System to approved NMOCD disposal s of Approval <u>ECORD ONLY.</u> All Federal <u>BLM APPROVAL.</u> N SUPERINTENDENT		

-

cepted	for	Rec	ord	Onl	Ver	
	5/0	CD	91	ZZ	120	4