Submit I Copy To Appropriate District OBBS OCD State of New Mexico	Form C-103
Office Program Control Energy Minerals and Natural Resources	Revised July 18, 2013_
1625 N. French Dr., Hobbs, NM 88 9CT 08 2014 District II - (575) 748-1283	WELL API NO. 30-025-07290
811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 8741 RECEIVED 1220 South St. Francis Dr.	STATE FEE X
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	6. State Oil & Gas Lease No.
87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Rose Eaves
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	8. Well Number 1
2. Name of Operator	9. OGRID Number
State of New Mexico formerly Platunum Exploration, Inc.	10. Paul mana a Wildow
3. Address of Operator	10. Pool name or Wildcat Knowles Devonian
1625 N. French Drive Hobbs, NM 88240	Knowles Bevonlan
Unit Letter N : 660 feet from the South line and 1980 feet from the West line	
Section 35 Township 16S Range 38E	NMPM County Lea
11. Elevation (Show whether DR, RKB, RT, GR, etc.	
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
<u></u>	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WOR TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DR	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	
DOWNHOLE COMMINGLE	
CLOSED-LOOP SYSTEM	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion.	
1. MIRU. GIH w/ guage ring to 12,200'. GIH w/ CIBP. Set at 12,200'. Cap w/ 25 sx Class H cmt	
2. POOH to 9250'. Spot 25 sx Class H cmt.	
3. Perf at 6300'. Sqz w/ 50 sx. WOC and tag.	
4. Perf at 4855'. Sqz w/70 sx. WOC and tag. (Int shoe)	
5. Perf at 2100'. Sqz w/ 50 sx. WOC and tag. (Top of salt)	
6. Perf at 330'. Sqz w/ 50 sx. WOC and tag. (Surface shoe)	
7. Perf at 100'. Circ cmt to surface.	
8. Cut wellhead off 4' below ground level. Install dry hole marker.	
Spud Date: Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
SIGNATURE Malbtilde TITLE Compliance Officer DATE 10/8/2014	
Type or print name Mark Whitaker E-mail address:	PHONE: 575-393-6161
For State Use Only	
APPROVED BY: Makey Shown TITLE Dest. Supervision DATE 10/8/2014	
APPROVED BY: 1 Conditions of Approval (if any):	DATE TO SOLUTION

Rose Eaves No. 1 **PROPOSED RE-ENTRY** 660' FSL & 1980' FWL DF: 3712' KB: Sec 35, T-16S, R-38E Lea County, NM API #: 30-025-07290 Well Type: Plugged (1/70) 19 ¹/₂" Hole 16" 63.5&65# H&J @ 280' w/ 350 sx 10 3/4" Csg Patch @ 400' TOC @ 2,770' by TS 13 ³/₄" Hole 10 $^{3}/_{4}$ " 45.5 & 51# J&N @ 4,805' w/ 1,550 sx 7 ⁵/₈" Csg Patch @ 4,992' 8 ³/₄" Hole TOC @ 9,250' by TS Perfs 12,418'- 50'(10/67) Perfs 12,354'- 403'(12/67) Perf 12,504'- 18' (11/49) Perf 12,532'- 50' & 12,550'- 73' 7 $^{5}/_{8}"$ 29.7&33.7# J&N @ 12,574' w/ 800 sx

TD: 12,575' PBTD: 12,574'