Form 3160-5 (March 2012)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Hob	bs _
HOBBS	OCI

FORM APPROVED OMB No. 1004-0137

Expires: October 31, 2014

SUNDRY NOTICES AND REPORTS ON WELLS $~\eta0V$

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals

5. Lease Serial No. 1 20 4 M NM 112939 6. If Indian, Allottee or Tribe Name

abandoned well.	Use Form 3160-3 (A	(PD) for such proposa	RECEIVE	3	
SUBMI	T IN TRIPLICATE - Other	r instructions on page 2.	W. C. L.	7. If Unit of CA/Agre	ement, Name and/or No.
1. Type of Well		·			
Oil Well Gas V	Well Other		8. Well Name and No Bevo 11 Federal No		
2. Name of Operator Adventure Exploration Partners II LLC				9. API Well No. 30-025-41804	
3a. Address		3b. Phone No. (include area co	ode)	10. Field and Pool or	Exploratory Area
500 W. Texas Avenue, Suite 1000 Midland, TX 79701		432-684-8006		(28432) Grama Ridge; Bone Spring W.	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) At surface: 700 FSL 8890 FEL, Sec. 11, 7225, R33E				11. County or Parish, State	
At surface: 700' FSL &890' FEL, Sec. 11, T22S, R33E At proposed prod. zone: 330' FNL & 660' FEL, Sec. 11, T22S, R33E			Lea County, NM		
. 12. CHEC	CK THE APPROPRIATE BO	OX(ES) TO INDICATE NATUR	RE OF NOTIC	E, REPORT OR OTH	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Acidize	Deepen Deepen	Produ	ction (Start/Resume)	Water Shut-Off
White of Interior	Alter Casing	Fracture Treat	Reclas	mation	Well Integrity
Cubarana Parana	Casing Repair	New Construction	Recon	nolete	Other Change to original
Subsequent Report	Change Plans	Plug and Abandon	Temp	orarily Abandon	APD
Final Abandonment Notice	Convert to Injection	Plug Back		Disposal	
13. Describe Proposed or Completed Op the proposal is to deepen directions Attach the Bond under which the w following completion of the involv- testing has been completed. Final a determined that the site is ready for	ally or recomplete horizontally ork will be performed or produced operations. If the operation that the operation of the oper	ly, give subsurface locations and ovide the Bond No. on file with I on results in a multiple completion	I measured and BLM/BIA. Re on or recomple	I true vertical depths o equired subsequent rep etion in a new interval	of all pertinent markers and zones. Forts must be filed within 30 days To Form 3160-4 must be filed once
Adventure Exploiration Partners II re	spectfully requests appro-	val to run DV/ECP tool in the	9-5/8" casing	due to lost circulation	on potential.
DV/ECP tool in 9-5/8" casing at +/- 4	.000'				
		•			

Plan Volumes:

Stage 1: 150 sx lead, 365 sx tail Stage 2: 1050 sx lead, 140 sx tail

Lead Cements: 65:35 C Poz @12.9 ppg, 1.87 yield Tail Cements: Class C @ 14.8 ppg, 1.33 yield

SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct. Name (Primed/Typed) David Wantuck	Title Project Manager	
Signature 6	Date 10/28/2014	
THIS SPACE FOR FEDER	RAL OR STATE OFFICE USE	APPROVED
Approved by	Title	Date 007 0 0 2014
Conditions of approval, if any, are attached. Approval of this notice does not warrant or ce that the applicant holds legal or equitable title to those rights in the subject lease which wo entitle the applicant to conduct operations thereon.	rtify office	Isl Chris Walls
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any per fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	son knowingly and willfully to make to any depar	CARLSBAD FIELD OFFICE

(Instructions on page 2)

Conditions of Approval

Operator has proposed DV tool at a depth of 4000'. Operator is to submit sundry if DV tool depth varies by more than 100' from approved depth.

1. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

a.	First stage to DV tool:
\boxtimes	Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.
b.	Second stage above DV tool:

□ Cement to surface. If cement does not circulate, contact the appropriate BLM office.
 Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to potash.