Submit I Copy To Appropriate Distr Office	State of Ivev		Form C-103
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 882	Energy, Minerals and	Natural Resources	Revised July 18, 2013 WELL API NO. 30-025-41614
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVAT		5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 874	1220 South St.		STATE STEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NN	Santa Fe, NI		6. State Oil & Gas Lease No.
87505		HOBBS OCD	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR DUFFE : 2014			7. Lease Name or Unit Agreement Name PICKARD STATE
PROPOSALS.) 1. Type of Well: Oil Well		JLI -	8. Well Number 002H
2. Name of Operator MATADOR PRODUCT		RECEIVED	9. OGRID Number 228937
3. Address of Operator 5400 LBJ FREEWA	AY, STE 1500, DALLAS	, TX 75240	10. Pool name or Wildcat E-K; WOLFCAMP
4. Well Location			
Unit Letter O Section 20	: 702 feet from the SO		L776 feet from the EAST line
Section 20	Township 185	Range 34E	NMPM County LEA
	405	3 ' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A			
PULL OR ALTER CASING	☐ MULTIPLE COMPL ☐	CASING/CEMEN	IT JOB
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM			
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
Sidetrack - co	ming off of pilot ho	le:	
03/11/14 - Drill pilot hole to 12,546';set open hole whipstock @ 11,100'			
with stinger below @ 12,515'. Pumped 154 bbls of cement from			
	515' - 11,100'. Coul	-	
03/16/14 - Set cement plug from 9,000' - 5,790' inside open hole.			
03/21/14 - Set cased hole whipstock @ 5,500'. Mill window out of intermedia			
casing @ 5,500' and continued drilling to next casing point to			
	next string of casi		3 1
			
Spud Date: 01/27/20	14 Rig Relea	ase Date: 05/0	09/2014
I hereby certify that the inform	nation above is true and complete to	the best of my knowled	ge and belief.
SIGNATURE Cloan	TITLE !	Sr. Engineerin	ng Tech DATE 9/15/14
Type or print name Ava Mo	onroe E-maila	amonroe@ ddressm <u>atadorres</u>	ources.comPHONE: 972-371-5218
For State Use Only	52//-	••	1-1-/10
APPROVED BY: TITLE Petroleum Engineer DATE 12/24/19			