

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-42363
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Encore M State
8. Well Number 015
9. OGRID Number 370080
10. Pool name or Wildcat Blinbry Gas & Oil (Oil), Drinkard, Wantz;Abo
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3375 GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	
2. Name of Operator Breitburn Operating, LP	
3. Address of Operator 600 Travis Houston, Texas 77002-3026	
4. Well Location Unit Letter: J 2004 feet from the South line and 1975 feet from the East line Section 20 Township 22S Range 37E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3375 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/12/2015: Drilled surface 17 1/2" hole to 1314'.

03/13/2015: RU casing crew and run 31 jts. of 13 3/8", 54.5# J-55 casing to 1308'. Pump cement as follows: Lead cement 223 bbls (710 sx) 13.50 ppg, 1.76 yield, 8.98 gal/sk. Tail cement, 82 bbls (345 sx) 14.80, 1.33 yields, 6.32 gal/sk. 96 bbls displacement brine water. Bumped plug w/500 psi over floats held and 1 bbl back. Full returns were maintained through job and 130 bbls of cement to surface.

03/14/2015: N/U BOP, PSI test and find that BOP needs repair. Repair BOP.

03/15/2015: Test all BOP equipment 250 psi/2100 psi and hold 5 minutes. Test choke 250 psi/2100 psi and hold 5 minutes. Test casing to 1900 psi and hold for 30 minutes. All tests pass.


Spud Date: 03/11/2015 Rig Release Date:

Recomp ☐ Add New Well ☐
Cancel Well ☐ Create Pool ☐

I hereby certify that the information above is true and complete to the best of my knowledge and
SIGNATURE: Electronically Signed TITLE: Regulatory Manager DATE: 03/18/2015
E-PERMITTING -- New Well ☐
Comp ☐ P&A ☐ TA ☐
CSNG MB Loc Chng ☐
ReComp ☐ Add New Well ☐

Type or print name: Jeanie McMillan E-mail address: jeaniemcmillan@breitburn.com PHONE: 713-634-4696

For State Use Only

APPROVED BY:  TITLE: Petroleum Engineer DATE: 03/18/15
Conditions of Approval (if any):

MAR 20 2015