Form 3160-5	LINITE	D STATES		FORM APPROVED
(March 2012)		OF THE INTERIOR		OMB No. 1004-0137 Expires: October 31, 2014
	BUREAU OF LAND MANAGEMENT			5. Lease Serial No.
	SUNDRY NOTICES A	CES AND REPORTS ON WELLS		NMLC030132B
	not use this form for pro adoned well. Use Form 3		ch proposals.	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on pa			12.1.1	INIVILCUSUI32B
1. Type of Well Gas Well Other			NOV 09	2013 Well Name and No. Closson B Federal #3
2. Name of Operator Breitburn Operating LP 3a. Address 3b. Phone No. (include)				30-025-08962
1401 McKinney, Ste 24	400,HoustonTX77010 7		ode) RECE	10. Field and Pool, or Exploratory Area     S Eunice     11. County or Parish, State
<ol> <li>Location of Well (Footage, Sec., T., R., M., or Survey Description)</li> <li>D-20-22S-36E, 660 FNL, 330 FWL 32.382689 -103.29474</li> </ol>			Lea County NM	
12. CHE0	CK APPROPRIATE BOX(E	ES) TO INDICATE NA		CE REPORT. OR OTHER DATA
TYPE OF SUBMISSIO	ON		TYP E-F	ERMITTING <swdinje< td=""></swdinje<>
	Acidize	Deepen		NVERSION RBDMS
Notice of Intent	Alter Casing	Fracture Treat		TURN TO TA
Subsequent Report	Casing Repair	New Construction	CSI	NGENVIROCHGLC
Final Abandonment Notice	Change Plans	Plug and Abandon		TO PA P&A NR P&A F
	Convert to Injection	Plug Back	Water Dispose	
determined that the site is re- 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Press Tagged plug @ 2930'. 1510-1377'. WOC. 08	ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( casingbelow 900' 1304'. Perf'd casing	requirements, includ ig @ 3483'. Cin ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd (	ing reclamantion, have been completed, and the open rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on
determined that the site is re- 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Press Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ yed off. 09/02/15 Moved	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( casingbelow 900' 1304'. Perf'd casing d in welder and bac	requirements, includ ig @ 3483'. Cin ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( ckhoe. Dug out	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface.
determined that the site is re- 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Press Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ yed off. 09/02/15 Moved	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( casingbelow 900' 1304'. Perf'd casing d in welder and bac	requirements, includ ig @ 3483'. Cin ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( ckhoe. Dug out	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on
determined that the site is re- 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Press Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off.
determined that the site is re- 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Press Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @) ved off. 09/02/15 Moved Hole Marker". Backfille	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac d cellar. Removed	requirements, includ ig @ 3483'. Cin ssure tested cas 08/29/15 Spotte to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off.
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Pressu Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry H	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out a deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off.
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Pressu Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry H	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac d cellar. Removed	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out a deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off.
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Pressu Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry H	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out a deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473- casing @ 3201'. Pressu Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry F	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out a deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BURE/U OF LAND MANAGEMEN
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473-: casing @ 3201'. Press Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry H Z - 2	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @) ved off. 09/02/15 Moved Hole Marker". Backfille Acc Lia Sur	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed	requirements, includ ig @ 3483'. Cit ssure tested cas 08/29/15 Spotte to 500 psi. Helo g @ 60'. Sqz'd ( khoe. Dug out deadmen. Clea g of the well hor retained until outploted.	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BURE /U OF LAND MANAGEMEN CARLSBAD FIELD OFFICE
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473-: casing @ 3201'. Presso Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry I Z - 2 14. Thereby certify that the fores Jeanie McMillan	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @) ved off. 09/02/15 Moved Hole Marker". Backfille Act Lia Sur	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( I casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed cepted as to plage bility under bond is the restoration is can need/Typed)	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g @ 60'. Sqz'd ( ckhoe. Dug out a deadmen. Clea g @ 60'. sqz'd ( choe. Dug out a deadmen. Clea g @ 60'. sqz'd ( choe. Dug out a deadmen. Clea	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BURE /U OF LAND MANAGEMEN CARLSBAD FIELD OFFICE
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473-: casing @ 3201'. Presso Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry I Z - 2 14. Thereby certify that the foreg Jeanie McMillan	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille Action 4 - 16 Sur going is true and correct. Name (Prin	tbg and tagged plu plug @ 3251'. Pre ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g@ 60'. Sqz'd 0 khoe. Dug out a deadmen. Clea g@ 6' the well bor retained until ompleted. Regulatory M a 09/03/15	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BURE/U OF LAND MANAGEMEN CARLSBAD FIELD OFFICE
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473-: casing @ 3201'. Presso Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry I Z - 2 14. Thereby certify that the fores Jeanie McMillan	d. Final Abandonment Notices sh ady for final inspection. ging equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @ ved off. 09/02/15 Moved Hole Marker". Backfille Action 4 - 16 Sur going is true and correct. Name (Prin	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( I casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed cepted as to plage bility under bond is the restoration is can need/Typed)	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g@ 60'. Sqz'd 0 khoe. Dug out a deadmen. Clea g@ 6' the well bor retained until ompleted. Regulatory M a 09/03/15	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BURE/U OF LAND MANAGEMEN CARLSBAD FIELD OFFICE
determined that the site is re 08/27/15 MIRU plugg 30 sx cement @ 3473-: casing @ 3201'. Presso Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry F Z - 2 14. I hereby certify that the foreg Jeanie McMillan Signature Approved by Conditions of approval, if any, are that the applicant holds legal or ex- time of the second second second second second second Conditions of approval, if any, are that the applicant holds legal or ex- time of the second sec	d. Final Abandonment Notices sh ady for final inspection. Fing equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @) wed off. 09/02/15 Moved Hole Marker". Backfille Action Hole Marker Backfille Marker Backfille Marker Backfille THIS SPACE	tbg and tagged plu plug @ 3251'. Pre- ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac d cellar. Removed cepted as to plage's bility under bond is flace restoration is can need/Typed) Title Date FOR FEDERAL	requirements, includ ig @ 3483'. Cir ssure tested cas 08/29/15 Spotter to 500 psi. Helo g@ 60'. Sqz'd 0 khoe. Dug out a deadmen. Clea g@ 6' the well bor retained until ompleted. Regulatory M a 09/03/15	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC d. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BURE/U OF LAND MANAGEMEN CARLSBAD FIELD OFFICE
determined that the site is re- 08/27/15 MIRU plugg 30 sx cement @ 3473-: casing @ 3201'. Presso Tagged plug @ 2930'. 1510-1377'. WOC. 08 Rigged down and mov "Above Ground Dry H "Above G	d. Final Abandonment Notices sh ady for final inspection. Fing equipment. RIH w/ 3177. 08/28/15 Tagged ured up on perfs and we (Per Jim Amos). Tested 8/31/15 Tagged plug @) wed off. 09/02/15 Moved Hole Marker". Backfille Action Hole Marker". Backfille Marker Sur Child Sur this SPACE	tbg and tagged plu plug @ 3251'. Pres ell communicated. ( l casingbelow 900' 1304'. Perf'd casing d in welder and bac ed cellar. Removed cepted as to plage's bility under bond is face restoration is cont inted/Typed) Title Date <b>FOR FEDERAL</b>	requirements, includ ig @ 3483'. Cit ssure tested cas 08/29/15 Spotte to 500 psi. Helo g @ 60'. Sqz'd @ ckhoe. Dug out deadmen. Clea Contine well bor retained until omplored. Regulatory M a 09/03/15 OR STATE OF Title	rculated hole w/ mud laden fluid. Spot ing to 500 psi. Did not hold pressure. P d 25 sx cement @ 3251-3000'. WOC 1. Perf'd csg @ 1510'. Sqz'd 55 sx ceme 50 sx cement and circulated to surface. cellar. Cut off well head. Welded on ned location and moved off. ACCEPTED FOR RECO NOV 6 2015 BUREAU OF LAND MANAGEMEN CARLSBAD FIELD OFFICE Manager FICE USE

١		
1	N	r
y	II	ſ