
LINITED STATES

OCD Hobbs

FORM APPROVED

| | TMENT OF THE IN | | | MB NO. 1004-0135 pires: July 31, 2010 | |
|--|--|---|--|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS OCD | | | 5. Lease Serial 1 | 5. Lease Serial No. NMNM19623 | |
| Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. | | | | ottee or Tribe Name | |
| | () | MOV 9 0 20 | the state of the s | | |
| SUBMIT IN TRIPLICATE - Other instructions on reverse side. | | | 7. If Unit or CA NMNM104 | /Agreement, Name and/or No. 037X | |
| 1. Type of Well | RECEIVED | 8. Well Name an RED HILLS | d No. NORTH UNIT 302 | | |
| ■ Oil Well | Contact: 5 | STAN WAGNER | 9. API Well No. | | |
| EOG RESOURCES INCORPORAT | er@eogresources.com | 30-025-321 | | | |
| 3a. Address | | | b. Phone No. (include area code) 10. Field and Pool, or Explore th: 432-686-3689 11. Field and Pool, or Explore | | |
| MIDLAND, TX 79702 | | 111. 402-000-0005 | THE THE CO | | |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description, | | 11. County of | | arish, and State | |
| Sec 13 T25S R33E NWNE 660FNL 32.135954 N Lat, 103.523904 W Lc | | C | E-PERMITTING SWEN | ITY, NM | |
| 12. CHECK APPROPR | RIATE BOX(ES) TO | INDICATE NA' CS | ONVERSION SWID | TER DATA | |
| TYPE OF SUBMISSION | | INT | VG TO PA ENVIRO | D. M. | |
| | | | PA ENVIRO | RBDMS TIONS | |
| ☐ Notice of Intent | Acidize | ☐ Deepen | - Pen | TA OMS CTIONS | |
| Cubecquent Deport | Alter Casing | ☐ Fracture Treat | Reclan. | CHG LOC P&AR | |
| | Casing Repair | ■ New Construction | Recomplete | P&ACOC | |
| _ | Change Plans | Plug and Abandon | ☐ Temporarily Abandon | N PM | |
| | Convert to Injection | □ Plug Back | ☐ Water Disposal | | |
| following completion of the involved operat testing has been completed. Final Abandom determined that the site is ready for final ins 09/24/15 MIRU to P&A. 09/25/15 POOH w/ 2-7/8" IPC inject 09/26/15 RIH and spot 25' cement to 9325'. 09/27/15 Spot 35 sx Class H ceme plugging mud. Spot 60 sx Class C co 09/29/15 RIH and tag cement at 46 5-1/2" casing. Run freepoint. Detection 5-1/2" casing. Run freepoint. Detection 10/01/15 RIH and tag cement at 25 1575'. WOC 4 hrs. RIH and tag cement at 25 1575'. WOC 4 hrs. RIH and tag cement at 25 1575'. | ment Notices shall be file spection.) ction tubing and 5-1/2 on CIBP at 11600'. It is present plug from 9360' to be ment plug from 523 658'. Witnessed by Brmined casing free at ement plug at 2750'. | 2" RBP. RIH w/ CIBP and s Displace w/ 10# plugging m 9160'. Pull up hole to 523 32' to 4985'. Pull up hole to 6LM. POOH. Rig up casing 1 2700'. Cut casing at 2700 | set at 11600'. set at 11600'. sud. Pull up hole 2'. Load hole w/ 3000'. jacks and pull on '. POOH w/ Accepted as to cement plug at jability under | plugging of the well bore bond is retained until | |
| 14. I hereby certify that the foregoing is true as | nd correct. | | | serve and American | |
| Elec | tronic Submission #3 | 18891 verified by the BLM W | ell Information System | LLANTALIUN | |
| | | essing by LINDA JIMENEZ of | on 10/21/2015 (15LJ1640SE) | 4-2-16 | |
| Name(Printed/Typed) STAN WAGNE | R | Title REGL | JLATORY ANALYST | | |
| - A STATE OF THE S | | | 100 | | |
| Signature (Electronic Submis | | | /2015 | nen e | |
| | THIS SPACE FO | R FEDERAL OR STATE | preice pset it lu | טאנ | |
| Approved By | | Title | | Date | |
| Conditions of approval, if any, are attached. App | | NOV 21 9 2015 | | | |
| certify that the applicant holds legal or equitable which would entitle the applicant to conduct oper | title to those rights in the | subject lease Office | A Proper | | |
| Title 18 U.S.C. Section 1001 and Title 43 U.S.C. States any false, fictitious or fraudulent statement | Section 1212, make it a cents or representations as t | rime for any person knowingly a to any matter within is jurisdiction | of willfully to make to any department AU OF LAND MANAGEME | ent or agency of the United | |



DEC 0 2 2015

Additional data for EC transaction #318891 that would not fit on the form

32. Additional remarks, continued

Pull up hole to 700'. Spot 50 sx Class C cement plug at 700'. 10/02/15 RIH and tag cement at 520'. Pull up hole to 316'. Spot 90 sx Class C cement plug from 316' to surface. Witnessed by BLM. Cut off wellhead and weld on ground level P&A marker. Well P&A.