1625 N. French Dr., Hobbs, NM 8 District II – (575) 748-1283		WELL API NO. 30-025-20134	
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIV	5. Indicate Type of Lease	-
District III - (505) 334-6178	1220 South St. Francis I	Or. STATE FEE	
1000 Rio Brazos Rd., Aztec, NM 8 District IV – (505) 476-3460	Santa Fe, NM 87505	6. State Oil & Gas Lease No.	_
1220 S. St. Francis Dr., Santa Fe, N	NM .	06361	
87505 SUNDRY	NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name	-
(DO NOT USE THIS FORM FOR DIFFERENT RESERVOIR. USE	PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BAC "APPLICATION FOR PERMIT" (FORM C-101) FOR SUC	CK TO AND	
PROPOSALS.)  1. Type of Well: Oil Well	Gas Well Other	8. Well Number	_
2. Name of Operator	/ nc	8. Well Number  9. OGRID Number	
OX	Y USA Inc.	. 10070	
3. Address of Operator	D. 50050 M.H. 1 TV 50510	RECEIVED 10. Pool name or Wildcat  Mascalero San Andres	
	Box 50250 Midland, TX 79710	Mescalero San Andres	
4. Well Location	100-11		
Unit Letter		line and 1650 feet from the west line	
Section 14		32E NMPM County Lea /	
	11. Elevation (Show whether DR, RKB, 4336)	, RT, GR, etc.)	
	1750		-
12 C	neck Appropriate Box to Indicate Nature	of Notice Report or Other Data	
		E-PERMITTING <swd injection=""></swd>	
NOTICE (	OF INTENTION TO:	CONVERSION RBDMS	
PERFORM REMEDIAL WO		RETURN TO TA	
TEMPORARILY ABANDON	CHANGE PLANS CC	CSNG ENVIRO CHG LOC	
PULL OR ALTER CASING DOWNHOLE COMMINGLE	☐ MULTIPLE COMPL ☐ CA	INT TO PA P&A NR P&A R	
CLOSED-LOOP SYSTEM	H	TOTAL TOTAL	
OTHER:	ОТН	IER:	
<ol><li>Describe proposed o</li></ol>	r completed operations. (Clearly state all pertine	ent details, and give pertinent dates, including estimated date	e
of starting any propo	sed work). SEE RULE 19.15. NMAC. For	Multiple Completions: Attach wellbore diagram of	
	sed work). SEE RULE 19.15. NMAC. For a or recompletion.	Multiple Completions: Attach wellbore diagram of	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For	Multiple Completions: Attach wellbore diagram of	
of starting any propo	osed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'		
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.	DC-Surf-Circ	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole	DC-Surf-Circ e, TOC-2475'-Calc	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to	DC-Surf-Circ e, TOC-2475'-Calc	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag	DC-Surf-Circ e, TOC-2475'-Calc	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-	DC-Surf-Circ e, TOC-2475'-Calc 3840'	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-	DC-Surf-Circ e, TOC-2475'-Calc 3840'	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface	DC-Surf-Circ e, TOC-2475'-Calc 3840'	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-	DC-Surf-Circ e, TOC-2475'-Calc 13840' -Tag -Tag	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs	DC-Surf-Circ e, TOC-2475'-Calc 13840' -Tag -Tag	
of starting any propo	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs	DC-Surf-Circ e, TOC-2475'-Calc 13840' -Tag -Tag	
of starting any propo- proposed completion	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized.	DC-Surf-Circ e, TOC-2475'-Calc 13840' -Tag -Tag	
of starting any propo- proposed completion	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized.  Rig Release Date:	DC-Surf-Circ e, TOC-2475'-Calc 93840' -Tag -Tag	
of starting any propo- proposed completion	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized.	DC-Surf-Circ e, TOC-2475'-Calc 93840' -Tag -Tag	
of starting any propo- proposed completion	sed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized.  Rig Release Date:	DC-Surf-Circ e, TOC-2475'-Calc 93840' -Tag -Tag	
of starting any propo- proposed completion  Spud Date:	seed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized Rig Release Date:	DC-Surf-Circ e, TOC-2475'-Calc a 3840' -Tag -Tag dd my knowledge and belief.	
of starting any propo- proposed completion	seed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TC 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag 3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized Rig Release Date:	DC-Surf-Circ e, TOC-2475'-Calc 93840' -Tag -Tag	
of starting any proportion proposed completion  Spud Date:  I hereby certify that the information of the starting any proposed completion of the starting and starting any proposed completion of the starting and starting any proposed completion of the starting and sta	seed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TO 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag  3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs  Above ground steel tanks will be utilized.  Rig Release Date:  TITLE Sr. Regul	DC-Surf-Circ e, TOC-2475'-Calc a 3840' -Tag -Tag dd my knowledge and belief.	
of starting any propo- proposed completion  Spud Date:  I hereby certify that the inform  SIGNATURE  Type or print name  David	seed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TO 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag  3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs  Above ground steel tanks will be utilized.  Rig Release Date:  TITLE Sr. Regul	DC-Surf-Circ e, TOC-2475'-Calc 3840' -Tag -Tag -Tag d my knowledge and belief.  latory Advisor DATE \(\infty\) \(\infty\) \(\infty\)	The state of the s
of starting any proportion proposed completion  Spud Date:  I hereby certify that the information of the starting any proposed completion of the starting and starting any proposed completion of the starting and starting any proposed completion of the starting and sta	seed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TO 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag  3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs  Above ground steel tanks will be utilized.  Rig Release Date:  TITLE Sr. Regulation and complete to the best of reserved and complete to the co	DC-Surf-Circ e, TOC-2475'-Calc  3840' -Tag -Tag -Tag  dd  my knowledge and belief.  latory Advisor DATE \( \subseteq \beta \) avid_stewart@oxy.com PHONE: 432-685-5717	The same of the sa
of starting any propo- proposed completion  Spud Date:  I hereby certify that the inform  SIGNATURE  Type or print name  David	seed work). SEE RULE 19.15. NMAC. For a or recompletion.  TD-4500' PBTD-4465' Perfs-4140-4380'  8-5/8" 24# csg @ 370' w/ 350sx, 11" hole, TO 5-1/2" 14# csg @ 4496' w/ 350sx, 7-7/8" hole  1. RIH & set CIBP @ 4090', M&P 25sx cmt to 2. M&P 25sx cmt @ 3450-3200' WOC-Tag  3. Perf @ 2250', sqz 45sx cmt to 2125' WOC-4. Perf @ 1625', sqz 45sx cmt to 1500' WOC-5. Perf @ 420' sqz 140sx cmt to surface 10# MLF between plugs  Above ground steel tanks will be utilized.  Rig Release Date:  TITLE Sr. Regulation and complete to the best of reserved and complete to the co	DC-Surf-Circ e, TOC-2475'-Calc 3840' -Tag -Tag -Tag d my knowledge and belief.  latory Advisor DATE \(\infty\) \(\infty\) \(\infty\)	

DFC 1 5 2015

Ile

OXY USA Inc. - Proposed State BN #1 API No. 30-025-20134

140sx @ 420'-Surface

11" hole @ 370' 8-5/8" csg @ 370' w/ 350sx-TOC-Surf-Circ

Perf @ 420'

Perf @ 1625'


Perf @ 2250'

45sx @ 1625-1500' WOC-Tag

45sx @ 2250-2125' WOC-Tag

25sx @ 3450-3200' WOC-Tag

CIBP @ 4090' w/ 25sx to 3840'



Perfs @ 4140-4380'

7-7/8" hole @ 4500' 4-1/2" csg @ 4496' w/ 350sx-TOC-2475'-Calc

PB-4465'

OXY USA Inc. - Current State BN #1 API No. 30-025-20134

PB-4465'

