

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-39840	✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	✓
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Crossroads 22 State	✓
8. Well Number 3H	✓
9. OGRID Number 14187	✓
10. Pool name or Wildcat Flying M; Abo	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4359' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Marshall & Winston, Inc. ✓

3. Address of Operator
P. O. Box 50880, Midland, Texas 79710-0880

4. Well Location
Unit Letter C : 400 feet from the North line and 1980 feet from the West line
Section 22 Township 9S Range 33E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	INT TO PA <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OF <input type="checkbox"/>	P&A NR <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	P&A R <input type="checkbox"/>
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Marshall & Winston, Inc. respectfully request permission to plug and abandon the Crossroads 22 State #3H.
(see attached proposed plug and abandon procedure)

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING
PLUGGING OPERATIONS

LPC AREA

Spud Date:

07/27/10

Rig Release Date:

10/17/10

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Todd Passmore TITLE Operations Manager DATE 03/16/16

Type or print name Todd Passmore E-mail address: tpassmore@mar-win.com PHONE: 432-684-6373

For State Use Only

APPROVED BY: Mark Whitaker TITLE Petroleum Engr. Specialist DATE 03/22/2016

Conditions of Approval (if any):

MAR 22 2016

CROSSROADS 22 STATE #3H
LEA COUNTY, NEW MEXICO
API #30-025-39840

INTENT TO PLUG AND ABANDON
SUNDRY DATED 03/16/16 ATTACHMENT

Proposed Plug and Abandon Procedure:

1. Notify NMOCD of plugging operations.
2. Move in rig up pulling unit & nipple up blow out preventer.
3. Confirm top of fish depth.
4. Run in hole w/ cast iron bridge plug, set 10' above fish.
5. Tag cast iron bridge plug w/ tubing, confirm depth.
6. Pump 25 sx of cement on plug.
7. Displace w/ 9.0 ppg salt gel based mud.
8. Pump cement plug from 4150' up to 3950' (Notify NMOCD).
9. Displace w/ 9.0 ppg salt gel based mud.
10. Wait on cement.
11. Tag cement w/ NMOCD official on location.
12. Pump cement from 2200' – 1800'.
13. Displace w/ 9.0 ppg salt gel based mud.
14. Pump cement from 460' – 340' (Notify NMOCD).
15. Displace w/ 9.0 ppg salt gel based mud.
16. Wait on cement.
17. Tag cement w/ NMOCD official on location.
18. Displace w/ 9.0 ppg salt gel based mud.
19. Pump cement from 60' – surface.
20. Cut off wellhead 3' below surface.
21. Cap well with ½" steel plate.
22. Well marker on plate, no more than 4' above ground w/ well name, operator, legal location and plug & abandon date.
23. Reclaim location.

Pressure test csg to 500psi
Spot 25sx @ 4650' WOC-Tag

Shoe plug

← spot 25sx @ 2550' (B.S.)

Inj. interval
in offset
wells

