

**UNORTHODOX  
LOCATION**

OCD Hobbs

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**HOBBS OCD**

**APPLICATION FOR PERMIT TO DRILL OR REENTER** 18 2016

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		7. If Unit or CA Agreement, Name and No. [316103]	
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		8. Lease Name and Well No. Squints Federal Com #2H	
2. Name of Operator COG Operating LLC. [229137]		9. API Well No. 30-025 43163	
3a. Address 2208 West Main Street Artesia, NM 88210		3b. Phone No. (include area code) 575-748-6940	
10. Field and Pool, or Exploratory OJO Chiso; Bone Spring (96553)		11. Sec., T.R.M. or Blk and Survey or Area Sec. 27 - T22S - R34E	
12. County or Parish Lea County		13. State NM	
14. Distance in miles and direction from nearest town or post office* About 17 miles from Eunice		15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) 190'	
16. No. of acres in lease NMNM043565: 640 NMNM043564: 1,920		17. Spacing Unit dedicated to this well 160	
18. Distance from location* to nearest well, drilling, completed, SHL: 30' (Prop. Squints #6H) applied for, on this lease, ft. BHL: 4509'		19. Proposed Depth TVD: 11,240' MD: 15,796'	
20. BLM/BIA Bond No. on file NMB000740 & NMB000215		21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3407.5' GL	
22. Approximate date work will start* 10/1/2015		23. Estimated duration 30 days	

**24. Attachments**

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature <i>Mayte Reyes</i>	Name (Printed/Typed) Mayte Reyes	Date 7-20-15
----------------------------------	----------------------------------	--------------

Regulatory Analyst

Approved by (Signature) <i>/s/ STEPHEN J. CAFFEY</i>	Name (Printed/Typed)	Date APR 13 2016
Title FOR FIELD MANAGER	Office BLM-CARLSBAD FIELD OFFICE	

Application approval does not warrant conduct operations thereon.  
Conditions of approval, if any, are at Title 18 U.S.C. Section 1001 and Title States any false, fictitious or fraudulent

The NMOC Gas Capture Plan notice has been posted on the web site under Announcements/Notice to Operators. A copy of the GCP form is included with the notice and is also in the Forms section under Unnumbered forms. Please submit accordingly in a timely manner.

subject lease which would entitle the applicant to APPROVAL FOR TWO YEARS

make to any department or agency of the United

(Continued on page 2)

Witness Surface & Intermediate Casing (Instructions on page 2)

APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS  
AND SPECIAL STIPULATIONS  
ATTACHED

*Ka*  
*04/18/16*

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

APR 22 2016

# COG Operating LLC, Squints Federal 2H

## 1. Geologic Formations

TVD of target	11240'	Pilot hole depth	NA
MD at TD:	15796'	Deepest expected fresh water:	605'

### Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	1701'	Water	
Top of Salt	1897'	Salt	
Tansill	3637'	Barren	
Yates	3716'	Oil/Gas	
Capitan Reef	4045'	Water	Possible lost circ
Delaware Group	5313'	Oil/Gas	Possible lost circ
Bone Spring	8534'	Oil/Gas	
3 <sup>rd</sup> Bone Spring Sand	10975'	Target Zone	
Wolfcamp	11343'	Oil/Gas	

## 2. Casing Program

See COA

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0'	1840'	13.375"	54.5	J55	STC	1.30	1.03	5.13
12.25"	0'	<del>5500'</del> 5600'	9.625"	40	L80	BTC	1.17	1.08	4.09
8.75"	0'	15796'	5-1/2"	17	P110	LTC	1.41	2.00	1.66D
BLM Minimum Safety Factor							1.125	1.00	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
- BLM standard formulas were used on all SF calculations.
- Used 9.1 PPG for pore pressure calculations
- Will set DV tool within 100' of the top of the Capitan Reef. Estimated setting depth is 3950'.

## COG Operating LLC, Squints Federal 2H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	Y
If yes, does production casing cement tie back a minimum of 50' above the Reef?	Y
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

### 2. Cementing Program

Casing	# Sk	Wt. lb/gal	Yld ft <sup>3</sup> /sack	H <sub>2</sub> O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	790	13.5	1.75	9.2	13	Lead: Class C + 4% Gel + 2% CaCl <sub>2</sub>
	275	14.8	1.34	6.4	6	Tail: Class C + 2% CaCl <sub>2</sub>
Inter. Stg 1	280	12.9	1.92	10.0	12	Lead: Class C Lite (65:35:6) + 4% Salt + 5# Kolseal
	200	14.8	1.34	6.4	6	Tail: Class C
Inter. Stg 2	975	12.9	1.92	10.0	12	Lead: Class C Lite (65:35:6) + 4% Salt + 5# Kolseal
	200	14.8	1.34	6.4	6	Tail: Class C
Prod.	1040	10.3	3.52	21.3	75	Lead: Halliburton Tuned Lite w/ 2# kolseal, 1.5# salt, 1/4# D-Air 5000, 1/8# PEF, etc
	1220	14.4	1.25	5.7	22	Tail: 50:50:2 H blend (FR, Retarder, FL adds as necessary)

Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

## COG Operating LLC, Squints Federal 2H

Casing String	TOC	% Excess
Surface	0'	36%
Intermediate – Stage 1	3950'	51%
Intermediate – Stage 2	0'	124%
Production	0'	39%

Pilot hole depth: NA

KOP: 10763'

### 4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	2M	Annular	x	50% of working pressure
			Blind Ram		2M
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	13-5/8"	5M <del>3M</del>	Annular	x	50% testing pressure
			Blind Ram		5M <del>3M</del>
			Pipe Ram		
			Double Ram	x	
			Other *		

\* Actual equipment is 13-5/8" 5M Hydril Annular, will use for 2M WP System.

\*\* - Actual equipment is 13-5/8" 5M Hydril Annular & 13-5/8" 10M Cameron triple ram, will use for ~~3M~~ WP System.

5M MUST TEST TO 5,000 PSI

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

## COG Operating LLC, Squints Federal 2H

See COA

X	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
	Are anchors required by manufacturer? No.
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. See attached schematic.

### 5. Mud Program

See COA

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. shoe	FW Gel	8.6 – 9.0	28-34	N/C
Surf csg	Int shoe	*Saturated Brine	10.0 - 10.2	28-34	N/C
Int shoe	TMD	Cut Brine	8.6 - 9.4	28-34	N/C

\*If lost circulation is encountered, will switch to fresh water.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Pason PVT
---	-----------

### 6. Logging and Testing Procedures

Logging, Coring and Testing.	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
X Mud log	Production

## COG Operating LLC, Squints Federal 2H

### 7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	5319 psi – 3 <sup>rd</sup> Bone Spring Sand (11240' TVD)
Abnormal Temperature	No

Mitigation measure for abnormal conditions.

- Lost circulation material/sweeps/mud scavengers.
- Maintain stock of LCM and weighting materials onsite.

Hydrogen Sulfide (H<sub>2</sub>S) monitors will be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

N | H<sub>2</sub>S is present

Y | H<sub>2</sub>S Plan attached

### 8. Other facets of operation

Is this a walking operation? Yes. *See COA*

Will be pre-setting casing? No.

Will well be hydraulically fractured? Yes.

#### Attachments

- Directional Plan
- Anticollision Report
- BOP & Choke Schematics
- C102 and supporting maps
- Rig plat
- H<sub>2</sub>S schematic
- H<sub>2</sub>S contingency plan
- Interim reclamation plat