Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources	Revised July 18, 2013
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-025-28981 5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr. Santa Fe, NM 87505	STATE X FEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa FC, ININ 67505	6. State Oil & Gas Lease No. State of New Mexico A-1212-0002
SUNDRY NOT	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A ICATION FOR PERMIT" (FORM C-101) FOR SUCH	South Hobbs Unit (G/SA)
1. Type of Well: Oil Well X	Gas Well Other HOBBS OCD	8. Well Number 186
2. Name of Operator Occidental Permian Ltd.	✓ MAY 0 3 2016	9. OGRID Number 157984
3. Address of Operator		10. Pool name or Wildcat
P.O. Box 4294, Houst	on, TX 77210 RECEIVED	Hobbs (G/SA)
4. Well Location	2420 Get General North Hand	212 Continue Monte line
Unit Letter E	: <u>2420</u> feet from the <u>North</u> line and Township 19S Range 38E	<u>213</u> feet from the <u>West</u> line NMPM County Lea
Section 4	Township 19S Range 38E 11. Elevation (Show whether DR, RKB, RT, GR, etc.) RKB, RT, GR, etc.)	
	3624.4' KB	
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER:	CHANGE PLANS COMMENCE D MULTIPLE COMPL CASING/CEME	ORILLING OPNS. P AND A
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tog and tagged PBTD @ 4310', treating pkr w/ downhole press kylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg	work). SEE RULE 19.15.7.14 NMAC. For Multiple C completion. D wellhead, NUBOP, and rig up workfloor. POOH ssembled and moved off to safe location with fo and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed c and ESP equipment. NDBOP, NU wellhead and t	Completions: Attach wellbore diagram of I w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 g downhole shut valve. Released pkr, POOH w/
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg	work). SEE RULE 19.15.7.14 NMAC. For Multiple C completion. D wellhead, NUBOP, and rig up workfloor. POOH ssembled and moved off to safe location with fo and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed c and ESP equipment. NDBOP, NU wellhead and t	Completions: Attach wellbore diagram of I w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 j downhole shut valve. Released pkr, POOH w/
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64	work). SEE RULE 19.15.7.14 NMAC. For Multiple C completion. D wellhead, NUBOP, and rig up workfloor. POOH ssembled and moved off to safe location with fo and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed c and ESP equipment. NDBOP, NU wellhead and t	Completions: Attach wellbore diagram of I w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 g downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workflo
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg cleaned location and MO location Spud Date: 3/15/2016	work). SEE RULE 19.15.7.14 NMAC. For Multiple C ccompletion. D wellhead, NUBOP, and rig up workfloor. POOH ssembled and moved off to safe location with fo and circulated well w/ 120 bbls FW. POOH w/ 1: sure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed c and ESP equipment. NDBOP, NU wellhead and t ion. Rig Release Date: 3/21/2016	Completions: Attach wellbore diagram of I w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 g downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workflo
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg cleaned location and MO location spud Date: 3/15/2016	vork). SEE RULE 19.15.7.14 NMAC. For Multiple C completion. D wellhead, NUBOP, and rig up workfloor. POOH ssembled and moved off to safe location with fo and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed of and ESP equipment. NDBOP, NU wellhead and to ion.	Completions: Attach wellbore diagram of I w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 g downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workflo
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg cleaned location and MO location Spud Date: 3/15/2016 hereby certify that the information	work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. D wellhead, NUBOP, and rig up workfloor. POOH seembled and moved off to safe location with for and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed complete states and ESP equipment. NDBOP, NU wellhead and the second seco	Completions: Attach wellbore diagram of A w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 g downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workflo
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg cleaned location and MO locati Spud Date: 3/15/2016 hereby certify that the information SIGNATURE <u>June Wit</u>	work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. D wellhead, NUBOP, and rig up workfloor. POOH seembled and moved off to safe location with for and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed complete and ESP equipment. NDBOP, NU wellhead and the ion. Rig Release Date: 3/21/2016 mabove is true and complete to the best of my knowled Mult TITLE Regulatory Specialist	Completions: Attach wellbore diagram of A w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 j 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 g downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workfloc dge and belief. DATE <u>5/2/16</u>
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tbg and tagged PBTD @ 4310', treating pkr w/ downhole press xylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg cleaned location and MO location Spud Date: 3/15/2016 hereby certify that the information SIGNATURE <u>June Wit</u> Sype or print name <u>Sarah Mitchell</u>	work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. D wellhead, NUBOP, and rig up workfloor. POOH seembled and moved off to safe location with for and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed complete and ESP equipment. NDBOP, NU wellhead and the ion. Rig Release Date: 3/21/2016 mabove is true and complete to the best of my knowled Mult TITLE Regulatory Specialist	Completions: Attach wellbore diagram of A w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134, 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workflo
of starting any proposed w proposed completion or re (3/15/16) MIRU, killed well, NI detected on ESP, so it was disa- tog and tagged PBTD @ 4310', treating pkr w/ downhole press kylene mixed with 50 gals EC64 126 jts tbg. RIH w/ 124 jts tbg cleaned location and MO location cleaned location and MO location spud Date: 3/15/2016 hereby certify that the information sIGNATURE <u>June With</u>	work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. D wellhead, NUBOP, and rig up workfloor. POOH seembled and moved off to safe location with for and circulated well w/ 120 bbls FW. POOH w/ 12 sure shut off valve, set pkr @ 4009', and pressure shut off valve, set pkr @ 4009', and pressure 195B, flushed with 26 BBLs 10 # BW, and closed complete and ESP equipment. NDBOP, NU wellhead and the ion. Rig Release Date: 3/21/2016 mabove is true and complete to the best of my knowled Mult TITLE Regulatory Specialist	Completions: Attach wellbore diagram of A w/ 122 jts tbg, ESP equipment, NORM was rklift. RIH w/ 4 3/4" bit, csg scraper, and 134 34 jts tbg, bit, and csg scraper. RIH w/ 5 1/2" e tested to 600 psi, which held. Pumped 500 downhole shut valve. Released pkr, POOH w/ ested tree to 3000 psi, which held, RD workflow dge and belief. DATE $5/2/14$ M@oxy.com PHONE: 713-366-5469