Office LORBS UCD	te of New Mexico	Form C-103 Revised July 18, 2013
District I – (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240  District II – (575) 748-1283 811 S. First St., Artesia, NM 88240  0 8 2016 OIL CONSERVATION DIVISION		WELL API NO.
		30-025-43218
District III – (505) 334-6178 1220 South St. Francis Dr.		5. Indicate Type of Lease
1000 Pio Prozos Pd Aztec NIM 97/10	nta Fe, NM 87505	STATE FEE  6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	, , , , , , , , , , , , , , , , , , , ,	o. State off & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Lomas Rojas 26 State Com
PROPOSALS.)  1. Type of Well: Oil Well Gas Well Other		8. Well Number 705H
2. Name of Operator		9. OGRID Number
EOG Resources, Inc.  3. Address of Operator		7377  10. Pool name or Wildcat
P.O. Box 2267 Midland, TX 79702		*WC-025 G-09 S253336D; Upper Wolfcamp
4. Well Location C 807 North 1 1806 West		
Unit Letter reet from the line and reet from the line		
Section 26 Township 25S Range 33E NMPM County Lea  11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
3341' GR		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A		
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐ CASING/CEMENT JOB ☑		
DOWNHOLE COMMINGLE		
CLOSED-LOOP SYSTEM  OTHER:	OTHER:	П
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or recompletion.		
5/31/16 Spud 14-3/4" hole.	50	
Ran 26 jts 10-3/4", 40.5#, J55 STC casing set at 1154'.  Cement lead w/ 527 sx 50/50 Class C POZ, 13.5 ppg, 1.75 CFS yield;		
tail w/ 288 sx Class C, 14.8 ppg, 1.34 CFS yield.		
Circulated 286 sx cement to surface. WOC 19 hrs.		
6/01/16 Tested casing to 1500 psi for 30 minutes. Test good.  Resumed drilling 9-7/8" hole.		
Resultied diffilling 9-176 Tible.		
		*
Sand Date: 5/21/16	Rig Release Date:	
Spud Date: 5/31/16	Rig Release Date:	
I hereby certify that the information above is true and co	omplete to the best of my knowledge	e and belief.
SIGNATURE Stan W	TITLE Regulatory Analyst	DATE 06/02/2016
Stan Wagner	_ IIILL	432 696 3690
Type or print name  For State Use Only	E-mail address:	PHONE: 432-000-3009
For State Ose Only	Petroleum Engi	neer
APPROVED BY:	TITLE	DATE Oblio16