

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

WELL API NO.  
**30-025-04511**

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:  
**Eunice Monument South Unit**

8. Well Number  
**197**

9. OGRID Number  
**005380**

10. Pool name or Wildcat  
**Eunice Monument; Grayburg-San Andres**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☐ Other **Injection**

2. Name of Operator  
**XTO Energy, Inc.**

3. Address of Operator  
**500 W. Illinois St Ste 100 Midland, TX 79701**

4. Well Location

Unit Letter **F** : **1980'** feet from the **North** line and **1980'** feet from the **West** line

Section **5** Township **21S** Range **36E** NMPM County **Lea**

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☒ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: **csg lk. = run liner** ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

XTO Energy, Inc respectfully requests to perform the following on the referenced well:

1. Isolate csg lk.
2. If unable to isolate csg lk, run 4-1/2" liner to 3675' and cement to surface.
3. Acidize perms & OH w/4000gals 15% HCl.
4. Run good MIT.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE **Stephanie Rabadue** TITLE **Regulatory Analyst** DATE **05/27/2016**

Type or print name **Stephanie Rabadue** E-mail address: **stephanie\_rabadue@xtoenergy.com** PHONE **432-620-6714**

For State Use Only

APPROVED BY **[Signature]** TITLE **Petroleum Engineer** DATE **07/11/16**

Conditions of Approval (if any):