## **UNITED STATES** DEPARTMENT OF THE INTERIOR

OCD Hobbs

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

BUREAU OF LAND MANAGEMENT	00
SUNDRY NOTICES AND REPORTS ON WELLSHOBBS	, UC

Do not use this form for proposals to drill or to re-onte

Lease Serial No. NMNM30398

abandoned well. Use form 3160-3 (APD) for such proposals AUG 0 3 2016				n, Allottee or Tribe Name	
SUBMIT IN TRI	PLICATE - Other instructi		7. If Unit	or CA/Agreement, Name and/or No.	
1. Type of Well  ☑ Oil Well ☐ Gas Well ☐ Other				8. Well Name and No. CAVINESS FEDERAL 06	
Name of Operator Contact: STAN WAGNER EOG RESOURCES INCORPORATEDE-Mail: stan_wagner@eogresources.com				9. API Well No. 30-025-30246-00-S1	
3a. Address MIDLAND, TX 79702		3b. Phone No. (include area code Ph: 432-686-3689		10. Field and Pool, or Exploratory MESCALERO ESCARPE	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  Sec 11 T18S R33E NENW 990FNL 2310FWL				11. County or Parish, and State  LEA COUNTY, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, REPORT, O	R OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
☐ Notice of Intent ☑ Subsequent Report ☐ Final Abandonment Notice	☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Convert to Injection	☐ Deepen ☐ Fracture Treat ☐ New Construction ☑ Plug and Abandon ☐ Plug Back	☐ Production (Start/R☐ Reclamation☐ Recomplete☐ Temporarily Abanc☐ Water Disposal	P&A NRP&A R	

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

MIRU to P&A. RIH and laydown rods and tubing.

RIH w/ 5-1/2" CIBP and set at 8580'. Spot 25 sx Class C cement plug from 8580' to 8327'.

5/25/16

RIH and did not tag cement. Re-spot 25 sx Class H cement plug from 8580' to 8400'. POOH WOC 4 hrs.

RIH and tag plug at 8400'. Spot 25 sx Class C cement plug from 6525' to 6275'.

5/26/16

RIH and tag plug at 6275'. Spot 25 sx Class C cement plug from 5670' to 5417'. Spot 60 sx Class C cement plug from 3149' to 2600'. POOH, WOC 4 hrs.
RIH and tag plug at 2600'. RIH and perforate at 1915'. RIH and set 5-1/2" packer at 1600'.

Establish injection rate. Squeezed 40 sx Class C cement plug.

14. I hereby certify that the foregoing is true and correct Electronic Submission #340822 verified by the BLM Well Information System For EOG RESOURCES INCORPORATED, sent to the Hobbs
Committed to AFMSS for processing by PRISCILLA PEREZ on 06/01/2016 (16PP0033SE)

Name (Printed/Typed) STAN WAGNER Title REGULATORY ANALYST

Signature (Electronic Submission) Date 06/01/2016

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

Title

7-24-

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

MW/OCD 8-3-2016

## Additional data for EC transaction #340822 that would not fit on the form

32 Additional remarks, continued

5/27/16
Released packer, POOH. RIH and tag plug at 1740'. RIH and perforate at 425'. Establish injection rate. Squeezed 120 sx Class C cement to surface. Notified BLM. Cut off wellhead, weld on below ground level P&A marker.