	EPARTMENT OF THE	ES INTERIOR NM	OCD	FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010	
AUG 2 SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.			obbs 5	5. Lease Serial No. NMNM831976. If Indian, Allottee or Tribe Name	
			6		
SUBMIT IN TR	RIPLICATE - Other instru	uctions on reverse side.	. 7	7. If Unit or CA/Agreement, Name and/or No	
1. Type of Well ☑ Oil Well ☐ Gas Well ☐ Other 2. Name of Operator RIDGEWAY ARIZONA OIL CORP Contact: JAMIE HOGU E-Mail: jhogue@enhancedoilres.com			8. Well Name and No. FEDERAL 23 1 JE 9. API Well No. 30-041-10527-00-S1		
Location of Well (Footage, Sec.,	T., R., M., or Survey Description	on)	1	1. County or Parish, and State	
Sec 23 T7S R33E SWSW 66	60FSL 660FWL			ROOSEVELT COUNTY, NM	
12. CHECK APP	PROPRIATE BOX(ES)	TO INDICATE NATURE (OF NOTICE, REP	ORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	☐ Acidize	□ Deepen	□ Production	n (Start INT TO PA	
	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	1 GAT CITAL	
■ Subsequent Report	☐ Casing Repair	■ New Construction	□ Recomple	te P&AR	
☐ Final Abandonment Notice	☐ Change Plans	☑ Plug and Abandon			
	☐ Convert to Injection ☐ Plug Back ☐ Water		☐ Water Dis	posal	
0 11 ' 1 1' 0 1 ' 1		10 1 10 1 1 1 1	1 1		
following completion of the involve testing has been completed. Final A determined that the site is ready for 07/21/16 MIRU plugging equals to 3000'(w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut the 500 psi. Spotted 25 sx cemer 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant support of the shall be a final inspection.) Jipment. Rods Stuck at significant support of the shall be a final	results in a multiple completion or iled only after all requirements, in urface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w. C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi of cement @ 2775' inside the ole w/ mud laden fluid. Pressg @ 2300'. Set packer @ on csg. Leaked off pressure good plug @ 2169'. WOC. Tagged plug @ 29d down and moved off. 0 ged down and moved off. 0	r recompletion in a new cluding reclamation, he followed by CACL and distablished rate of 1. and displaced w/ 1 g. WOC. 07/26/16 ssure tested csg to 2009'. Sqz'd 45 sx es @ 1875'. Set pa 1765'. Perf'd csg 0/17/29/16 Moved in	splaced 5 0.75 6 0 K w/ cement	
following completion of the involve testing has been completed. Final A determined that the site is ready for 07/21/16 MIRU plugging equal hole. 07/26/16 Freepoint tbg to 3000' (w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut tb 500 psi. Spotted 25 sx cemer 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and welder and backhoe. Dug ou	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant from the sanchez w/BLM). Word pumped 75 sx cement 1500 psi. Calculated top of 2450'. Circulated the significant from the sanchez w/BLM? Performent @ 2450-2324'. Performent @ 2450-2324'. Performent @ 2450-2324'. Performent from the sanchez with	results in a multiple completion or iled only after all requirements, in urface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w.C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi for cement @ 2775' inside the ole w/ mud laden fluid. Pressg @ 2300'. Set packer @ on csg. Leaked off pressur ged plug @ 2169'. Perf'd c: 725'. WOC. Tagged plug @ ged down and moved off. Welded on "Underground I welde	recompletion in a new cluding reclamation, he concluding reclamation, he concluding reclamation, he concluding reclamation, he concluding the	splaced 5 0.75 6 0 0 W/ cement acker 0 @	
following completion of the involve testing has been completed. Final A determined that the site is ready for 07/21/16 MIRU plugging equal hole. 07/26/16 Freepoint tbg to 3000' (w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut tb 500 psi. Spotted 25 sx cemer 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and welder and backhoe. Dug ou	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant from the sanchez w/BLM). Word pumped 75 sx cement 1500 psi. Calculated top of 2450'. Circulated the significant from the sanchez w/BLM? Performent @ 2450-2324'. Performent @ 2450-2324'. Performent @ 2450-2324'. Performent from the sanchez with	results in a multiple completion or iled only after all requirements, in urface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w.C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi for cement @ 2775' inside the ole w/ mud laden fluid. Pressg @ 2300'. Set packer @ on csg. Leaked off pressur ged plug @ 2169'. Perf'd c: 725'. WOC. Tagged plug @ ged down and moved off. Welded on "Underground I welde	recompletion in a new cluding reclamation, he concluding reclamation, he concluding reclamation, he concluding reclamation, he concluding the	splaced 5 0.75 6 0 0 W/ cement acker 0 @	
following completion of the involve testing has been completed. Final A determined that the site is ready for 07/21/16 MIRU plugging equal hole. 07/26/16 Freepoint tbg to 3000'(w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut tb 500 psi. Spotted 25 sx cemer 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and welder and backhoe. Dug our	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant shall be a final inspection.) Jipment. Rods Stuck at significant shall be a final inspection.) Jipment. Rods Stuck at significant shall be a final shall be	results in a multiple completion or iled only after all requirements, in urface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w.C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi of cement @ 2775' inside the ole w/ mud laden fluid. Pressg @ 2300'. Set packer @ on csg. Leaked off pressur ged plug @ 2169'. Perf'd c: 725'. WOC. Tagged plug @ ged down and moved off. Welded on "Underground I welded on "Underground I was a work of the state of the s	recompletion in a new cluding reclamation, he concluding reclamation, he concluding reclamation, he concluding reclamation, he concluding the	splaced 5 0.75 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
following completion of the involve testing has been completed. Final A determined that the site is ready for 07/21/16 MIRU plugging equal hole. 07/26/16 Freepoint tbg to 3000' (w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut tb 500 psi. Spotted 25 sx cemer 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and welder and backhoe. Dug our I hereby certify that the foregoing to Name (Printed/Typed) JAMIE Hills.	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant shall be a final inspection.) Jipment. Rods Stuck at significant shall be a final inspection.) Jipment. Rods Stuck at significant shall be a final shall be	results in a multiple completion or iled only after all requirements, in urface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w.C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi for cement @ 2775' inside the ole w/ mud laden fluid. Pressg @ 2300'. Set packer @ on csg. Leaked off pressur ged plug @ 2169'. Perf'd cr725'. WOC. Tagged plug @ ged down and moved off. Welded on "Underground I welded on "Underground I welded on Tunderground I welded	recompletion in a new cluding reclamation, he cluding reclamation, he can be considered with tablished rate of 1, and displaced w/ 1 and displaced w/ 1 and displaced w/ 1 are tested csg to 2009'. Sqz'd 45 sx e. Re-Sqz'd 45 sx eg @ 1875'. Set pa 1765'. Perf'd csg 17/29/16 Moved in Dry Hole Marker". Well Information S t to the Roswell on 08/15/2016 (16M	splaced 5 0.75 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
testing has been completed. Final Adetermined that the site is ready for 07/21/16 MIRU plugging equ hole. 07/26/16 Freepoint tbg to 3000'(w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut the 500 psi. Spotted 25 sx cemer 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and welder and backhoe. Dug out the state of the sta	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant of the shall be a final inspection.) Jipment. Rods Stuck at significant of the shall be a	results in a multiple completion or iled only after all requirements, in urface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w.C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi for cement @ 2775' inside the ole w/ mud laden fluid. Pressg @ 2300'. Set packer @ on csg. Leaked off pressur ged plug @ 2169'. Perf'd cr725'. WOC. Tagged plug @ ged down and moved off. Welded on "Underground I welded on "Underground I welded on Tunderground I welded	recompletion in a new cluding reclamation, he cluding reclamation, he can be called the control of the control of the called the cal	splaced 5 0.75 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
following completion of the involve testing has been completed. Final A determined that the site is ready for 07/21/16 MIRU plugging equ hole. 07/26/16 Freepoint tbg to 3000'(w/approval of Jennif bbl/min @ 400 lbs. Mixed an bbls. Pressure increased to 1 Tagged TOC @ 2452'. Cut tb 500 psi. Spotted 25 sx cemel 2% CACL and displace to 21 @ 2300' and displaced to 21 @ 1632'. Sqz'd 45 sx w/ 2% 60'. Sqz'd 25 sx cement and welder and backhoe. Dug ou out the complete of the complet	Abandonment Notices shall be a final inspection.) Jipment. Rods Stuck at significant of the shall be a final inspection.) Jipment. Rods Stuck at significant of the shall be a	results in a multiple completion or iled only after all requirements, in surface. 07/22/16 to 07/25/11 and Sqz'd 75 sx cement w.C. Pressure tested sqz. Es @ 1.5 bbls/min @ 400 psi of cement @ 2775' inside the ole w/ mud laden fluid. Press @ 2300'. Set packer @ on csg. Leaked off pressur ged plug @ 2169'. Perf'd cr725'. WOC. Tagged plug @ 2169'. Perf'd cr725'. WOC and moved off. Welded on "Underground I welded on "Underground I was a with the set of the set o	recompletion in a new cluding reclamation, he cluding reclamation, he can be called the control of the control of the called the cal	splaced 5 0.75 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **
Approved as to plugging of the

RECLAMATION DUE: JAN 29 2017

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

FOR RECORD ONLY

Additional data for EC transaction #347752 that would not fit on the form

32. Additional remarks, continued

Backfilled cellar. Removed deadmen, cleaned location, and moved off.