Office	State of New Mexico	Form C-103
District I - (575) 393-6161	Energy, Minerals and Natural Res	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283		WELL API NO. 30-025-00960
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVI	SION 50-025-00960 5. Indicate Type of Lease
District III – (505) 334-6178 NUV 0 0 2 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr	STATE X FEE
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, MC EN	VED Santa Fe, NM 87505	6. State Oil & Gas Lease No. E-9062
SUNDRY NOTIC (DO NOT USE THIS FORM FOR PROPOSA	ES AND REPORTS ON WELLS ALS TO DRILL OR TO DEEPEN OR PLUG BACK	
PROPOSALS.)	ATION FOR PERMIT" (FORM C-101) FOR SUCH	8. Well Number
	Gas Well Other	1
2. Name of Operator CHEVRON USA INC		9. OGRID Number 4323
3. Address of Operator 6301 DEAUVILLE BLVD. RM #N3	3002, MIDLAND TX. 79706	10. Pool name or Wildcat SALT LAKE, MARROW, SO.
	- LAT 32.53855 X-LONG -103.712	
	feet from the SOUTH line at	
Section 25	Township 20-S Range 32-	
Environment of the State of the	11. Elevation (Show whether DR, RKB, H	
素的数据 与 机关节 经金属	3,634' GL	
12. Check Ap	opropriate Box to Indicate Nature of	of Notice, Report or Other Data
NOTICE OF INT		SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK		DIAL WORK ALTERING CASING
TEMPORARILY ABANDON	P&A NR ROOM	MENCE DRILLING OPNS. PANDA
PULL OR ALTER CASING	P&A R CASIN	IG/CEMENT JOB
DOWNHOLE COMMINGLE		
CLOSED-LOOP SYSTEM OTHER:	OTHE	R: RE-PLUG /
	OTHE	t details, and give pertinent dates, including estimated date
		Aultiple Completions: Attach wellbore diagram of
proposed completion or recor		
10/10-23/16 MI &RU, NDWH & NU	BOP, TEST, RIH DRILL OUT CEMENT	FROM SURFACE TO 2,709' NOTIFIED MARK
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO	DE.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830'	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @	DE.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/60 SX CL "C" CMT FR	DE. 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500'
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/60 SX CL "C" CMT FR @ 2,100' SQZ W/4 BBLS RAW RESIN	OE. () 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/28/16 RIH TAG @ 1/28/16 RIH	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/	OE. () 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ 10/29/16 RIH TAG @ 1/29/16 RIH T	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87	OE. () 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'.	OE. () 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830° RIH W/ PKR & SET @ 2,325° INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430°, PERF @ 10/28/16 RIH TAG @ 1,964°, PERF @ 10/29/16 RIH TAG @ 1,327°, PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972°, TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'.	OE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS IT 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR 2,100' SQZ W/ 4 BBLS RAW RESIN W/ 1,450', SQZ 4 BBLS RAW RESIN W/ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX	OE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C"	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,200', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX "CMT FROM 198'-100'.	DE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. '2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS IT 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/101/16 RIH TAG @ 90', PERF @ 8	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX "CMT FROM 198'-100'. 5' NO SQZ, PERF @ 75', CIR UP 13 5/8	OE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS IT 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" 11/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX 10 SQZ, PERF @ 198', RIH TO 420' MIX 10 SQZ, PERF @ 75', CIR UP 13 5/8 10 SQZ, PERF @ 75', CIR UP 13 5/8	DE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. '2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS IT 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 S" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C"
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIRE	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX 10 SQZ, PERF @ 198', RIH TO 420' MIX 10 SQZ, PERF @ 75', CIR UP 13 5/8 10 C" UP 13 5/8" TO SURFACE ON BOTH ELD ON DRY HOLE MARKER, TO ME ED DISPOSAL, CLEAN LOCATION	DE. 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS T 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 S" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIRE ALL CEMENT PLUGS CLASS" C	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN, TEST CSG TO 1,500# GOOD, PERF (ATE 1BBL (A) 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR (A) 2,100' SQZ W/ 4 BBLS RAW RESIN W/ (B) 1,450', SQZ 4 BBLS RAW RESIN W/ (B) 1,200', UNABLE TO CIR. PERF (A) 87' FROM 1,100'-1,000'. BOOM GOOD. PERF (B) 570', MIX & SPO' OF FROM 570'-470'. BOOM SQZ, PERF (B) 198', RIH TO 420' MIX (B) SQZ, PERF (B) 198', CIR UP 13 5/8' C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME CED DISPOSAL, CLEAN LOCATION (C", W/ CLOSED LOOP SYSTEM US)	OE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. '2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS IT 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 S" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIRE	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHO , TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,450', SQZ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX 10 SQZ, PERF @ 198', RIH TO 420' MIX 10 SQZ, PERF @ 75', CIR UP 13 5/8 10 C" UP 13 5/8" TO SURFACE ON BOTH ELD ON DRY HOLE MARKER, TO ME ED DISPOSAL, CLEAN LOCATION	OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL "C" CMT FROM 1,450'- 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS T 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 S" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIRE ALL CEMENT PLUGS CLASS" C	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN, TEST CSG TO 1,500# GOOD, PERF (ATE 1BBL (A) 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR (A) 2,100' SQZ W/ 4 BBLS RAW RESIN W/ (B) 1,450', SQZ 4 BBLS RAW RESIN W/ (B) 1,200', UNABLE TO CIR. PERF (A) 87' FROM 1,100'-1,000'. BOOM GOOD. PERF (B) 570', MIX & SPO' OF FROM 570'-470'. BOOM SQZ, PERF (B) 198', RIH TO 420' MIX (B) SQZ, PERF (B) 198', CIR UP 13 5/8' C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME CED DISPOSAL, CLEAN LOCATION (C", W/ CLOSED LOOP SYSTEM US)	OE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. '2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS IT 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 S" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" 11/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIRI ALL CEMENT PLUGS CLASS " C Spud Date:	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN, TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ 20,100', SQZ 4 BBLS RAW RESIN W/ 20,1200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. BOW GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. SQZ, PERF @ 198', RIH TO 420' MIX "CMT FROM 198'-100'. SYNO SQZ, PERF @ 75', CIR UP 13 5/8 "C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME CED DISPOSAL, CLEAN LOCATION "W/ CLOSED LOOP SYSTEM US Rig Release Date:	OE. Q 2,600' UNABLE TO EST. INJ. RATE, OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL 'C" CMT FROM 1,450'- 1,350'. '2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS If 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 S" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" 11/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIRI ALL CEMENT PLUGS CLASS " C Spud Date:	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN, TEST CSG TO 1,500# GOOD, PERF (ATE 1BBL (A) 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR (A) 2,100' SQZ W/ 4 BBLS RAW RESIN W/ (B) 1,450', SQZ 4 BBLS RAW RESIN W/ (B) 1,200', UNABLE TO CIR. PERF (A) 87' FROM 1,100'-1,000'. BOOM GOOD. PERF (B) 570', MIX & SPO' OF FROM 570'-470'. BOOM SQZ, PERF (B) 198', RIH TO 420' MIX (B) SQZ, PERF (B) 198', CIR UP 13 5/8' C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME CED DISPOSAL, CLEAN LOCATION (C", W/ CLOSED LOOP SYSTEM US)	OM 2,600'-2,500' W/ 60 SX CL "C" CMT FROM 2,100'- 2,000'. 60 SX CL "C" CMT FROM 1,450'- 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS " 25 SX CL "C" CMT FROM 940'- 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420'- 280', SQZ 4 " UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "C REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIR ALL CEMENT PLUGS CLASS" C Spud Date:	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN TO SURFACE SHOWN TO SURFACE SHOWN TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87' FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX "CMT FROM 198'-100'. 15' NO SQZ, PERF @ 75', CIR UP 13 5/8' "C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME ED DISPOSAL, CLEAN LOCATION C", W/ CLOSED LOOP SYSTEM US Rig Release Date:	OM 2,600' UNABLE TO EST. INJ. RATE, OM 2,600' UNABLE TO EST. INJ. RATE, OM 2,600' -2,500' W/ 60 SX CL "C" CMT FROM 2,100' - 2,000'. 60 SX CL 'C" CMT FROM 1,450' - 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS T 25 SX CL "C" CMT FROM 940' - 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420' - 280', SQZ 4 B" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIR ALL CEMENT PLUGS CLASS " C Spud Date: I hereby certify that the information of SIGNATURE Type or print name Monty L. McC	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN, TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ 2,100', SQZ 4 BBLS RAW RESIN W/ 2,1200', UNABLE TO CIR. PERF @ 87 FROM 1,100'-1,000'. BOWN GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. SQZ, PERF @ 198', RIH TO 420' MIX "CMT FROM 198'-100'. SYNO SQZ, PERF @ 75', CIR UP 13 5/8 "C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME ED DISPOSAL, CLEAN LOCATION "W/ CLOSED LOOP SYSTEM US Rig Release Date: TITLE Agent for Charver E-mail address: _ monty mccarv	OM 2,600' UNABLE TO EST. INJ. RATE, OM 2,600' -2,500' W/ 60 SX CL "C" CMT FROM 2,100' - 2,000'. 60 SX CL 'C" CMT FROM 1,450' - 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS T 25 SX CL "C" CMT FROM 940' - 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420' - 280', SQZ 4 BY UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.
10/10-23/16 MI &RU, NDWH & NU WHITAKER W/ NMOCD REQUEST 10/25/16 RIH & TAG CIBP @ 2,830' RIH W/ PKR & SET @ 2,325' INJ RA 10/26/16 MIX & PUMP 4 BBLS OF F 10/27/16 RIH TAG @ 2,430', PERF @ 10/28/16 RIH TAG @ 1,964', PERF @ 10/29/16 RIH TAG @ 1,327', PERF @ RAW RESIN W/ 60 SX CL "C" CMT 10/30/16 RIH TAG @ 972', TEST 2,0 RAW RESIN W/ 60 SX CL "C" CMT 10/31/16 PERF @ 400', UNABLE TO BBLS RAW RESIN W/ 60 SX CL "C" L1/01/16 RIH TAG @ 90', PERF @ 8 4 BBLS RAW RESIN W/ 10 SX CL "C REMOVED 3' BELOW GRADE. WE HAUL ALL FLUIDS TO A REQUIR ALL CEMENT PLUGS CLASS" C Spud Date:	BOP, TEST, RIH DRILL OUT CEMENT TO DRILL DOWN TO SURFACE SHOWN TO SURFACE SHOWN TO SURFACE SHOWN TEST CSG TO 1,500# GOOD, PERF @ ATE 1BBL @ 1,950#. RAW RESIN W/ 60 SX CL "C" CMT FR @ 2,100' SQZ W/ 4 BBLS RAW RESIN W/ @ 1,200', UNABLE TO CIR. PERF @ 87' FROM 1,100'-1,000'. 100# GOOD. PERF @ 570', MIX & SPO' FROM 570'-470'. 10 SQZ, PERF @ 198', RIH TO 420' MIX "CMT FROM 198'-100'. 15' NO SQZ, PERF @ 75', CIR UP 13 5/8' "C" UP 13 5/8" TO SURFACE ON BOTH CLD ON DRY HOLE MARKER, TO ME ED DISPOSAL, CLEAN LOCATION C", W/ CLOSED LOOP SYSTEM US Rig Release Date:	OM 2,600' UNABLE TO EST. INJ. RATE, OM 2,600' UNABLE TO EST. INJ. RATE, OM 2,600' -2,500' W/ 60 SX CL "C" CMT FROM 2,100' - 2,000'. 60 SX CL 'C" CMT FROM 1,450' - 1,350'. 2' UNABLE TO CIR. PERF @ 1,100' SQZ 4 BBLS T 25 SX CL "C" CMT FROM 940' - 800', SQZ 4 BBLS & SPOT 25 SX CL "C" CMT FROM 420' - 280', SQZ 4 B" UNABLE CIR 9 5/8". MIX & CIR 25 SX CL "C" H STRINGS, CUT ALL CASING & ANCHORS & ET WITH RULE 19.15.7.14 NMAC REQUIMENTS. Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.