

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-40312 ✓
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> ✓
2. Name of Operator BTA Oil Producers LLC 260297		6. State Oil & Gas Lease No. V-2564
3. Address of Operator 104 S. Pecos, Midland, TX 79701		7. Lease Name or Unit Agreement Name: Eagle 8806 JV-P ✓
4. Well Location Unit Letter <u>F</u> : <u>1650</u> feet from the <u>north</u> line and <u>1650</u> feet from the <u>west</u> line Section <u>12</u> Township <u>10S</u> Range <u>33E</u> NMPM Lea County ✓		8. Well No. 2H ✓
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3804' GR		9. Pool name or Wildcat Lane; Abo (36671) ✓

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER:

INT TO PA

P&A NR Pm X
P&A R _____

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

BTA P&A'd this well as follows:

04/11/2016 RIM, tag CIBP @ 4580', circ hole w/mud gel, test csg to 500 psi - OK. Dump 25 sx cmt on CIBP 4580'-4333', spot 35 sx cmt 4058'-3712', tag plug @ 3748', spot 25 sx cmt 2721'-2572', spot 25 sx cmt 555'-406', tag @ 410', pump 15 sx surf plug - 60' to surface. Install dry hole marker

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Pam Inskeep TITLE Regulatory Administrator DATE 04/15/2016

Type or print name Pam Inskeep Telephone No. 432-682-3753

(This space for State use)

APPROVED BY Mah Whitcher TITLE P.E.S. DATE 04/20/2016

Conditions of approval, if any: