

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.
30-025-43583

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Black Bear 36 State

8. Well Number 601H

9. OGRID Number
7377

10. Pool name or Wildcat

WC-025 G-09 S253335K; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
EOG Resources, Inc.

3. Address of Operator
P.O. Box 2267 Midland, TX 79702

4. Well Location
Unit Letter A : 250 feet from the North line and 1160 feet from the East line
Section 36 Township 25S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3328' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/02/17 Spud 14-3/4" hole.

5/03/17 Ran 31 jts 10-3/4", 40.5#, J55 STC casing set at 1141'.

5/04/17 Cemented lead w/ 655 sx Class C, 13.5 ppg, 1.76 CFS yield;
tail w/ 250 sx Class C, 14.8 ppg, 1.36 CFS yield.

Circulated 140 bbls cement to surface. WOC 4 hrs. Released surface rig.

6/03/17 Tested 10-3/4" casing to 1500 psi for 30 minutes. Test good. Resumed drilling 8-3/4" hole.

6/10/17 Ran 7-5/8", 29.7#, (24 jts) ECP-110 BTC-SC & (246 jts) ICYP-110 FXL casing set at 11825'.

6/11/17 Cement w/ 600 sx Class H, 15.6 ppg, 1.22 CFS yield; WOC 4 hrs.

Tested casing to 2500 psi for 30 minutes. Test good.

Cement w/ 2500 sx Class C, 14.8 ppg, 1.52 CFS yield. Cement to surface.

Resumed drilling 6-3/4" hole.

Spud Date: 5/02/17

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 6/15/2017

Type or print name Stan Wagner E-mail address: PHONE: 432-686-3689

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 06/20/17
Conditions of Approval (if any):