30-025-44321

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Date: 01/04/18		GAS CA	PTURE PL	AN			
□ Original							
This Gas Capture Plan or new completion (new dril Note: Form C-129 must be sa	l, recomplete to	o new zone, re-fra	ac) activity.			facility flaring/venting for	
Well(s)/Production Facility – Name of facility							
The well(s) that will be low Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	ow. Flared or Vented	Comments	
Ram 3 B2PA State Com #2	70-029-		185' FSL & 560' FEL		NA	ONLINE AFTER FRAC	
Gathering System and Pipeline Notification Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Lucid and will be connected to low/high pressure gathering system located in Lea County, New Mexico. It will require o 'of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides (periodically) to Lucid a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Mewbourne Oil Company and Lucid have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Lucid Processing Plant located in Sec. 25 , Twn. 185 , Rng. 25E , Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.							
flared or vented. During fl	lowback, the flued to product	uids and sand con ion facilities. Gas	tent will be not sales should	nonitored. V	when the prodon as the wel	action tanks and gas will be luced fluids contain minimal ls start flowing through the ed on current information, it	

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines