Form 3160-5 (June 2015)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

٥.	Lease Serial No.
	NMNM122622

BI	UREAU OF LAND MANAGEN	MENT MIMOCD		1.444		
SUNDRY	5. Lease Se NMNM	rial No. 122622				
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals  SUBMIT IN TRIPLICATE - Other instructions on page 2				, Allottee or Tribe Name		
SUBMIT IN	TRIPLICATE - Other instruct	tions on page 2 FEB 1	7. If Unit o	r CA/Agreement, Name and/or No.		
1. Type of Well			8. Well Nan	ne and No. OOD 23 FED COM 703H		
	9. API Wel					
EOG RESOURCES, INC.		-44075				
3a. Address ATTN: STAN WAGNER P.O. BOX 2267 MIDLAND, TX 79702  3b. Phone No. (include area code) Ph: 432-686-3689				10. Field and Pool or Exploratory Area WC-025 S263327G UPPER WC		
4. Location of Well (Footage, Sec., T	11. County	or Parish, State				
Sec 23 T26S R33E Mer NMP	LEA CO	OUNTY, NM				
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION	TYPE OF ACTION					
☐ Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start/Re			
	☐ Alter Casing	☐ Hydraulic Fracturing	□ Reclamation	■ Well Integrity		
Subsequent Report	☐ Casing Repair	■ New Construction	☐ Recomplete	☑ Other Drilling Operations		
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon	☐ Temporarily Aband	on Diffing Operations		
13. Describe Proposed or Completed Ope	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal			
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.  11/19/17 Spud 17-1/2" hole. 11/20/17 Ran 13-3/8", 40.5#, J-55 STC casing set at 1011'. Cement lead w/ 565 sx Class C, 13.5 ppg, 1.76 CFS yield; tail w/ 310 sx Class C, 14.8 ppg, 1.36 CFs yield. Circulated 338 sx cement to surface. WOC 8 hrs. Tested casing to 1500 psi for 30 minutes. Test good. Released surface rig.						
01/02/18 Resumed drilling 12-1/4" hole. 01/04/18 Ran 9-5/8", 40#, J55 LTC (0'-4002') Ran 9-5/8", 40#, HCK55 LTC (4002'-5015') Cement lead w/ 1045 sx Class C, 12.7 ppg, 2.24 CFS yield;						
14. I hereby certify that the foregoing is	true and correct.	56 verified by the BLM Wel	Information System			
	Electronic Submission #4000 For EOG RESC	OURCES, INC., sent to the	Hobbs			
Committed to AFMSS for processing by JENNIFER SANCHEZ on 01/10/2018 ()  Name (Printed/Typed) STAN WAGNER  Title REGULATORY ANALYST						
		AC	CEPTED HUR I	RECORD		
Signature (Electronic S	Submission)	Date 01/09/20	018			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE C 1010						
	,		1			
Approved By	BUREAU OF LAND MAN	Date				
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  Office						
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						
(Instructions on page 2)  ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **						

## Additional data for EC transaction #400056 that would not fit on the form

## 32. Additional remarks, continued

tail w/ 497 sx Class C, 14.8 ppg, 1.34 CPS yield. Circulated 157 bbls cement to surface. Tested casing to 2500 psi for 30 minutes. Test good. 01/05/18 Resumed drilling 8-3/4" hole.