

Submit 1 Copy To Appropriate District
Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-00945

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Artesia Metex Unit

8. Well Number 5

9. OGRID Number
269864

10. Pool name or Wildcat
Artesia QU-GB-SA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

State of New Mexico formerly Canyon E&P Company

3. Address of Operator

1625 N. French Drive Hobbs, NM 88249

4. Well Location

Unit Letter L : 1650 feet from the South line and 990 feet from the West line
Section 24 Township 18S Range 27E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHMENTS

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE _____ TITLE Petroleum Engr Specialist DATE _____

Type or print name Mark Whitaker E-mail address: _____ PHONE: 575-393-6161

For State Use Only

APPROVED BY: Maury Brown TITLE AO/II DATE 2/20/2018
Conditions of Approval (if any)

Canyon E&P Company
Artesia Metex Unit No. 5
30-015-00945
1650' FSL & 990' FWL
UL – L, Sec. 24, T18S, R27E

8 5/8" 24# csg at 492' w/ 65 sx cmt.
Open Hole 492' – 2053'
TD 2053'

1. MIRU plugging equipment. POOH w/ production equipment.
2. Run in hole with tubing to 1850'
3. Spot 50 sx cement. WOC & Tag.
4. POOH to 542'. Pump sufficient cement to circulate to surface.
5. Cut off wellhead 3 feet below ground level.
6. Verify cement to surface on all strings.
7. Install upright P&A marker and cut off anchors.

NOTES: Mud laden fluid consists of 9.5 ppg with 25 sx salt gel per 100 bbls of fluid. If casing will not hold pressure, contact the OCD for instructions prior to preceding with P&A.

Canyon E P Company
Artesia Metex Unit No. 5

CURRENT

30-015-00945

8 5/8" 24# @ 492' w/ 65 sx

NOTES:

180 Qts Nitro 2032' - 2053'

Wtr Sands 180'-85' & 260'-65'

Open Hole from 492' to TD

TD 2053'

Canyon E P Company
Artesia Metex Unit No. 5

CURRENT

30-015-00945

CUT OFF WELLHEAD 3' BELOW GL
VERIFY CEMENT TO SURFACE ALL STRINGS
INSTALL P&A MARKER

8 5/8" 24# @ 492 w/ 65 sx

POOH TO 542'. FILL TO SURFACE W/ CMT

SPOT 50 SX CMT @ 1850' WOC & TAG
CIRC HOLE W/ MLF

Open Hole from 492' to TD

TD 2053'