District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

HOBBS OCD

MAY 142018

Pate: 05/11/18		GAS CAPTURE PLAN			RECEIVED	
☑ Original☐ Amended - Reason for	Operator & OGRID No.: Mewbourne Oil Company - 14744 Amendment:					

This Gas Capture Plan out new completion (new drill,				reduce we	1/production	facility flaring/venting for
Note: Form C-129 must be suit	mitted and app	roved prior to excee	ding 60 days a	llowed by Rule	e (Subsection A	of 19.15.18.12 NMAC).
Well(s)/Production Facili	ty – Name of	facility				
The well(s) that will be loc	ated at the pro		re shown in	the table bel	ow.	
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
El Mar 21 W1CN Fed Com #31	30-025-43072	C-21-26S-R33E	90 FNL & 1350 FWL	0	0	On line after frac
Gathering System and Pi	neline Notific	eation				
Well(s) will be connected to			owback oper	ations are c	omplete, if g	as transporter system is in
place. The gas produced from production facility is dedicated to Energy Transfer and will be connected to						
low/high pressure gathering system located in County, New Mexico. It will require of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides						
						r wells that are scheduled to
						have periodic
						wells will be processed at
Energy Transfer						County, New Mexico.
The actual flow of the gas w	ill be based on	compression oper	ating parame	ters and gathe	ering system p	oressures.
Flowback Strategy After the fracture treatmen	t/completion of	operations, well(s)) will be pro	duced to tem	porary produ	action tanks and gas will be
flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal						

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on __Energy Transfer_ system at that time. Based on current information, it

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines