and the second			
Submit 1 Copy To Appropriate District State of New Mexico			Form C-103
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		Revised August 1, 2011 WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505	30-005-60197	
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410			5. Indicate Type of Lease
District IV - (505) 476-3460		STATE X FEE	
1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCHCP PROPOSALS.) 1. Type of Well: Oil Well X Gas Well Other HOBBS			<ul><li>7. Lease Name or Unit Agreement Name</li><li>Double L Queen Unit</li></ul>
PROPOSALS.)	Gas Well Other LOBE	35 000	8. Well Number 1G
<ol> <li>1. Type of Well. On Well X</li> <li>2. Name of Operator</li> <li>State of New Mexico formerly Can</li> </ol>	von F&P Company	162018	9. OGRID Number 269864
3. Address of Operator	os, NM 88240	ECEIVED	10. Pool name or Wildcat Double L; Queen (Assoc)
4. Well Location			·
Unit LetterL:			_330feet from theWestline
Section 24	Township 14S 1 11. Elevation (Show whether DR,	Range 29E RKB. RT. GR. etc.	NMPM Chaves County
			, 
	PLL	SUB REMEDIAL WOR	
TEMPORARILY ABANDON	CH. INT TO PA	COMMENCE DR	
DOWNHOLE COMMINGLE	P&A R		
OTHER:		OTHER:	
	ork). SEE RULE 19.15.7.14 NMAC		d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of
	SEE ATTA	CHED	
I hereby certify that the information	above is true and complete to the be	st of my knowledg	e and belief.
SIGNATURE	TITLE		DATE
	E-mail address	:	PHONE:
APPROVED BY: Mall	Shitely_TITLE P.E	.S.	DATE 05/16/2018
Conditions of Approval (if any):			

## Plugging Report Double L Queen Unit #1G 30-005-60197

5/10/2018 Cleared location and installed one temporary anchor. Rigged up and SION.

5/11/2018 Unseated pump and laid down 73 ¾" rods. Could not get the cap off of the 8 1/8" Hinderliter wellhead. Unscrewed the wellhead head with the tubing hanging in the well. Laid down the wellhead and the first joint of tubing. Installed a 5 ½" X 8 5/8" Larkin wellhead. Installed BOP and POOH with the tubing. 56 joints 2 3/8" tubing in the hole. Made scrapper run to 1782' and POOH. SION.

5/14/2018 Set CIBP at 1780'. Circulated MLF. Fluid started leaking around the wellhead when fluid hit surface. Move in vacuum truck to catch the fluid. Spotted 50 sx cement on top of CIBP. POOH with tubing. Set packer on 1 stand of pipe at 60'. Pressured up below packer to 500#. Casing good below the packer. RIH to 373' and circulated cement to surface. Took 70 sx to get cement to surface. Cement was coming out of the hole in the 5 ½" casing below the wellhead and from the ground outside of the 8 5/8" casing. Rigged down. Dug out cellar and cut off the wellhead. Cement was to surface inside the 8 5/8" casing and filled up the 5 ½" casing with 5 sx. Installed marker, cut off anchors, cleaned the pit and cleared the location.