

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1288

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

Revised July 18, 2013

WELL API NO.

3002545062

5. Indicate Type of Lease

STATE ☒ FEE ☒ PRIVATE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

MAGNOLIA 15

8. Well Number 302H

9. OGRID Number 7377

10. Pool name or Wildcat

BONE SPRING-PA'D

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator EOG RESOURCES

3. Address of Operator P O BOX 2267, MIDLAND TX 79702

4. Well Location

Unit Letter M : 329 feet from the SOUTH line and 842 feet from the WEST line

Section 15 Township 26S Range 33E NMPM County LEA COUNTY

11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3295 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: DRILL CSG ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/26/18 SPUD-17 1/2" HOLE

Surface Casing @ 1,076'

Run: 13-3/8" 54.5# J-55 STC

Lead Cement w/ 735 sx Class C (13.5 ppg, 1.76 yld), Tail w/ 200 sx Class C (14.8 ppg, 1.36 yld)

Test casing to 1,500 psi for 30 min - bad test. Circ 425 sx cement to surface- waiting to P&A

Spud Date:

08/26/18

Rig Release Date:

08/31/18

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Emily Follis TITLE Sr. Regulatory Administrator DATE 10/01/18

Type or print name Emily Follis E-mail address: emily_follis@eogresources.com PHONE: 432-848-9163

For State Use Only

APPROVED BY: Mary Brown TITLE AO/I DATE 10/9/2018

Conditions of Approval (if any):