Submit 1 Copy To Appropriate District Office	State of New Me			Form C-103
<u>District I</u> – (575) 393-6161	Energy Minerals and Natural Resources		TITELY A DV	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	Energy Minerals and Natural Resources OIL CONSERVATION DIVISION OF 1220 South St. Francis Dr. Santa Fe, NM 87505		WELL API 1 30- 025-	
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION			Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUINDRY NOTICES AND SEPORTS ON WELLS		STATE FEE	
District IV - (505) 476-3460 Santa Fe, NM 87505			6. State Oil	& Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505				
SUNDAT NOTICES ALL WEEFORTS ON WELLS			7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO BRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Hodges B	
PROPOSALS.)			8. Well Number	
1. Type of Well: Oil Well Gas Well Other 2. Name of Operator			9. OGRID Number	
OXY USA Inc.			9. OGRID Number 16696	
3. Address of Operator			10. Pool name or Wildcat	
P.O. Box 50250 Midland, TX 79710			Justis-Tubb-Drinkand	
4. Well Location				
Unit Letter K: 1642 feet from the South line and 1660 feet from the west line				
Section Township 255 Range 37E NMPM County Lea				
11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
	3(10			· · · · · · · · · · · · · · · · · · ·
12. Check Appr	opriate Box to Indicate N	ature of Notice. I	Report or O	ther Data
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRII				☐ ALTERING CASING ☐☐☐ ☐ PAND A☐☐☐
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT				
DOWNHOLE COMMINGLE		o ionia o Emeri	,	
CLOSED-LOOP SYSTEM				
OTHER: Set CIBP, Run		OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of				
proposed completion or recompletion.				
TD-7941'M 7668'V PBTD-6584' Perfs-6240-6304' CIBP-6694'				
OXY USA WTP LP respectfully requests to temporarily abandon this well. It is currently being evaluated for future				
recompletion.				
1. POOH w/ prod equipment, RIH & set CIBP @ 6190', Dump Bail 5sx cmt to +/-6140', WOC-Tag				
2. Notify NMOCD of casing integrity test 24hrs in advance.				
3. RU pump truck, circulate well with treated water, pressure test casing to 500# for 30 min.				
Condition of Approval: notify				
Spud Date: Rig Release Date: OCD			Hobbs office 24 hours	
Nig Keleuse Bate.			unning MIT Test & Chart	
		brior of t	anning Mi	1 lest & Chart
I hereby certify that the information above	e is true and complete to the be	est of my knowledge	and belief.	
	•	, .		
SIGNATURE OF THE	TITLE Sr.	D		DATE 10130/18
SIGNATURE TITLE Sr. Regulatory Advisor DATE 101 SO 18				
Type or print name David Stewart	E-mail address:	david_stewart@	oxy.com P	PHONE: <u>432-685-5717</u>
For State Use Only				
APPROVED BY: 1 VALUE TITLE 170/1 DATE 11/5/2018				
Conditions of Approval (if any)				

A

OXY USA Inc. - Proposed Hodges B #5 API No. 30-025-11386

> 17-1/2" hole @ 499' 13-3/8" csg @ 498' w/ 540sx-TOC-Surf-Circ 12-1/4" hole @ 3405' 9-5/8" csg @ 3405' DVT @ 1036' 1st w/ 2400sx-TOC-1595'-TS 2nd w/ 1000sx-TOC-Surf-Circ Whipstock @ 4924' CIBP @ 6190' DB w/ 5sx Perfs @ 6240-6304' CIBP @ 6694' w/15sx to 6584' Tagged 6-1/8" hole @ 7941' 4-1/2" csg @ 7904' DVT @ 4918' 1st w/210sx-TOC-4915'-Circ 2nd w/230sx-TOC-150'-CBL CIBP @ 7184' w/ 25sx Perfs @ 7230-7240' CIBP @ 7350' w/ 4sx Perfs @ 7380-7390' 7941'M 7668'V

> > TD-8500

5/11-Sqz csg lk @ 3844-3966' w/ 180sx 1/12-Sqz csg lk @ 3876-4002' w/ 300sx

CIBP @ 4924' 5/11-25sx @ 5175-5075' 7/73-Perfs @ 5208-5368'

1/76-Perfs @ 5421-5793' 5/11-25sx @ 5875-5775' 6/82-Sqz perfs 5208-5793' w/ 400sx

5/11-25sx @ 6450-6350'

5/11-CIBP @ 7100' w/ 25sx 2/11-CIBP @ 7178' 6/82-Perfs @ 7147-7172' 4/62-Perfs @ 7186-7199'

8-3/4" hole @ 8500'
7" csg @ 7250'
DVT @ 5742'
1st w/ 520sx-TOC-5737'-Circ
2nd w/ 390sx-TOC-2950'-CBL

4/62-25sx @ 8500-8425'

OXY USA Inc. - Current Hodges B #5 API No. 30-025-11386

> 17-1/2" hole @ 499' 13-3/8" csq @ 498' w/ 540sx-TOC-Surf-Circ 12-1/4" hole @ 3405' 9-5/8" csg @ 3405' **DVT @ 1036'** 1st w/ 2400sx-TOC-1595'-TS 2nd w/ 1000sx-TOC-Surf-Circ Whipstock @ 4924' Perfs @ 6240-6304' CIBP @ 6694' w/15sx to 6584' Tagged 6-1/8" hole @ 7941' 4-1/2" csg @ 7904' DVT @ 4918' 1st w/210sx-TOC-4915'-Circ 2nd w/230sx-TOC-150'-CBL CIBP @ 7184' w/ 25sx Perfs @ 7230-7240' CIBP @ 7350' w/ 4sx Perfs @ 7380-7390' 7941'M 7668'V

> > TD-8500

5/11-Sqz csg lk @ 3844-3966' w/ 180sx 1/12-Sqz csg lk @ 3876-4002' w/ 300sx

CIBP @ 4924' 5/11-25sx @ 5175-5075' 7/73-Perfs @ 5208-5368'

1/76-Perfs @ 5421-5793' 5/11-25sx @ 5875-5775' 6/82-Sqz perfs 5208-5793' w/ 400sx

5/11-25sx @ 6450-6350'

5/11-CIBP @ 7100' w/ 25sx 2/11-CIBP @ 7178' 6/82-Perfs @ 7147-7172' 4/62-Perfs @ 7186-7199'

8-3/4" hole @ 8500'
7" csg @ 7250'
DVT @ 5742'
1st w/ 520sx-TOC-5737'-Circ
2nd w/ 390sx-TOC-2950'-CBL

4/62-25sx @ 8500-8425'