

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

June 19, 2008

<p>SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>WELL API NO. 30-025-31450</p>
<p>1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/></p>		<p>5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> State Oil & Gas Lease No.</p>
<p>2. Name of Operator Chevron Midcontinent, LP</p>		<p>7. Lease Name or Unit Agreement Name West Lovington Unit</p>
<p>3. Address of Operator 6301 Deauville Blvd., Midland, TX 79706</p>		<p>8. Well Number 85</p>
<p>4. Well Location Unit Letter N : 140 feet from the SOUTH line and 2625 feet from the WEST line Section 5 Township 17S Range 36E NMPM County Lea</p>		<p>9. OGRID Number 241333</p>
<p>11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3890' GL, 3,900' KB</p>		<p>10. Pool name or Wildcat West Lovington Upper San Andres</p>

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.
Restoration Due By 11-14-2019

N ☐
☐
☐
☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/8/2018 MIRU APWS Rig. Check PSI on well. Pump 20bbbls brine down tbg. Tbg on vacuum. PU on rod. LD polish rod. Strip on rod BOP. TOOHD LD rods. RU tbg. RD rod tongs. ND BOP. ND WH. PU on B-1. Reinstall B-1. RU on csg & attempt to kill well. RIH w/ tbg to 2440' & punch 6 holes. POOH. RD W/L. Pump 20bbbls of brine down the tbg to kill the well. ND B-1 and NU BOP. RU work floor. **11/9/18** Check PSI on well. Pump 20bbbls of brine down tbg to kill well. Release tbg anchor. TOOHD LD rods. Cut parted rod. X over to tbg. TOOHD w/ tbg. RU W/L. RIH & Set CIBP @ 4670'. POOH. RD W/L. **11/12/18** Check well PSI. All csg stings 0. Change out BOP rams to 2.375". Remove old tbg string & move in 2.375" tbg string. PU tbg. **11/13/18** Check pressure on well. PU tbg & tag top of CIBP @ 4671'. PT csg to 500#/15min. Test - OK. **Notified NMOCD (Mark Whitaker) for approval to move forward with job. Approval received.** Mix & pump 3sxs Salt Gel w/ 12bbbls 10ppg brine. Pumped Plug #1 - Mix & pump 85sxs Class C Neat cmt f/ 4671' t/ 3831'. Displaced w/ 14bbbls FW. POOH w/ tbg @ 3407'. Mix & pump 7sxs Salt gel w/ 28bbbls 10ppg brine. Pumped Plug #2 - Mix & pump 75sxs Class C Neat cmt f/ 3407' t/ 2667'. Displaced w/ 10bbbls FW. POOH w/ tbg @ 1550'. Reverse circ w/ 20bbbls FW. **11/14/18** Check PSI on well. Pumped Plug #3 - Mix & pump 100sxs cmt from 1550' - Surface. POOH w/ tbg. ND BOP. Topped well off with 33sxs Class C cmt from Surface. TOC @ 2' below WH. Installed B-1 flange. RDMO.

The subject well was P&A'd on 11/14/2018 per the above rig detail and the attached wellbore diagram.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Well Abandonment Engineer, Attorney-in-Fact DATE 12/4/18

Type or print name Howie Lucas E-mail address: howie.lucas@chevron.com PHONE: (832) 588-4044
For State Use Only

APPROVED BY: [Signature] TITLE P.E.S. DATE 12/04/2018
Conditions of Approval (if any):

West Lovington Unit #85
Plugged WBD

Lovington Upper San Andres West
140' FSL & 2625' FWL, Section 5, T17S, R36E
Lea County, NM/ API # 30-025-31450

Spud: 2/27/1992
Completed: 3/05/1992
Elevation: 3890' GL

Surface Csg: 8 5/8", 24# csg set @
1500'
Cmt w/ 600sxs Class C, circulated

(12 1/4" hole)

Plug #3: Mix & pump 100sxs Class
C Neat cmt from 1550' – Surface
(topped well off w/ 33sx Class C
after TOOH)

Plug #2: Mix & pump 75sxs Class C
Neat cmt from 3407'

Plug #1: Mix & pump 85sxs Class C
Neat cmt.
Set 5 1/2" CIBP @ 4671'

Perforations:
4716' - 5142'

Prod Csg 5 1/2" 15.5# csg set @
5230' Cmt w/ 1050sxs Class C cmt,
circulated

(7 7/8" hole)

PBTD @ 5183'
TD @ 5230'

