Submit 1 Copy To Appropriate District Office	State of New Mexico			Form C-103	
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240			es 「	WELL API NO.	Revised August 1, 2011
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	rict II - (575) 748-1283 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION		N	30-015-00990	/
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.			5. Indicate Type of Lea	ase
<u>District IV</u> – (505) 476-3460	Santa Fe, NM 8/505			STATE X	FEE ′
1220 S. St. Francis Dr., Santa Fe, NM 87505				6. State Oil & Gas Lea	se No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				7. Lease Name or Unit Agreement Name	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH				Artesia Metex Unit	/
PROPOSALS.) 1. Type of Well: Oil Well X	ROPOSALS.) Type of Well: Oil Well X Gas Well Other HOBBS OCD				
Name of Operator State of New Mexico formerly Can		DEC 05201	ix I	9. OGRID Number 269864	
3. Address of Operator	,	-		10. Pool name or Wild	cat
1625 N. French Drive Hobbs, 1	NM 88240	RECEIVE	D	Artesia QU-GB-SA	· ·
4. Well Location					
Unit LetterD_:_	330feet from the	North line and	ıd9	990feet from the	_Westline
Section 36	Township	18S Range 2	27E	NMPM Eddy	County
The high state of the	11. Elevation (Show whe	ther DR, RKB, RT, GR	R, etc.)	**	W. de la
NOTICE OF IN			SUBS	EQUENT REPOR	RT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI					ERING CASING 🔲
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN					ID A
DOWNHOLE COMMINGLE	Moeth Le oom L				
OTHER:	atad amanatiana (Classica	OTHER:			
13. Describe proposed or comp of starting any proposed wo proposed completion or rec	rk). SEE RULE 19.15.7.14				
	SEE A	ATTACHED			
I hereby certify that the information	above is true and complete	to the best of my know	wledge	and belief.	
SIGNATURE	TITLE			DATE	
Type or print name For State Use Only	E-mail address:			PHONE:	

APPROVED BY: Youk Conditions of Approval (if any):

DATE 12/05/2018

Canyon E&P Company Artesia Metex Unit #57 30-015-00990 330' FNL & 990' FWL UL-D, Sec 36, T18S, R27E

8 5/8" csg @ 479' with 50 sx cmt

Open hole: 479'-2025'

- 1. MIRU and lay down production equipment.
- 2. RIH with tubing and spot 50 sx cement at 1350'
- 3. Tag cement and circulate MLF.
- 4. POOH to 529' and circulate cement to surface.
- 5. Cut off 3' below ground level and verify cement is to surface.
- 6. Install upright marker and cut off anchors.

State of New Mexico for Canyon E&P Company Artesia Metex Unit #57 API 30-015-00990 WBD Before PA 8 5/8" casing set at 479' Cemented w/50 sx TD 2025' Open Hole 479'-2025'

State of New Mexico for Canyon E&P Company Artesia Metex Unit #57 API 30-015-00990 WBD After PA 8 5/8" casing set at 479' Cemented w/50 sx Circulate cement to surface from 529' Spot 50 sx cement at 1350'. WOC and tag. Circulate MLF TD 2025' Open Hole 479'-2025'