Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
<u>District I</u> – (575) 393-6161	Conergy, Minerals and Natural Resources	Revised July 18, 2013 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.	3002545369
811 S. First St., Artesia, NAT 88210 <u>District III</u> – (505) 334-6(78	ONSERVATION DIVISION	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87400 District IV - (505) 476-3460 Santa Fe, NM 87505		STATE FEE
District IV — (505) 476-3460 SP 1220 S. St. Francis Dr., Santa Fe, NM	Sainta Pe, NWI 87303	6. State Oil & Gas Lease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Caravan 28 State Com
1. Type of Well: Oil Well Gas Well Other		8. Well Number 601h
2. Name of Operator EOG RESOURCES		9. OGRID Number 7377
3. Address of Operator		10. Pool name or Wildcat
P O BOX 2267, MIDLAND TX 79702		96682 TRISTE DRAW BS, EAST
4. Well Location Unit Letter C: 483 feet from the NORTH line and 1444 feet from the WEST line		
Section 28 Township 24S Range 33E NMPM County LEA		
	11. Elevation (Show whether DR, RKB, RT, GR, etc.	•
3524' GL		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
	PLUG AND ABANDON REMEDIAL WOR	
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☑ P AND A ☐		
	MULTIPLE COMPL	T JOB 🗵
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM		
OTHER:	<u> </u>	LL CSG [X]
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
12/21/18 Spud 12-1/4" Hole		
12/21/18 Surface Casing @ 1,298' Run 9-5/8" 40# J-55 LTC		
Lead Cement w/ 580 sx Class C(1.76 yld, 13.5 ppg), Tail w/ 90 sx Class C (1.36 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min - Good Circ 303 sx cement to surface		
12/26/18 - 8-3/4" HOLE		
Intermediate Casing @ 11,615' Run 7-5/8", 29.7#, HCP-110 BTC SCC (0' - 992')		
Run 7-5/8", 29.7#, HCP-110 MO-FXL (992' - 11,615') Lead Cement w/ 440 sx Class C (3.58 yld, 9.0 ppg), follow w/180 sx Class C (2.54 yld, 11.0 ppg), Tail w/ 180 sx Class C (1.11 yld, 14.2 ppg)		
Test casing to 2,500 psi for 30 min - Good Did not circ cement to surface, TOC @ 3,307' by Calc Resume Drilling		
Spud Date: 12/21/19	Rig Release Date:	
12/21/18	Ng Neleuse Date.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE // TITLE Sr. Regulatory Administrator DATE 01/08/2019		
Type or print name Emily Follis	E-mail address: emily_follis@e	eogresources.comONE: 432-848-9163
For State Use Only 1990uBug unajonad		
APPROVED BY:	TITLE 133uinud mus	DATE 01/14/19
Conditions of Approval (if any):		•