District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

Date: 1/24/18

State of New Mexico
Energy, Minerals and Natural Resources partment

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Original to Appropriate District Office



GAS CAPTURE PLAN

×	Original		Operator	& OGRID	No.:(Cimarex Ener	gy Co- 215099	
	Amended - Reason fo	r Amendmen	t:					
	Gas Capture Plan o completion (new dri		-	-	o reduce we	ll/production	facility flaring/ventir	g for
Note	: Form C-129 must be s	ubmitted and a	pproved prior to excee	ding 60 days d	ıllowed by Rul	e (Subsection A	of 19.15.18.12 NMAC).	
<u>We</u> l	ll(s)/Production Fac	ility – Name	of facility					
The	well(s) that will be le	ocated at the p	production facility a	re shown in	the table bel	ow.		
	Well Name	API	Well Location	Footages	Expected	Flared or	Comments	7
		1	(III CTD)	I	MCE/D	Vented		

Gathering System and Pipeline Notification

Pending

70-025-45501

7-20S-35E

Lea 7 Federal Com 8H

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Gas Transporter and will be connected to Gas Transporter low/high pressure gathering system located in Lea County, New Mexico. It will require 141 'of pipeline to connect the facility to low/high pressure gathering system. Operator provides (periodically) to Gas Transporter a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Operator and Gas Transporter have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Gas Transporter Processing Plant located in Sec 36-19S-36E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

444 FSL &

1697 FWL

1600

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Transporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines